USAARL Report No. 94-41

Whole-body Vibration Assessment of the M1070 Heavy Equipment Transporter

Volume 2

By

Tammy L. Simmons
Barclay P. Butler
Nabih M. Alem
Bradley S. Erickson

Aircrew Protection Division

August 1994

Approved for public release; distribution unlimited.

United States Army Aeromedical Research Laboratory
Fort Rucker, Alabama 36362-0577

Notice

Qualified requesters

Qualified requesters may obtain copies from the Defense Technical Information Center (DTIC), Cameron Station, Alexandria, Virginia 22314. Orders will be expedited if placed through the librarian or other person designated to request documents from DTIC.

Change of address

Organizations receiving reports from the U.S. Army Aeromedical Research Laboratory on automatic mailing lists should confirm correct address when corresponding about laboratory reports.

Disposition

Destroy this document when it is no longer needed. Do not return it to the originator.

Disclaimer

The views, opinions, and/or findings contained in this report are those of the author(s) and should not be construed as an official Department of the Army position, policy, or decision, unless so designated by other official documentation. Citation of trade names in this report does not constitute an official Department of the Army endorsement or approval of the use of such commercial items.

Human use

Human subjects participated in these studies after giving their free and informed voluntary consent. Investigators adhered to AR 70-25 and USAMRDC Reg 70-25 on Use of Volunteers in Research.

Reviewed:

KEVIN T. MASON
LTC, MC, MFS
Director, Aircrew Protection Division

ROGER W. WILEY, O.D., Ph.D.
Chairman, Scientific Review Committee

Released for publication:

DENNIS F. SHANAHAN
Colonel, MC, MFS
Commanding

Unclassified
SECURITY CLASSIFICATION OF THIS PAGE

REPORT DOCUMENTATION PAGE

Form Approved
OMB No. 0704-0188

1a. REPORT SECURITY CLASSIFICATION Unclassified	1b. RESTRICTIVE MARKINGS
2a. SECURITY CLASSIFICATION AUTHORITY 2b. DECLASSIFICATION / DOWNGRADING SCHEDULE	3. DISTRIBUTION / AVAILABILITY OF REPORT Approved for public release, distribution unlimited
4. PERFORMING ORGANIZATION REPORT NUMBER(S) USAARL Report No. 94-41, Volume 2	5. MONITORING ORGANIZATION REPORT NUMBER(S)
6a. NAME OF PERFORMING ORGANIZATION U.S. Army Aeromedical Research Laboratory 6b. OFFICE SYMBOL (If applicable) SGRD-UAD-IV	7a. NAME OF MONITORING ORGANIZATION U.S. Army Medical Research, Development, Acquisition and Logistics Command
6c. ADDRESS (City, State, and ZIP Code) P.O. Box 620577 Fort Rucker, AL 36362-0577	7b. ADDRESS (City, State, and ZIP Code) Fort Detrick Frederick, MD 21702-5012
8a. NAME OF FUNDING / SPONSORING ORGANIZATION 8b. OFFICE SYMBOL (If applicable)	9. PROCUREMENT INSTRUMENT IDENTIFICATION NUMBER
8c. ADDRESS (City, State, and ZIP Code)	10. SOURCE OF FUNDING NUMBERS

PROGRAM ELEMENT NO.	PROJECT NO.	TASK NO.	WORK UNIT ACCESSION NO.
62787A	30162787A878	FA	145

11. TITLE (Include Security Classification)
Whole-body vibration assessment of the M1070 Heavy Equipment Transporter

12. PERSONAL AUTHOR(S)
Tammy L. Simmons, Barclay P. Butler, Nabih M. Alem and Bradley S. Erickson

13a. TYPE OF REPORT	13b. TIME COVERED	14. DATE OF REPORT (Year, Month, Day)	15. PAGE COUNT
	FROM _____ TO _____	1994 August	187

16. SUPPLEMENTARY NOTATION

17. COSATI CODES

FIELD	GROUP	SUB-GROUP
05	09	
20	11	

18. SUBJECT TERMS (Continue on reverse if necessary and identify by block number)
Whole-body vibration, health hazard assessment, exposure limits, tactical vehicles, terrain, crewmembers

19. ABSTRACT (Continue on reverse if necessary and identify by block number)

An evaluation of all new tactical vehicles and aircraft is required to assess potential whole-body vibration (WBV) health hazards to crewmembers. As requested by the U.S. Army Environmental Hygiene Agency (USAEHA), a health hazard assessment (HHA) was performed by the U.S. Army Aeromedical Research Laboratory (USAARL) on the M1070 Heavy Equipment Transporter System (HETS). The HETS was tested on three cross-country courses at Aberdeen Proving Ground (APG), MD, by the U.S. Army Combat Systems Test Activity (USACSTA), in coordination with the Response and Tolerance Branch of USAARL. The M1070 HETS was tested with a M1000 trailer in a loaded and unloaded configuration. The loaded configuration was obtained by placing an M1 tank on the bed of the M1000 trailer. The unloaded configuration consisted of a M1070 tractor with an empty M1000 trailer. While operating the HETS in its intended operational environment, the front passenger was exposed to an overall risk assessment code of 5. This consisted of an overall assignment of hazard severity category IV and hazard probability level D.

Volume 1 describes the tests and discusses the results. Volume 2 contains Appendix B, the data plots and graphs.

20. DISTRIBUTION / AVAILABILITY OF ABSTRACT ☒ UNCLASSIFIED/UNLIMITED ☐ SAME AS RPT. ☐ DTIC USERS	21. ABSTRACT SECURITY CLASSIFICATION Unclassified	
22a. NAME OF RESPONSIBLE INDIVIDUAL Chief, Science Support Center	22b. TELEPHONE (Include Area Code) 205-255-6907	22c. OFFICE SYMBOL SGRD-UAX-SI

DD Form 1473, JUN 86 Previous editions are obsolete.

SECURITY CLASSIFICATION OF THIS PAGE
Unclassified

Table of contents

Appendix B: ISO 2631 data plots and graphs 3

==========

This page left blank intentionally.

==========

Appendix B.

ISO 2631 data plots and graphs.

USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)

RUN-01 Driver

8-OCT-93 16:14:14

1: **HET Ride Quality**
2: **Oct 4, 1993**
3: **Paved**
4: **Driver**
5: **25 mph**
6: **Loaded**

Third-octave bands with greatest weighted RMS accelerations (m/s^2)

Durations of WBV exposure before reaching ISO limits* (given in hours:minutes)

X: Longitudinal

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
2.53	**0.0800**	**0.0633**	**9:25**	**38:45**	**82:37**
6.37	0.1700	0.0534	11:48	47:00	98:52
3.14	0.0700	0.0446	14:49	57:21	119:00
5.05	0.0900	0.0356	19:37	73:07	149:30
7.98	0.1100	0.0276	26:45	95:45	192:30

Y: Transverse

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
2.53	**0.1100**	**0.0871**	**6:05**	**26:45**	**58:36**
3.14	0.1000	0.0637	9:19	38:30	82:07
7.98	0.1700	0.0426	15:42	60:15	124:45
1.61	0.0300	0.0300	24:08	87:45	177:15
2.02	0.0300	0.0296	24:30	88:45	179:30

Z: Vertical

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
2.53	**0.4500**	**0.3576**	**1:07**	**6:46**	**16:45**
3.14	0.3200	0.2835	1:39	9:15	22:15
2.02	0.1700	0.1209	6:09	27:00	59:06
7.98	0.0900	0.0900	9:12	38:02	81:15
6.37	0.0700	0.0700	12:49	50:30	105:45

* International Standards Organization ISO 2631:

Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)

RUN-01 Front

8-OCT-93 16:14:14

1: **HET Ride Quality**
2: **Oct 4, 1993**
3: **Paved**
4: **Front**
5: **25 mph**
6: **Loaded**

Third-octave bands with greatest weighted RMS accelerations (m/s^2)

Durations of WBV exposure before reaching ISO limits* (given in hours:minutes)

X: Longitudinal

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
2.53	**0.0900**	**0.0712**	**8:02**	**33:51**	**72:52**
6.37	0.1800	0.0565	10:56	44:02	93:15
3.14	0.0800	0.0510	12:30	49:30	103:45
5.05	0.0900	0.0356	19:37	73:07	149:30
7.98	0.1200	0.0301	24:07	87:30	177:00

Y: Transverse

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
2.53	**0.0700**	**0.0554**	**11:12**	**45:00**	**95:00**
7.98	0.1600	0.0401	16:58	64:22	132:45
3.14	0.0600	0.0382	18:00	67:45	139:15
6.37	0.0700	0.0220	34:47	121:00	240:00
1.61	0.0200	0.0200	38:45	133:15	262:30

Z: Vertical

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
2.53	**0.5800**	**0.4610**	**0:37**	**4:43**	**12:08**
3.14	0.4700	0.4164	0:47	5:28	13:49
2.02	0.1700	0.1209	6:09	27:00	59:06
7.98	0.0900	0.0900	9:12	38:02	81:15
5.05	0.0700	0.0700	12:49	50:30	105:45

* International Standards Organization ISO 2631:

Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)

RUN-01 Roadside

8-OCT-93 16:14:14

1: **HET Ride Quality**
2: **Oct 4, 1993**
3: **Paved**
4: **Roadside**
5: **25 mph**
6: **Loaded**

Third-octave bands with greatest weighted RMS accelerations (m/s^2)

Durations of WBV exposure before reaching ISO limits* (given in hours:minutes)

X: Longitudinal

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
6.37	**0.2800**	**0.0879**	**6:01**	**26:25**	**58:06**
5.05	0.1400	0.0554	11:12	45:00	95:00
7.98	0.1700	0.0426	15:42	60:15	124:45
2.53	0.0500	0.0396	17:15	65:15	134:15
2.02	0.0300	0.0296	24:30	88:45	179:30

Y: Transverse

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
2.53	**0.0900**	**0.0712**	**8:02**	**33:51**	**72:52**
3.14	0.0800	0.0510	12:30	49:30	103:45
7.98	0.1600	0.0401	16:58	64:22	132:45
6.37	0.0900	0.0283	25:55	93:22	188:00
5.05	0.0700	0.0277	26:32	95:15	191:30

Z: Vertical

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
2.53	**0.3500**	**0.2782**	**1:44**	**9:30**	**22:47**
3.14	0.2600	0.2304	2:20	12:11	28:30
6.37	0.2000	0.2000	2:56	14:34	33:36
7.98	0.1300	0.1300	5:33	24:47	54:36
5.05	0.1100	0.1100	7:01	30:10	65:37

* International Standards Organization ISO 2631:
Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)

RUN-01 Curbside

8-OCT-93 16:14:14

1: **HET Ride Quality**
2: **Oct 4, 1993**
3: **Paved**
4: **Curbside**
5: **25 mph**
6: **Loaded**

Third-octave bands with greatest weighted RMS accelerations (m/s^2)

Durations of WBV exposure before reaching ISO limits* (given in hours:minutes)

X: Longitudinal

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
6.37	**0.2600**	**0.0816**	**6:39**	**28:52**	**63:00**
5.05	0.1400	0.0554	11:12	45:00	95:00
2.53	0.0500	0.0396	17:15	65:15	134:15
7.98	0.1500	0.0376	18:22	69:00	141:30
2.02	0.0300	0.0296	24:30	88:45	179:30

Y: Transverse

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
2.53	**0.0700**	**0.0554**	**11:12**	**45:00**	**95:00**
3.14	0.0600	0.0382	18:00	67:45	139:15
7.98	0.1500	0.0376	18:22	69:00	141:30
6.37	0.1000	0.0314	22:52	83:37	169:30
5.05	0.0700	0.0277	26:32	95:15	191:30

Z: Vertical

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
2.53	**0.4700**	**0.3735**	**1:00**	**6:22**	**15:52**
3.14	0.3800	0.3367	1:15	7:20	18:02
6.37	0.2100	0.2100	2:43	13:42	31:45
5.05	0.1300	0.1300	5:33	24:47	54:36
2.02	0.1400	0.0996	8:03	33:51	73:00

* International Standards Organization ISO 2631:

Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)

RUN-02 Driver

8-OCT-93 16:14:15

1: **HET Ride Quality**
2: **Oct 4, 1993**
3: **Paved**
4: **Driver**
5: **30 mph**
6: **Loaded**

Third-octave bands with greatest weighted RMS accelerations (m/s^2)

Durations of WBV exposure before reaching ISO limits* (given in hours:minutes)

X: Longitudinal

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
3.14	**0.0900**	**0.0573**	**10:45**	**43:21**	**91:45**
6.37	0.1800	0.0565	10:56	44:02	93:15
1.61	0.0500	0.0500	12:49	50:30	105:45
3.94	0.0800	0.0406	16:40	63:21	130:45
2.02	0.0400	0.0395	17:15	65:22	134:30

Y: Transverse

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
3.14	**0.1000**	**0.0637**	**9:19**	**38:30**	**82:07**
6.37	0.1400	0.0440	15:07	58:15	120:45
3.94	0.0800	0.0406	16:40	63:21	130:45
1.61	0.0400	0.0400	17:00	64:30	133:00
2.02	0.0400	0.0395	17:15	65:22	134:30

Z: Vertical

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
3.14	**0.3000**	**0.2658**	**1:52**	**10:07**	**24:02**
3.94	0.2400	0.2381	2:14	11:41	27:25
2.53	0.2500	0.1987	2:58	14:42	33:51
2.02	0.1700	0.1209	6:09	27:00	59:06
6.37	0.1000	0.1000	8:00	33:45	72:45

* International Standards Organization ISO 2631:
Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)

RUN-02 Front

8-OCT-93 16:14:15

1: **HET Ride Quality**
2: **Oct 4, 1993**
3: **Paved**
4: **Front**
5: **30 mph**
6: **Loaded**

Third-octave bands with greatest weighted RMS accelerations (m/s^2)

Durations of WBV exposure before reaching ISO limits* (given in hours:minutes)

X: Longitudinal

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
6.37	**0.1900**	**0.0596**	**10:11**	**41:26**	**88:00**
1.61	0.0500	0.0500	12:49	50:30	105:45
3.14	0.0600	0.0382	18:00	67:45	139:15
3.94	0.0700	0.0356	19:40	73:15	149:45
7.98	0.1400	0.0351	20:00	74:15	151:45

Y: Transverse

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
3.14	**0.0800**	**0.0510**	**12:30**	**49:30**	**103:45**
6.37	0.1300	0.0408	16:35	63:06	130:15
1.61	0.0400	0.0400	17:00	64:30	133:00
7.98	0.1500	0.0376	18:22	69:00	141:30
3.94	0.0700	0.0356	19:40	73:15	149:45

Z: Vertical

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
3.14	**0.4800**	**0.4253**	**0:45**	**5:18**	**13:27**
3.94	0.4000	0.3968	0:52	5:50	14:41
2.53	0.2500	0.1987	2:58	14:42	33:51
2.02	0.1600	0.1138	6:41	29:00	63:15
6.37	0.1000	0.1000	8:00	33:45	72:45

* International Standards Organization ISO 2631:
Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)

RUN-02 Roadside

8-OCT-93 16:14:15

1: **HET Ride Quality**
2: **Oct 4, 1993**
3: **Paved**
4: **Roadside**
5: **30 mph**
6: **Loaded**

Third-octave bands with greatest weighted RMS accelerations (m/s^2)

Durations of WBV exposure before reaching ISO limits* (given in hours:minutes)

X: Longitudinal

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
6.37	**0.3100**	**0.0973**	**5:11**	**23:25**	**51:51**
5.05	0.1500	0.0594	10:15	41:41	88:30
7.98	0.1900	0.0476	13:38	53:21	111:15
1.61	0.0400	0.0400	17:00	64:30	133:00
3.94	0.0700	0.0356	19:40	73:15	149:45

Y: Transverse

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
3.14	**0.0900**	**0.0573**	**10:45**	**43:21**	**91:45**
6.37	0.1700	0.0534	11:48	47:00	98:52
7.98	0.1800	0.0451	14:37	56:36	117:45
3.94	0.0800	0.0406	16:40	63:21	130:45
1.61	0.0300	0.0300	24:08	87:45	177:15

Z: Vertical

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
3.14	**0.3000**	**0.2658**	**1:52**	**10:07**	**24:02**
6.37	0.2500	0.2500	2:03	10:57	25:52
3.94	0.2500	0.2480	2:04	11:03	26:07
2.53	0.1900	0.1510	4:28	20:40	46:15
7.98	0.1500	0.1500	4:31	20:52	46:36

* International Standards Organization ISO 2631:

Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)

RUN-02 Curbside

8-OCT-93 16:14:15

1: **HET Ride Quality**
2: **Oct 4, 1993**
3: **Paved**
4: **Curbside**
5: **30 mph**
6: **Loaded**

Third-octave bands with greatest weighted RMS accelerations (m/s^2)

Durations of WBV exposure before reaching ISO limits* (given in hours:minutes)

X: Longitudinal

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
6.37	**0.2600**	**0.0816**	**6:39**	**28:52**	**63:00**
5.05	0.1300	0.0515	12:22	48:56	102:45
7.98	0.1800	0.0451	14:37	56:36	117:45
3.94	0.0800	0.0406	16:40	63:21	130:45
1.61	0.0400	0.0400	17:00	64:30	133:00

Y: Transverse

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
6.37	**0.1900**	**0.0596**	**10:11**	**41:26**	**88:00**
7.98	0.1800	0.0451	14:37	56:36	117:45
3.14	0.0700	0.0446	14:49	57:21	119:00
3.94	0.0700	0.0356	19:40	73:15	149:45
1.61	0.0300	0.0300	24:08	87:45	177:15

Z: Vertical

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
3.14	**0.4100**	**0.3633**	**1:05**	**6:37**	**16:25**
3.94	0.3500	0.3472	1:10	7:03	17:22
6.37	0.1700	0.1700	3:45	17:52	40:30
2.53	0.2000	0.1590	4:09	19:25	43:45
5.05	0.1000	0.1000	8:00	33:45	72:45

* International Standards Organization ISO 2631:

Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)

RUN-03 Driver

8-OCT-93 16:14:15

1: **HET Ride Quality**
2: **Oct 4, 1993**
3: **Paved**
4: **Driver**
5: **35 mph**
6: **Loaded**

Third-octave bands with greatest weighted RMS accelerations (m/s^2)

Durations of WBV exposure before reaching ISO limits* (given in hours:minutes)

X: Longitudinal

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
3.94	**0.1100**	**0.0559**	**11:07**	**44:36**	**94:15**
1.61	0.0500	0.0500	12:49	50:30	105:45
6.37	0.1500	0.0471	13:49	54:00	112:30
2.02	0.0400	0.0395	17:15	65:22	134:30
7.98	0.1400	0.0351	20:00	74:15	151:45

Y: Transverse

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
3.94	**0.1400**	**0.0711**	**8:03**	**33:51**	**73:00**
7.98	0.2100	0.0526	12:00	47:45	100:22
1.61	0.0400	0.0400	17:00	64:30	133:00
2.02	0.0400	0.0395	17:15	65:22	134:30
1.20	0.0300	0.0300	24:08	87:45	177:15

Z: Vertical

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
3.94	**0.2700**	**0.2679**	**1:50**	**10:00**	**23:52**
2.53	0.1900	0.1510	4:28	20:40	46:15
2.02	0.1900	0.1352	5:16	23:38	52:21
7.98	0.1300	0.1300	5:33	24:47	54:36
3.14	0.1300	0.1152	6:35	28:37	62:21

* International Standards Organization ISO 2631:
Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)

RUN-03 . Front

8-OCT-93 16:14:15

1: **HET Ride Quality**
2: **Oct 4, 1993**
3: **Paved**
4: **Front**
5: **35 mph**
6: **Loaded**

Third-octave bands with greatest weighted RMS accelerations (m/s^2)

Durations of WBV exposure before reaching ISO limits* (given in hours:minutes)

X: Longitudinal

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
3.94	**0.1100**	**0.0559**	**11:07**	**44:36**	**94:15**
1.61	0.0500	0.0500	12:49	50:30	105:45
6.37	0.1500	0.0471	13:49	54:00	112:30
7.98	0.1600	0.0401	16:58	64:22	132:45
2.02	0.0400	0.0395	17:15	65:22	134:30

Y: Transverse

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
3.94	**0.1700**	**0.0864**	**6:09**	**27:00**	**59:15**
7.98	0.2600	0.0651	9:03	37:30	80:15
1.61	0.0300	0.0300	24:08	87:45	177:15
1.20	0.0300	0.0300	24:08	87:45	177:15
2.02	0.0300	0.0296	24:30	88:45	179:30

Z: Vertical

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
3.94	**0.4500**	**0.4464**	**0:41**	**4:56**	**12:38**
2.53	0.1900	0.1510	4:28	20:40	46:15
7.98	0.1400	0.1400	5:00	22:40	50:21
2.02	0.1800	0.1281	5:41	25:15	55:36
3.14	0.1400	0.1240	5:56	26:10	57:36

* International Standards Organization ISO 2631:

Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)

RUN-03 Roadside

8-OCT-93 16:14:15

1: **HET Ride Quality**
2: **Oct 4, 1993**
3: **Paved**
4: **Roadside**
5: **35 mph**
6: **Loaded**

Third-octave bands with greatest weighted RMS accelerations (m/s^2)

Durations of WBV exposure before reaching ISO limits* (given in hours:minutes)

X: Longitudinal

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
3.94	**0.1500**	**0.0762**	**7:20**	**31:17**	**67:45**
6.37	0.2400	0.0753	7:26	31:40	68:37
7.98	0.1800	0.0451	14:37	56:36	117:45
1.61	0.0400	0.0400	17:00	64:30	133:00
5.05	0.0800	0.0317	22:37	82:52	168:00

Y: Transverse

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
3.94	**0.1300**	**0.0660**	**8:53**	**36:56**	**79:00**
7.98	0.2500	0.0626	9:33	39:15	83:37
2.02	0.0300	0.0296	24:30	88:45	179:30
10.10	0.1400	0.0277	26:30	95:15	191:30
6.37	0.0700	0.0220	34:47	121:00	240:00

Z: Vertical

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
3.94	**0.3400**	**0.3373**	**1:14**	**7:20**	**18:00**
6.37	0.1700	0.1700	3:45	17:52	40:30
7.98	0.1400	0.1400	5:00	22:40	50:21
2.53	0.1500	0.1192	6:16	27:25	60:06
2.02	0.1500	0.1067	7:20	31:15	67:45

* International Standards Organization ISO 2631:

Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)

RUN-03 Curbside

8-OCT-93 16:14:15

1: **HET Ride Quality**
2: **Oct 4, 1993**
3: **Paved**
4: **Curbside**
5: **35 mph**
6: **Loaded**

Third-octave bands with greatest weighted RMS accelerations (m/s^2)

Durations of WBV exposure before reaching ISO limits* (given in hours:minutes)

X: Longitudinal

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
3.94	**0.1500**	**0.0762**	**7:20**	**31:17**	**67:45**
6.37	0.2300	0.0722	7:54	33:17	71:52
1.61	0.0500	0.0500	12:49	50:30	105:45
7.98	0.1800	0.0451	14:37	56:36	117:45
5.05	0.0800	0.0317	22:37	82:52	168:00

Y: Transverse

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
7.98	**0.2400**	**0.0601**	**10:04**	**41:06**	**87:15**
3.94	0.1100	0.0559	11:07	44:36	94:15
1.61	0.0300	0.0300	24:08	87:45	177:15
6.37	0.0900	0.0283	25:55	93:22	188:00
10.10	0.1400	0.0277	26:30	95:15	191:30

Z: Vertical

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
3.94	**0.3800**	**0.3770**	**0:57**	**6:16**	**15:41**
6.37	0.1500	0.1500	4:31	20:52	46:36
7.98	0.1300	0.1300	5:33	24:47	54:36
2.53	0.1600	0.1272	5:43	25:25	56:00
2.02	0.1500	0.1067	7:20	31:15	67:45

* International Standards Organization ISO 2631:

Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)

RUN-04 Driver

8-OCT-93 16:14:16

1: **HET Ride Quality**
2: **Oct 4, 1993**
3: **Paved**
4: **Driver**
5: **40 mph**
6: **Loaded**

Third-octave bands with greatest weighted RMS accelerations (m/s^2)

Durations of WBV exposure before reaching ISO limits* (given in hours:minutes)

X: Longitudinal

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
3.94	**0.1400**	**0.0711**	**8:03**	**33:51**	**73:00**
1.61	0.0700	0.0700	8:14	34:30	74:15
5.05	0.1600	0.0633	9:25	38:45	82:37
2.02	0.0500	0.0494	13:00	51:15	107:15
1.20	0.0400	0.0400	17:00	64:30	133:00

Y: Transverse

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
3.94	**0.1700**	**0.0864**	**6:09**	**27:00**	**59:15**
5.05	0.1900	0.0752	7:28	31:45	68:45
1.61	0.0500	0.0500	12:49	50:30	105:45
2.02	0.0500	0.0494	13:00	51:15	107:15
10.10	0.1900	0.0376	18:20	68:52	141:15

Z: Vertical

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
5.05	**0.2300**	**0.2300**	**2:20**	**12:12**	**28:32**
3.94	0.2300	0.2282	2:23	12:19	28:52
2.53	0.2800	0.2225	2:29	12:45	29:40
2.02	0.2500	0.1779	3:30	16:53	38:30
7.98	0.1000	0.1000	8:00	33:45	72:45

* International Standards Organization ISO 2631:
Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)

RUN-04 Front

8-OCT-93 16:14:16

1: **HET Ride Quality**
2: **Oct 4, 1993**
3: **Paved**
4: **Front**
5: **40 mph**
6: **Loaded**

Third-octave bands with greatest weighted RMS accelerations (m/s^2)

Durations of WBV exposure before reaching ISO limits* (given in hours:minutes)

X: Longitudinal

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
1.61	**0.0900**	**0.0900**	**5:48**	**25:45**	**56:36**
2.02	0.0700	0.0691	8:22	35:00	75:15
3.94	0.1100	0.0559	11:07	44:36	94:15
7.98	0.2100	0.0526	12:00	47:45	100:22
5.05	0.1300	0.0515	12:22	48:56	102:45

Y: Transverse

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
3.94	**0.1800**	**0.0914**	**5:41**	**25:15**	**55:36**
5.05	0.2000	0.0792	6:58	29:55	65:07
10.10	0.2100	0.0416	16:10	61:51	127:45
7.98	0.1600	0.0401	16:58	64:22	132:45
1.61	0.0400	0.0400	17:00	64:30	133:00

Z: Vertical

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
5.05	**0.3700**	**0.3700**	**1:02**	**6:26**	**16:02**
3.94	0.3500	0.3472	1:10	7:03	17:22
2.53	0.2800	0.2225	2:29	12:45	29:40
2.02	0.2300	0.1636	3:59	18:45	42:17
7.98	0.1200	0.1200	6:13	27:15	59:45

* International Standards Organization ISO 2631:

Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)

RUN-04 Roadside

8-OCT-93 16:14:16

1: **HET Ride Quality**
2: **Oct 4, 1993**
3: **Paved**
4: **Roadside**
5: **40 mph**
6: **Loaded**

Third-octave bands with greatest weighted RMS accelerations (m/s^2)

Durations of WBV exposure before reaching ISO limits* (given in hours:minutes)

X: Longitudinal

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
3.94	**0.2100**	**0.1067**	**4:33**	**20:58**	**46:51**
5.05	0.2400	0.0950	5:22	24:07	53:21
1.61	0.0600	0.0600	10:07	41:11	87:30
7.98	0.2000	0.0501	12:48	50:21	105:30
2.02	0.0500	0.0494	13:00	51:15	107:15

Y: Transverse

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
3.94	**0.1300**	**0.0660**	**8:53**	**36:56**	**79:00**
5.05	0.1500	0.0594	10:15	41:41	88:30
10.10	0.2900	0.0574	10:42	43:15	91:30
7.98	0.2100	0.0526	12:00	47:45	100:22
1.61	0.0300	0.0300	24:08	87:45	177:15

Z: Vertical

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
5.05	**0.3600**	**0.3600**	**1:06**	**6:41**	**16:37**
3.94	0.3300	0.3274	1:17	7:37	18:40
2.53	0.2100	0.1669	3:51	18:17	41:21
7.98	0.1400	0.1400	5:00	22:40	50:21
2.02	0.1900	0.1352	5:16	23:38	52:21

* International Standards Organization ISO 2631:
Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)

RUN-04 Curbside

8-OCT-93 16:14:16

1: **HET Ride Quality**
2: **Oct 4, 1993**
3: **Paved**
4: **Curbside**
5: **40 mph**
6: **Loaded**

Third-octave bands with greatest weighted RMS accelerations (m/s^2)

Durations of WBV exposure before reaching ISO limits* (given in hours:minutes)

X: Longitudinal

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
3.94	**0.1900**	**0.0965**	**5:16**	**23:40**	**52:21**
5.05	0.2300	0.0910	5:43	25:22	55:51
1.61	0.0700	0.0700	8:14	34:30	74:15
2.02	0.0600	0.0593	10:15	41:45	88:37
7.98	0.2100	0.0526	12:00	47:45	100:22

Y: Transverse

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
3.94	**0.1200**	**0.0610**	**9:53**	**40:26**	**86:00**
10.10	0.2900	0.0574	10:42	43:15	91:30
5.05	0.1400	0.0554	11:12	45:00	95:00
7.98	0.2200	0.0551	11:18	45:17	95:37
1.61	0.0400	0.0400	17:00	64:30	133:00

Z: Vertical

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
5.05	**0.3500**	**0.3500**	**1:09**	**6:58**	**17:13**
3.94	0.3300	0.3274	1:17	7:37	18:40
2.53	0.2300	0.1828	3:21	16:20	37:17
2.02	0.1900	0.1352	5:16	23:38	52:21
7.98	0.1100	0.1100	7:01	30:10	65:37

* International Standards Organization ISO 2631:

Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)

RUN-05 Driver

8-OCT-93 16:14:17

1: **HET Ride Quality**
2: **Oct 4, 1993**
3: **Cross Country #2**
4: **Driver**
5: **5 mph**
6: **Loaded**

Third-octave bands with greatest weighted RMS accelerations (m/s^2)

Durations of WBV exposure before reaching ISO limits* (given in hours:minutes)

X: Longitudinal

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
1.20	**0.0600**	**0.0600**	**10:07**	**41:11**	**87:30**
1.61	0.0500	0.0500	12:49	50:30	105:45
3.94	0.0r800	0.0406	16:40	63:21	130:45
2.02	0.0400	0.0395	17:15	65:22	134:30
20.10	0.3300	0.0328	21:40	79:45	162:00

Y: Transverse

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
1.20	**0.2100**	**0.2100**	**1:34**	**8:49**	**21:17**
1.61	0.1900	0.1900	1:52	10:04	24:02
2.02	0.0900	0.0889	5:54	26:07	57:21
2.53	0.0600	0.0475	13:41	53:30	111:30
20.10	0.3400	0.0338	20:53	77:15	157:15

Z: Vertical

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
2.02	**0.2300**	**0.1636**	**3:59**	**18:45**	**42:17**
2.53	0.1800	0.1431	4:50	22:05	49:11
1.61	0.2000	0.1270	5:45	25:30	56:06
1.20	0.1700	0.0932	8:48	36:32	78:15
6.37	0.0800	0.0800	10:47	43:30	92:00

* International Standards Organization ISO 2631:

Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)

RUN-05 Front

8-OCT-93 16:14:17

1: **HET Ride Quality**
2: **Oct 4, 1993**
3: **Cross Country #2**
4: **Front**
5: **5 mph**
6: **Loaded**

Third-octave bands with greatest weighted RMS accelerations (m/s^2)

Durations of WBV exposure before reaching ISO limits* (given in hours:minutes)

X: Longitudinal

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
1.20	**0.0900**	**0.0900**	**5:48**	**25:45**	**56:36**
1.61	0.0800	0.0800	6:50	29:32	64:22
2.02	0.0400	0.0395	17:15	65:22	134:30
2.53	0.0400	0.0317	22:37	82:52	168:00
3.94	0.0600	0.0305	23:40	86:15	174:30

Y: Transverse

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
1.20	**0.1900**	**0.1900**	**1:52**	**10:04**	**24:02**
1.61	0.1500	0.1500	2:43	13:42	31:45
2.02	0.0700	0.0691	8:22	35:00	75:15
2.53	0.0400	0.0317	22:37	82:52	168:00
6.37	0.1000	0.0314	22:52	83:37	169:30

Z: Vertical

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
2.02	**0.2300**	**0.1636**	**3:59**	**18:45**	**42:17**
2.53	0.1900	0.1510	4:28	20:40	46:15
1.61	0.1700	0.1079	7:13	30:52	67:00
3.14	0.1100	0.0975	8:18	34:45	74:45
3.94	0.0900	0.0893	9:19	38:26	82:00

* International Standards Organization ISO 2631:
Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)

RUN-05 Roadside

8-OCT-93 16:14:17

1: **HET Ride Quality**
2: **Oct 4, 1993**
3: **Cross Country #2**
4: **Roadside**
5: **5 mph**
6: **Loaded**

Third-octave bands with greatest weighted RMS accelerations (m/s^2)

Durations of WBV exposure before reaching ISO limits* (given in hours:minutes)

X: Longitudinal

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
1.61	**0.0600**	**0.0600**	**10:07**	**41:11**	**87:30**
1.20	0.0600	0.0600	10:07	41:11	87:30
3.94	0.1000	0.0508	12:33	49:36	104:00
6.37	0.1300	0.0408	16:35	63:06	130:15
5.05	0.1000	0.0396	17:15	65:15	134:15

Y: Transverse

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
1.20	**0.1600**	**0.1600**	**2:27**	**12:37**	**29:30**
1.61	0.1300	0.1300	3:24	16:25	37:30
2.02	0.0600	0.0593	10:15	41:45	88:37
6.37	0.1300	0.0408	16:35	63:06	130:15
2.53	0.0500	0.0396	17:15	65:15	134:15

Z: Vertical

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
2.02	**0.1800**	**0.1281**	**5:41**	**25:15**	**55:36**
20.10	0.3000	0.1194	6:16	27:25	60:00
2.53	0.1400	0.1113	6:54	29:47	64:45
1.61	0.1700	0.1079	7:13	30:52	67:00
12.74	0.1700	0.1068	7:18	31:15	67:45

* International Standards Organization ISO 2631:

Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)

RUN-05 Curbside

8-OCT-93 16:14:17

1: **HET Ride Quality**
2: **Oct 4, 1993**
3: **Cross Country #2**
4: **Curbside**
5: **5 mph**
6: **Loaded**

Third-octave bands with greatest weighted RMS accelerations (m/s^2)

Durations of WBV exposure before reaching ISO limits* (given in hours:minutes)

X: Longitudinal

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
1.20	**0.0900**	**0.0900**	**5:48**	**25:45**	**56:36**
1.61	0.0800	0.0800	6:50	29:32	64:22
2.02	0.0500	0.0494	13:00	51:15	107:15
3.94	0.0900	0.0457	14:22	55:45	116:00
2.53	0.0500	0.0396	17:15	65:15	134:15

Y: Transverse

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
1.20	**0.1300**	**0.1300**	**3:24**	**16:25**	**37:30**
1.61	0.1000	0.1000	5:00	22:40	50:21
2.02	0.0500	0.0494	13:00	51:15	107:15
6.37	0.1200	0.0377	18:17	68:45	141:15
7.98	0.1400	0.0351	20:00	74:15	151:45

Z: Vertical

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
2.02	**0.2000**	**0.1423**	**4:52**	**22:15**	**49:30**
2.53	0.1600	0.1272	5:43	25:25	56:00
1.61	0.1600	0.1016	7:50	33:06	71:30
12.74	0.1400	0.0879	9:30	39:06	83:22
6.37	0.0800	0.0800	10:47	43:30	92:00

* International Standards Organization ISO 2631:

Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)

RUN-06 Driver

8-OCT-93 16:14:18

1: **HET Ride Quality**
2: **Oct 4, 1993**
3: **Cross Country #2**
4: **Driver**
5: **10 mph**
6: **Loaded**

Third-octave bands with greatest weighted RMS accelerations (m/s^2)

Durations of WBV exposure before reaching ISO limits* (given in hours:minutes)

X: Longitudinal

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
2.02	**0.1100**	**0.1087**	**4:26**	**20:30**	**45:56**
1.61	0.0900	0.0900	5:48	25:45	56:36
2.53	0.1100	0.0871	6:05	26:45	58:36
5.05	0.2100	0.0831	6:30	28:15	61:45
1.20	0.0800	0.0800	6:50	29:32	64:22

Y: Transverse

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
1.20	**0.2500**	**0.2500**	**1:09**	**6:58**	**17:13**
1.61	0.1800	0.1800	2:01	10:49	25:38
2.02	0.1700	0.1679	2:15	11:52	27:52
2.53	0.1700	0.1346	3:13	15:45	36:00
3.14	0.1300	0.0828	6:31	28:22	62:00

Z: Vertical

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
2.02	**0.4600**	**0.3273**	**1:17**	**7:39**	**18:40**
2.53	0.4100	0.3259	1:19	7:41	18:47
1.61	0.4000	0.2539	2:00	10:44	25:25
1.20	0.3700	0.2030	2:51	14:19	33:02
3.14	0.2200	0.1949	3:02	15:04	34:36

* International Standards Organization ISO 2631:
Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)

RUN-06 Front

8-OCT-93 16:14:18

1: **HET Ride Quality**
2: **Oct 4, 1993**
3: **Cross Country #2**
4: **Front**
5: **10 mph**
6: **Loaded**

Third-octave bands with greatest weighted RMS accelerations (m/s^2)

Durations of WBV exposure before reaching ISO limits* (given in hours:minutes)

X: Longitudinal

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
1.61	**0.0800**	**0.0800**	**6:50**	**29:32**	**64:22**
1.20	0.0800	0.0800	6:50	29:32	64:22
2.02	0.0800	0.0790	6:58	30:00	65:15
5.05	0.1600	0.0633	9:25	38:45	82:37
2.53	0.0800	0.0633	9:25	38:45	82:37

Y: Transverse

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
1.20	**0.2300**	**0.2300**	**1:21**	**7:48**	**19:02**
1.61	0.1300	0.1300	3:24	16:25	37:30
2.02	0.1100	0.1087	4:26	20:30	45:56
2.53	0.1300	0.1029	4:48	21:53	48:45
3.14	0.1200	0.0764	7:18	31:10	67:37

Z: Vertical

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
2.53	**0.4000**	**0.3179**	**1:22**	**7:56**	**19:22**
2.02	0.4300	0.3059	1:28	8:22	20:17
1.61	0.3900	0.2476	2:05	11:04	26:10
3.14	0.2200	0.1949	3:02	15:04	34:36
1.20	0.3200	0.1755	3:34	17:10	39:02

* International Standards Organization ISO 2631:
Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)

RUN-06 Roadside

8-OCT-93 16:14:18

1: **HET Ride Quality**
2: **Oct 4, 1993**
3: **Cross Country #2**
4: **Roadside**
5: **10 mph**
6: **Loaded**

Third-octave bands with greatest weighted RMS accelerations (m/s^2)

Durations of WBV exposure before reaching ISO limits* (given in hours:minutes)

X: Longitudinal

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
5.05	**0.3100**	**0.1227**	**3:42**	**17:38**	**40:00**
2.02	0.1100	0.1087	4:26	20:30	45:56
1.61	0.1000	0.1000	5:00	22:40	50:21
2.53	0.1200	0.0950	5:22	24:07	53:21
3.14	0.1300	0.0828	6:31	28:22	62:00

Y: Transverse

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
1.20	**0.1900**	**0.1900**	**1:52**	**10:04**	**24:02**
1.61	0.1300	0.1300	3:24	16:25	37:30
2.02	0.1100	0.1087	4:26	20:30	45:56
2.53	0.1100	0.0871	6:05	26:45	58:36
6.37	0.2300	0.0722	7:54	33:17	71:52

Z: Vertical

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
2.02	**0.3700**	**0.2632**	**1:52**	**10:14**	**24:22**
2.53	0.3300	0.2623	1:53	10:17	24:25
3.14	0.2300	0.2038	2:50	14:15	32:56
1.61	0.3200	0.2031	2:51	14:18	33:00
3.94	0.1800	0.1786	3:30	16:50	38:17

* International Standards Organization ISO 2631:

Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)

RUN-06 Curbside

8-OCT-93 16:14:18

1: **HET Ride Quality**
2: **Oct 4, 1993**
3: **Cross Country #2**
4: **Curbside**
5: **10 mph**
6: **Loaded**

Third-octave bands with greatest weighted RMS accelerations (m/s^2)

Durations of WBV exposure before reaching ISO limits* (given in hours:minutes)

X: Longitudinal

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
5.05	**0.3000**	**0.1187**	**3:53**	**18:23**	**41:32**
2.02	0.1100	0.1087	4:26	20:30	45:56
1.61	0.1000	0.1000	5:00	22:40	50:21
2.53	0.1200	0.0950	5:22	24:07	53:21
1.20	0.0900	0.0900	5:48	25:45	56:36

Y: Transverse

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
1.20	**0.1700**	**0.1700**	**2:14**	**11:41**	**27:25**
1.61	0.1100	0.1100	4:20	20:10	45:15
2.02	0.1000	0.0988	5:05	23:00	51:06
2.53	0.1000	0.0792	6:58	29:55	65:07
6.37	0.2300	0.0722	7:54	33:17	71:52

Z: Vertical

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
2.53	**0.3300**	**0.2623**	**1:53**	**10:17**	**24:25**
2.02	0.3600	0.2561	1:59	10:37	25:10
1.61	0.3200	0.2031	2:51	14:18	33:00
3.14	0.2100	0.1861	3:16	16:00	36:32
3.94	0.1800	0.1786	3:30	16:50	38:17

* International Standards Organization ISO 2631:

Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)

RUN-07 Driver

8-OCT-93 16:14:19

1: **HET Ride Quality**
2: **Oct 4, 1993**
3: **Cross Country #2**
4: **Driver**
5: **15 mph**
6: **Loaded**

Third-octave bands with greatest weighted RMS accelerations (m/s^2)

Durations of WBV exposure before reaching ISO limits* (given in hours:minutes)

X: Longitudinal

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
3.14	**0.1900**	**0.1210**	**3:46**	**17:58**	**40:41**
3.94	0.2300	0.1168	3:59	18:45	42:21
1.61	0.1100	0.1100	4:20	20:10	45:15
2.02	0.0900	0.0889	5:54	26:07	57:21
1.20	0.0800	0.0800	6:50	29:32	64:22

Y: Transverse

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
1.61	**0.2000**	**0.2000**	**1:42**	**9:26**	**22:37**
1.20	0.1800	0.1800	2:01	10:49	25:38
2.02	0.1500	0.1482	2:45	13:56	32:15
3.94	0.1700	0.0864	6:09	27:00	59:15
2.53	0.1000	0.0792	6:58	29:55	65:07

Z: Vertical

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
2.02	**0.5400**	**0.3842**	**0:56**	**6:07**	**15:18**
1.61	0.5600	0.3555	1:07	6:48	16:52
2.53	0.3500	0.2782	1:44	9:30	22:47
3.14	0.2200	0.1949	3:02	15:04	34:36
3.94	0.1900	0.1885	3:13	15:42	36:00

* International Standards Organization ISO 2631:
Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)

RUN-07 Front

8-OCT-93 16:14:19

1: **HET Ride Quality**
2: **Oct 4, 1993**
3: **Cross Country #2**
4: **Front**
5: **15 mph**
6: **Loaded**

Third-octave bands with greatest weighted RMS accelerations (m/s^2)

Durations of WBV exposure before reaching ISO limits* (given in hours:minutes)

X: Longitudinal

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
1.61	**0.1200**	**0.1200**	**3:49**	**18:08**	**41:02**
1.20	0.1000	0.1000	5:00	22:40	50:21
3.94	0.1600	0.0813	6:41	29:00	63:15
2.02	0.0700	0.0691	8:22	35:00	75:15
3.14	0.1000	0.0637	9:19	38:30	82:07

Y: Transverse

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
1.20	**0.1700**	**0.1700**	**2:14**	**11:41**	**27:25**
1.61	0.1600	0.1600	2:27	12:37	29:30
2.02	0.1000	0.0988	5:05	23:00	51:06
3.14	0.1000	0.0637	9:19	38:30	82:07
2.53	0.0700	0.0554	11:12	45:00	95:00

Z: Vertical

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
2.02	**0.5100**	**0.3628**	**1:05**	**6:37**	**16:25**
1.61	0.5100	0.3238	1:20	7:45	18:55
2.53	0.3400	0.2702	1:49	9:53	23:37
3.94	0.2100	0.2083	2:45	13:52	32:02
3.14	0.2200	0.1949	3:02	15:04	34:36

* International Standards Organization ISO 2631:

Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)

RUN-07 Roadside

8-OCT-93 16:14:19

1: **HET Ride Quality**
2: **Oct 4, 1993**
3: **Cross Country #2**
4: **Roadside**
5: **15 mph**
6: **Loaded**

Third-octave bands with greatest weighted RMS accelerations (m/s^2)

Durations of WBV exposure before reaching ISO limits* (given in hours:minutes)

X: Longitudinal

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
3.94	**0.3100**	**0.1575**	**2:30**	**12:53**	**30:00**
3.14	0.2000	0.1274	3:30	16:52	38:21
5.05	0.2800	0.1108	4:18	20:00	44:56
1.61	0.0900	0.0900	5:48	25:45	56:36
6.37	0.2600	0.0816	6:39	28:52	63:00

Y: Transverse

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
1.20	**0.1500**	**0.1500**	**2:43**	**13:42**	**31:45**
1.61	0.1400	0.1400	3:01	14:57	34:26
2.02	0.1100	0.1087	4:26	20:30	45:56
3.94	0.1500	0.0762	7:20	31:17	67:45
5.05	0.1800	0.0712	8:02	33:51	72:52

Z: Vertical

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
2.02	**0.4400**	**0.3130**	**1:24**	**8:07**	**19:45**
1.61	0.4600	0.2920	1:35	8:55	21:30
3.94	0.2900	0.2877	1:37	9:06	21:52
2.53	0.3000	0.2384	2:13	11:38	27:22
3.14	0.2400	0.2126	2:40	13:30	31:17

* International Standards Organization ISO 2631:

Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)

RUN-07 Curbside

8-OCT-93 16:14:19

1: **HET Ride Quality**
2: **Oct 4, 1993**
3: **Cross Country #2**
4: **Curbside**
5: **15 mph**
6: **Loaded**

Third-octave bands with greatest weighted RMS accelerations (m/s^2)

Durations of WBV exposure before reaching ISO limits* (given in hours:minutes)

X: Longitudinal

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
3.94	**0.3200**	**0.1626**	**2:24**	**12:22**	**28:55**
3.14	0.2000	0.1274	3:30	16:52	38:21
1.61	0.1100	0.1100	4:20	20:10	45:15
5.05	0.2500	0.0989	5:05	22:58	51:00
1.20	0.0900	0.0900	5:48	25:45	56:36

Y: Transverse

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
1.61	**0.1200**	**0.1200**	**3:49**	**18:08**	**41:02**
1.20	0.1200	0.1200	3:49	18:08	41:02
3.94	0.1800	0.0914	5:41	25:15	55:36
2.02	0.0900	0.0889	5:54	26:07	57:21
5.05	0.1900	0.0752	7:28	31:45	68:45

Z: Vertical

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
2.02	**0.4300**	**0.3059**	**1:28**	**8:22**	**20:17**
1.61	0.4300	0.2730	1:46	9:45	23:17
3.94	0.2700	0.2679	1:50	10:00	23:52
2.53	0.3000	0.2384	2:13	11:38	27:22
3.14	0.2400	0.2126	2:40	13:30	31:17

* International Standards Organization ISO 2631:
Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)

RUN-08 Driver

8-OCT-93 16:14:19

1: **HET Ride Quality**
2: **Oct 4, 1993**
3: **Secondary A**
4: **Driver**
5: **10 mph**
6: **Loaded**

Third-octave bands with greatest weighted RMS accelerations (m/s^2)

Durations of WBV exposure before reaching ISO limits* (given in hours:minutes)

X: Longitudinal

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
3.14	**0.1200**	**0.0764**	**7:18**	**31:10**	**67:37**
3.94	0.1400	0.0711	8:03	33:51	73:00
5.05	0.1600	0.0633	9:25	38:45	82:37
2.53	0.0800	0.0633	9:25	38:45	82:37
6.37	0.1900	0.0596	10:11	41:26	88:00

Y: Transverse

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
1.20	**0.1600**	**0.1600**	**2:27**	**12:37**	**29:30**
1.61	0.1300	0.1300	3:24	16:25	37:30
2.02	0.1200	0.1185	3:54	18:25	41:36
2.53	0.1300	0.1029	4:48	21:53	48:45
3.14	0.1100	0.0701	8:12	34:30	74:15

Z: Vertical

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
2.53	**0.3800**	**0.3020**	**1:30**	**8:30**	**20:37**
2.02	0.3600	0.2561	1:59	10:37	25:10
3.94	0.1800	0.1786	3:30	16:50	38:17
3.14	0.2000	0.1772	3:31	17:00	38:36
1.61	0.2400	0.1524	4:24	20:28	45:51

* International Standards Organization ISO 2631:
Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)

RUN-08 Front

8-OCT-93 16:14:19

1: **HET Ride Quality**
2: **Oct 4, 1993**
3: **Secondary A**
4: **Front**
5: **10 mph**
6: **Loaded**

Third-octave bands with greatest weighted RMS accelerations (m/s^2)

Durations of WBV exposure before reaching ISO limits* (given in hours:minutes)

X: Longitudinal

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
1.20	**0.0800**	**0.0800**	**6:50**	**29:32**	**64:22**
1.61	0.0700	0.0700	8:14	34:30	74:15
5.05	0.1500	0.0594	10:15	41:41	88:30
2.53	0.0700	0.0554	11:12	45:00	95:00
2.02	0.0500	0.0494	13:00	51:15	107:15

Y: Transverse

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
1.20	**0.1600**	**0.1600**	**2:27**	**12:37**	**29:30**
1.61	0.1100	0.1100	4:20	20:10	45:15
2.02	0.0900	0.0889	5:54	26:07	57:21
2.53	0.0900	0.0712	8:02	33:51	72:52
15.97	0.5200	0.0651	9:03	37:30	80:15

Z: Vertical

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
2.53	**0.4200**	**0.3338**	**1:15**	**7:26**	**18:15**
2.02	0.3200	0.2277	2:24	12:22	28:55
3.14	0.2400	0.2126	2:40	13:30	31:17
3.94	0.1900	0.1885	3:13	15:42	36:00
1.61	0.2200	0.1397	5:01	22:45	50:30

* International Standards Organization ISO 2631:

Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)

RUN-08 Roadside

8-OCT-93 16:14:19

1: **HET Ride Quality**
2: **Oct 4, 1993**
3: **Secondary A**
4: **Roadside**
5: **10 mph**
6: **Loaded**

Third-octave bands with greatest weighted RMS accelerations (m/s^2)

Durations of WBV exposure before reaching ISO limits* (given in hours:minutes)

X: Longitudinal

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
5.05	**0.2500**	**0.0989**	**5:05**	**22:58**	**51:00**
3.94	0.1800	0.0914	5:41	25:15	55:36
3.14	0.1400	0.0892	5:54	26:00	57:06
6.37	0.2700	0.0848	6:20	27:37	60:21
2.02	0.0600	0.0593	10:15	41:45	88:37

Y: Transverse

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
1.20	**0.1200**	**0.1200**	**3:49**	**18:08**	**41:02**
1.61	0.0900	0.0900	5:48	25:45	56:36
2.02	0.0800	0.0790	6:58	30:00	65:15
2.53	0.0900	0.0712	8:02	33:51	72:52
6.37	0.2100	0.0659	8:56	37:00	79:15

Z: Vertical

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
2.53	**0.3100**	**0.2464**	**2:06**	**11:08**	**26:22**
2.02	0.2800	0.1992	2:57	14:41	33:45
3.94	0.2000	0.1984	2:58	14:45	33:56
3.14	0.2100	0.1861	3:16	16:00	36:32
6.37	0.1800	0.1800	3:27	16:38	38:00

* International Standards Organization ISO 2631:
Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)

RUN-08 Curbside

8-OCT-93 16:14:19

1: **HET Ride Quality**
2: **Oct 4, 1993**
3: **Secondary A**
4: **Curbside**
5: **10 mph**
6: **Loaded**

Third-octave bands with greatest weighted RMS accelerations (m/s^2)

Durations of WBV exposure before reaching ISO limits* (given in hours:minutes)

X: Longitudinal

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
5.05	**0.2400**	**0.0950**	**5:22**	**24:07**	**53:21**
3.94	0.1600	0.0813	6:41	29:00	63:15
3.14	0.1100	0.0701	8:12	34:30	74:15
1.61	0.0700	0.0700	8:14	34:30	74:15
1.20	0.0700	0.0700	8:14	34:30	74:15

Y: Transverse

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
1.20	**0.1100**	**0.1100**	**4:20**	**20:10**	**45:15**
1.61	0.0800	0.0800	6:50	29:32	64:22
2.02	0.0700	0.0691	8:22	35:00	75:15
6.37	0.2200	0.0691	8:22	35:02	75:22
5.05	0.1400	0.0554	11:12	45:00	95:00

Z: Vertical

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
2.53	**0.3600**	**0.2861**	**1:38**	**9:10**	**22:00**
2.02	0.2800	0.1992	2:57	14:41	33:45
3.14	0.2200	0.1949	3:02	15:04	34:36
5.05	0.1800	0.1800	3:27	16:38	38:00
3.94	0.1800	0.1786	3:30	16:50	38:17

* International Standards Organization ISO 2631:

Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)

RUN-09 Driver

8-OCT-93 16:14:20

1: **HET Ride Quality**
2: **Oct 4, 1993**
3: **Secondary A**
4: **Driver**
5: **15 mph**
6: **Loaded**

Third-octave bands with greatest weighted RMS accelerations (m/s^2)

Durations of WBV exposure before reaching ISO limits* (given in hours:minutes)

X: Longitudinal

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
3.94	**0.1800**	**0.0914**	**5:41**	**25:15**	**55:36**
6.37	0.2300	0.0722	7:54	33:17	71:52
5.05	0.1700	0.0673	8:41	36:06	77:30
3.14	0.1000	0.0637	9:19	38:30	82:07
7.98	0.2400	0.0601	10:04	41:06	87:15

Y: Transverse

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
1.61	**0.1500**	**0.1500**	**2:43**	**13:42**	**31:45**
1.20	0.1100	0.1100	4:20	20:10	45:15
2.02	0.1100	0.1087	4:26	20:30	45:56
7.98	0.2500	0.0626	9:33	39:15	83:37
3.94	0.1100	0.0559	11:07	44:36	94:15

Z: Vertical

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
2.02	**0.3600**	**0.2561**	**1:59**	**10:37**	**25:10**
2.53	0.3200	0.2543	2:00	10:42	25:22
3.94	0.2300	0.2282	2:23	12:19	28:52
3.14	0.2200	0.1949	3:02	15:04	34:36
1.61	0.3000	0.1904	3:10	15:30	35:36

* International Standards Organization ISO 2631:
Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)

RUN-09 Front

8-OCT-93 16:14:20

1: **HET Ride Quality**
2: **Oct 4, 1993**
3: **Secondary A**
4: **Front**
5: **15 mph**
6: **Loaded**

Third-octave bands with greatest weighted RMS accelerations (m/s^2)

Durations of WBV exposure before reaching ISO limits* (given in hours:minutes)

X: Longitudinal

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
1.61	**0.0800**	**0.0800**	**6:50**	**29:32**	**64:22**
3.94	0.1300	0.0660	8:53	36:56	79:00
2.02	0.0600	0.0593	10:15	41:45	88:37
7.98	0.2000	0.0501	12:48	50:21	105:30
1.20	0.0500	0.0500	12:49	50:30	105:45

Y: Transverse

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
1.61	**0.1200**	**0.1200**	**3:49**	**18:08**	**41:02**
1.20	0.1000	0.1000	5:00	22:40	50:21
2.02	0.0900	0.0889	5:54	26:07	57:21
7.98	0.2100	0.0526	12:00	47:45	100:22
2.53	0.0600	0.0475	13:41	53:30	111:30

Z: Vertical

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
2.02	**0.3500**	**0.2490**	**2:03**	**11:00**	**26:00**
2.53	0.3100	0.2464	2:06	11:08	26:22
3.94	0.2400	0.2381	2:14	11:41	27:25
3.14	0.2300	0.2038	2:50	14:15	32:56
1.61	0.3000	0.1904	3:10	15:30	35:36

* International Standards Organization ISO 2631:

Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)

RUN-09 Roadside

8-OCT-93 16:14:20

1: **HET Ride Quality**
2: **Oct 4, 1993**
3: **Secondary A**
4: **Roadside**
5: **15 mph**
6: **Loaded**

Third-octave bands with greatest weighted RMS accelerations (m/s^2)

Durations of WBV exposure before reaching ISO limits* (given in hours:minutes)

X: Longitudinal

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
3.94	**0.2400**	**0.1219**	**3:44**	**17:47**	**40:21**
6.37	0.3300	0.1036	4:45	21:45	48:26
5.05	0.2400	0.0950	5:22	24:07	53:21
7.98	0.3200	0.0802	6:50	29:30	64:15
1.61	0.0700	0.0700	8:14	34:30	74:15

Y: Transverse

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
1.61	**0.1100**	**0.1100**	**4:20**	**20:10**	**45:15**
7.98	0.3500	0.0877	6:01	26:30	58:15
1.20	0.0800	0.0800	6:50	29:32	64:22
2.02	0.0800	0.0790	6:58	30:00	65:15
5.05	0.1400	0.0554	11:12	45:00	95:00

Z: Vertical

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
3.94	**0.2500**	**0.2480**	**2:04**	**11:03**	**26:07**
2.53	0.2600	0.2066	2:46	14:00	32:21
2.02	0.2900	0.2063	2:47	14:00	32:26
3.14	0.2000	0.1772	3:31	17:00	38:36
7.98	0.1600	0.1600	4:07	19:15	43:21

* International Standards Organization ISO 2631:
Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)

RUN-09 Curbside

8-OCT-93 16:14:20

1: **HET Ride Quality**
2: **Oct 4, 1993**
3: **Secondary A**
4: **Curbside**
5: **15 mph**
6: **Loaded**

Third-octave bands with greatest weighted RMS accelerations (m/s^2)

Durations of WBV exposure before reaching ISO limits* (given in hours:minutes)

X: Longitudinal

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
3.94	**0.2200**	**0.1118**	**4:15**	**19:47**	**44:30**
6.37	0.2600	0.0816	6:39	28:52	63:00
1.61	0.0800	0.0800	6:50	29:32	64:22
5.05	0.1900	0.0752	7:28	31:45	68:45
7.98	0.3000	0.0752	7:28	31:47	68:52

Y: Transverse

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
7.98	**0.3500**	**0.0877**	**6:01**	**26:30**	**58:15**
1.61	0.0800	0.0800	6:50	29:32	64:22
1.20	0.0700	0.0700	8:14	34:30	74:15
3.94	0.1200	0.0610	9:53	40:26	86:00
2.02	0.0600	0.0593	10:15	41:45	88:37

Z: Vertical

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
3.94	**0.2500**	**0.2480**	**2:04**	**11:03**	**26:07**
2.53	0.2800	0.2225	2:29	12:45	29:40
2.02	0.3100	0.2205	2:30	12:53	30:00
3.14	0.2100	0.1861	3:16	16:00	36:32
6.37	0.1800	0.1800	3:27	16:38	38:00

* International Standards Organization ISO 2631:

Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)

RUN-10 Driver

8-OCT-93 16:14:21

1: **HET Ride Quality**
2: **Oct 4, 1993**
3: **Secondary A**
4: **Driver**
5: **20 mph**
6: **Loaded**

Third-octave bands with greatest weighted RMS accelerations (m/s^2)

Durations of WBV exposure before reaching ISO limits* (given in hours:minutes)

X: Longitudinal

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
3.94	**0.2200**	**0.1118**	**4:15**	**19:47**	**44:30**
2.02	0.1100	0.1087	4:26	20:30	45:56
5.05	0.2700	0.1069	4:33	20:55	46:45
6.37	0.3100	0.0973	5:11	23:25	51:51
1.61	0.0900	0.0900	5:48	25:45	56:36

Y: Transverse

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
1.61	**0.1900**	**0.1900**	**1:52**	**10:04**	**24:02**
2.02	0.1800	0.1778	2:03	11:00	26:00
1.20	0.1400	0.1400	3:01	14:57	34:26
2.53	0.1300	0.1029	4:48	21:53	48:45
7.98	0.3900	0.0977	5:09	23:17	51:41

Z: Vertical

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
2.02	**0.5800**	**0.4126**	**0:48**	**5:31**	**14:00**
2.53	0.5000	0.3974	0:52	5:50	14:41
1.61	0.3900	0.2476	2:05	11:04	26:10
3.94	0.2200	0.2183	2:33	13:03	30:22
6.37	0.1900	0.1900	3:11	15:34	35:41

* International Standards Organization ISO 2631:
Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)

RUN-10 . Front

8-OCT-93 16:14:21

1: **HET Ride Quality**
2: **Oct 4, 1993**
3: **Secondary A**
4: **Front**
5: **20 mph**
6: **Loaded**

Third-octave bands with greatest weighted RMS accelerations (m/s^2)

Durations of WBV exposure before reaching ISO limits* (given in hours:minutes)

X: Longitudinal

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
3.94	**0.1800**	**0.0914**	**5:41**	**25:15**	**55:36**
1.61	0.0900	0.0900	5:48	25:45	56:36
1.20	0.0900	0.0900	5:48	25:45	56:36
5.05	0.2200	0.0871	6:05	26:45	58:36
2.02	0.0800	0.0790	6:58	30:00	65:15

Y: Transverse

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
1.61	**0.1400**	**0.1400**	**3:01**	**14:57**	**34:26**
2.02	0.1400	0.1383	3:04	15:12	34:56
1.20	0.1300	0.1300	3:24	16:25	37:30
2.53	0.1100	0.0871	6:05	26:45	58:36
7.98	0.3200	0.0802	6:50	29:30	64:15

Z: Vertical

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
2.53	**0.4700**	**0.3735**	**1:00**	**6:22**	**15:52**
2.02	0.5200	0.3700	1:02	6:26	16:02
1.61	0.3700	0.2349	2:16	11:52	27:52
3.94	0.2200	0.2183	2:33	13:03	30:22
3.14	0.2200	0.1949	3:02	15:04	34:36

* International Standards Organization ISO 2631:

Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)

RUN-10 Roadside

8-OCT-93 16:14:21

1: **HET Ride Quality**
2: **Oct 4, 1993**
3: **Secondary A**
4: **Roadside**
5: **20 mph**
6: **Loaded**

Third-octave bands with greatest weighted RMS accelerations (m/s^2)

Durations of WBV exposure before reaching ISO limits* (given in hours:minutes)

X: Longitudinal

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
5.05	**0.4000**	**0.1583**	**2:30**	**12:48**	**29:52**
3.94	0.3000	0.1524	2:39	13:26	31:10
6.37	0.4400	0.1381	3:05	15:12	35:00
7.98	0.4600	0.1152	4:03	19:05	43:00
10.10	0.4500	0.0891	5:54	26:00	57:11

Y: Transverse

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
1.61	**0.1300**	**0.1300**	**3:24**	**16:25**	**37:30**
2.02	0.1200	0.1185	3:54	18:25	41:36
1.20	0.1100	0.1100	4:20	20:10	45:15
7.98	0.4200	0.1052	4:39	21:17	47:36
6.37	0.2700	0.0848	6:20	27:37	60:21

Z: Vertical

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
2.53	**0.4400**	**0.3497**	**1:09**	**6:58**	**17:13**
2.02	0.4800	0.3415	1:13	7:13	17:45
3.94	0.2900	0.2877	1:37	9:06	21:52
5.05	0.2800	0.2800	1:42	9:26	22:37
6.37	0.2600	0.2600	1:55	10:23	24:40

* International Standards Organization ISO 2631:
Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)

RUN-10 Curbside

8-OCT-93 16:14:21

1: **HET Ride Quality**
2: **Oct 4, 1993**
3: **Secondary A**
4: **Curbside**
5: **20 mph**
6: **Loaded**

Third-octave bands with greatest weighted RMS accelerations (m/s^2)

Durations of WBV exposure before reaching ISO limits* (given in hours:minutes)

X: Longitudinal

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
3.94	**0.3100**	**0.1575**	**2:30**	**12:53**	**30:00**
5.05	0.3700	0.1464	2:48	14:08	32:41
6.37	0.3800	0.1193	3:51	18:17	41:21
7.98	0.3900	0.0977	5:09	23:17	51:41
1.61	0.0800	0.0800	6:50	29:32	64:22

Y: Transverse

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
7.98	**0.4300**	**0.1077**	**4:28**	**20:43**	**46:21**
1.61	0.1000	0.1000	5:00	22:40	50:21
2.02	0.1000	0.0988	5:05	23:00	51:06
5.05	0.2400	0.0950	5:22	24:07	53:21
1.20	0.0900	0.0900	5:48	25:45	56:36

Z: Vertical

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
2.53	**0.4500**	**0.3576**	**1:07**	**6:46**	**16:45**
2.02	0.4600	0.3273	1:17	7:39	18:40
5.05	0.2800	0.2800	1:42	9:26	22:37
3.94	0.2600	0.2579	1:57	10:30	24:55
6.37	0.2400	0.2400	2:12	11:33	27:10

* International Standards Organization ISO 2631:

Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)

RUN-11 Driver

8-OCT-93 16:14:22

1: **HET Ride Quality**
2: **Oct 4, 1993**
3: **Secondary A**
4: **Driver**
5: **25 mph**
6: **Loaded**

Third-octave bands with greatest weighted RMS accelerations (m/s^2)

Durations of WBV exposure before reaching ISO limits* (given in hours:minutes)

X: Longitudinal

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
6.37	**0.3900**	**0.1224**	**3:43**	**17:40**	**40:06**
5.05	0.2300	0.0910	5:43	25:22	55:51
7.98	0.3400	0.0852	6:16	27:25	60:06
1.61	0.0800	0.0800	6:50	29:32	64:22
1.20	0.0800	0.0800	6:50	29:32	64:22

Y: Transverse

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
1.20	**0.1100**	**0.1100**	**4:20**	**20:10**	**45:15**
1.61	0.1000	0.1000	5:00	22:40	50:21
2.02	0.1000	0.0988	5:05	23:00	51:06
2.53	0.1200	0.0950	5:22	24:07	53:21
7.98	0.3500	0.0877	6:01	26:30	58:15

Z: Vertical

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
2.53	**0.4000**	**0.3179**	**1:22**	**7:56**	**19:22**
2.02	0.3700	0.2632	1:52	10:14	24:22
3.14	0.2400	0.2126	2:40	13:30	31:17
7.98	0.1800	0.1800	3:27	16:38	38:00
6.37	0.1800	0.1800	3:27	16:38	38:00

* International Standards Organization ISO 2631:
Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)

RUN-11 Front

8-OCT-93 16:14:22

1: **HET Ride Quality**
2: **Oct 4, 1993**
3: **Secondary A**
4: **Front**
5: **25 mph**
6: **Loaded**

Third-octave bands with greatest weighted RMS accelerations (m/s^2)

Durations of WBV exposure before reaching ISO limits* (given in hours:minutes)

X: Longitudinal

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
1.61	**0.0900**	**0.0900**	**5:48**	**25:45**	**56:36**
1.20	0.0900	0.0900	5:48	25:45	56:36
6.37	0.2800	0.0879	6:01	26:25	58:06
5.05	0.1900	0.0752	7:28	31:45	68:45
7.98	0.3000	0.0752	7:28	31:47	68:52

Y: Transverse

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
1.20	**0.1000**	**0.1000**	**5:00**	**22:40**	**50:21**
1.61	0.0800	0.0800	6:50	29:32	64:22
7.98	0.2900	0.0727	7:50	33:02	71:22
6.37	0.2300	0.0722	7:54	33:17	71:52
2.02	0.0600	0.0593	10:15	41:45	88:37

Z: Vertical

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
2.53	**0.4500**	**0.3576**	**1:07**	**6:46**	**16:45**
2.02	0.3800	0.2704	1:49	9:52	23:35
3.14	0.2800	0.2481	2:04	11:03	26:07
6.37	0.2000	0.2000	2:56	14:34	33:36
3.94	0.1900	0.1885	3:13	15:42	36:00

* International Standards Organization ISO 2631:
Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)

RUN-11 Roadside

8-OCT-93 16:14:22

1: **HET Ride Quality**
2: **Oct 4, 1993**
3: **Secondary A**
4: **Roadside**
5: **25 mph**
6: **Loaded**

Third-octave bands with greatest weighted RMS accelerations (m/s^2)

Durations of WBV exposure before reaching ISO limits* (given in hours:minutes)

X: Longitudinal

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
6.37	**0.5400**	**0.1695**	**2:14**	**11:42**	**27:32**
5.05	0.3500	0.1385	3:04	15:11	34:51
7.98	0.4500	0.1127	4:11	19:37	44:02
10.10	0.4900	0.0971	5:13	23:30	52:06
3.94	0.1900	0.0965	5:16	23:40	52:21

Y: Transverse

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
7.98	**0.3700**	**0.0927**	**5:35**	**24:50**	**54:45**
6.37	0.2900	0.0910	5:43	25:22	55:51
1.20	0.0900	0.0900	5:48	25:45	56:36
1.61	0.0800	0.0800	6:50	29:32	64:22
10.10	0.3700	0.0733	7:43	32:45	70:45

Z: Vertical

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
6.37	**0.3500**	**0.3500**	**1:09**	**6:58**	**17:13**
2.53	0.3400	0.2702	1:49	9:53	23:37
7.98	0.2300	0.2300	2:20	12:12	28:32
3.94	0.2300	0.2282	2:23	12:19	28:52
5.05	0.2200	0.2200	2:31	12:56	30:07

* International Standards Organization ISO 2631:

Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)

RUN-11 Curbside

8-OCT-93 16:14:22

1: **HET Ride Quality**
2: **Oct 4, 1993**
3: **Secondary A**
4: **Curbside**
5: **25 mph**
6: **Loaded**

Third-octave bands with greatest weighted RMS accelerations (m/s^2)

Durations of WBV exposure before reaching ISO limits* (given in hours:minutes)

X: Longitudinal

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
6.37	**0.5000**	**0.1570**	**2:31**	**12:56**	**30:07**
5.05	0.3500	0.1385	3:04	15:11	34:51
7.98	0.4600	0.1152	4:03	19:05	43:00
3.94	0.1900	0.0965	5:16	23:40	52:21
10.10	0.4200	0.0832	6:30	28:15	61:36

Y: Transverse

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
6.37	**0.3200**	**0.1005**	**4:58**	**22:32**	**50:06**
7.98	0.3800	0.0952	5:22	24:02	53:15
1.20	0.0800	0.0800	6:50	29:32	64:22
10.10	0.3900	0.0773	7:11	30:47	66:45
5.05	0.1900	0.0752	7:28	31:45	68:45

Z: Vertical

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
6.37	**0.3400**	**0.3400**	**1:13**	**7:15**	**17:50**
2.53	0.4000	0.3179	1:22	7:56	19:22
2.02	0.3300	0.2348	2:16	11:53	27:52
3.14	0.2600	0.2304	2:20	12:11	28:30
3.94	0.2100	0.2083	2:45	13:52	32:02

* International Standards Organization ISO 2631:

Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)

RUN-12 Driver

8-OCT-93 16:14:23

1: **HET Ride Quality**
2: **Oct 4, 1993**
3: **Cross Country #2**
4: **Driver**
5: **5 mph**
6: **No Load**

Third-octave bands with greatest weighted RMS accelerations (m/s^2)

Durations of WBV exposure before reaching ISO limits* (given in hours:minutes)

X: Longitudinal

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
2.02	**0.0400**	**0.0395**	**17:15**	**65:22**	**134:30**
2.53	0.0400	0.0317	22:37	82:52	168:00
1.61	0.0300	0.0300	24:08	87:45	177:15
6.37	0.0800	0.0251	29:47	105:30	211:00
5.05	0.0600	0.0237	31:47	111:45	222:30

Y: Transverse

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
1.61	**0.1000**	**0.1000**	**5:00**	**22:40**	**50:21**
1.20	0.0900	0.0900	5:48	25:45	56:36
2.02	0.0600	0.0593	10:15	41:45	88:37
2.53	0.0400	0.0317	22:37	82:52	168:00
3.14	0.0400	0.0255	29:17	104:00	208:00

Z: Vertical

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
2.02	**0.2200**	**0.1565**	**4:15**	**19:47**	**44:30**
2.53	0.1400	0.1113	6:54	29:47	64:45
1.61	0.1700	0.1079	7:13	30:52	67:00
3.14	0.0800	0.0709	12:37	49:47	104:30
7.98	0.0600	0.0600	15:37	59:51	124:00

* International Standards Organization ISO 2631:

Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)

RUN-12 Front

8-OCT-93 16:14:23

1: **HET Ride Quality**
2: **Oct 4, 1993**
3: **Cross Country #2**
4: **Front**
5: **5 mph**
6: **No Load**

Third-octave bands with greatest weighted RMS accelerations (m/s^2)

Durations of WBV exposure before reaching ISO limits* (given in hours:minutes)

X: Longitudinal

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
1.61	**0.0600**	**0.0600**	**10:07**	**41:11**	**87:30**
1.20	0.0400	0.0400	17:00	64:30	133:00
2.02	0.0400	0.0395	17:15	65:22	134:30
12.74	0.2300	0.0361	19:17	72:00	147:15
15.97	0.2200	0.0276	26:45	95:45	192:30

Y: Transverse

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
1.61	**0.1000**	**0.1000**	**5:00**	**22:40**	**50:21**
1.20	0.1000	0.1000	5:00	22:40	50:21
2.02	0.0500	0.0494	13:00	51:15	107:15
7.98	0.1200	0.0301	24:07	87:30	177:00
3.94	0.0400	0.0203	38:06	131:00	258:30

Z: Vertical

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
2.02	**0.2200**	**0.1565**	**4:15**	**19:47**	**44:30**
2.53	0.1600	0.1272	5:43	25:25	56:00
1.61	0.1600	0.1016	7:50	33:06	71:30
3.94	0.0900	0.0893	9:19	38:26	82:00
3.14	0.0900	0.0797	10:49	43:36	92:22

* International Standards Organization ISO 2631:

Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)

RUN-12 Roadside

8-OCT-93 16:14:23

1: **HET Ride Quality**
2: **Oct 4, 1993**
3: **Cross Country #2**
4: **Roadside**
5: **5 mph**
6: **No Load**

Third-octave bands with greatest weighted RMS accelerations (m/s^2)

Durations of WBV exposure before reaching ISO limits* (given in hours:minutes)

X: Longitudinal

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
6.37	**0.1300**	**0.0408**	**16:35**	**63:06**	**130:15**
1.61	0.0400	0.0400	17:00	64:30	133:00
2.02	0.0400	0.0395	17:15	65:22	134:30
2.53	0.0400	0.0317	22:37	82:52	168:00
7.98	0.1200	0.0301	24:07	87:30	177:00

Y: Transverse

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
1.20	**0.0700**	**0.0700**	**8:14**	**34:30**	**74:15**
1.61	0.0600	0.0600	10:07	41:11	87:30
2.02	0.0400	0.0395	17:15	65:22	134:30
7.98	0.1100	0.0276	26:45	95:45	192:30
5.05	0.0600	0.0237	31:47	111:45	222:30

Z: Vertical

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
2.02	**0.1900**	**0.1352**	**5:16**	**23:38**	**52:21**
1.61	0.1500	0.0952	8:33	35:41	76:37
7.98	0.0900	0.0900	9:12	38:02	81:15
2.53	0.1100	0.0874	9:34	39:21	83:52
6.37	0.0800	0.0800	10:47	43:30	92:00

* International Standards Organization ISO 2631:

Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)

RUN-12 Curbside

8-OCT-93 16:14:23

1: **HET Ride Quality**
2: **Oct 4, 1993**
3: **Cross Country #2**
4: **Curbside**
5: **5 mph**
6: **No Load**

Third-octave bands with greatest weighted RMS accelerations (m/s^2)

Durations of WBV exposure before reaching ISO limits* (given in hours:minutes)

X: Longitudinal

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
1.61	**0.0500**	**0.0500**	**12:49**	**50:30**	**105:45**
1.20	0.0400	0.0400	17:00	64:30	133:00
2.02	0.0400	0.0395	17:15	65:22	134:30
6.37	0.1200	0.0377	18:17	68:45	141:15
2.53	0.0400	0.0317	22:37	82:52	168:00

Y: Transverse

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
1.20	**0.0600**	**0.0600**	**10:07**	**41:11**	**87:30**
1.61	0.0500	0.0500	12:49	50:30	105:45
2.02	0.0300	0.0296	24:30	88:45	179:30
7.98	0.1100	0.0276	26:45	95:45	192:30
12.74	0.1600	0.0251	29:47	105:30	210:45

Z: Vertical

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
2.02	**0.1900**	**0.1352**	**5:16**	**23:38**	**52:21**
2.53	0.1300	0.1033	7:39	32:30	70:15
1.61	0.1400	0.0889	9:22	38:36	82:30
6.37	0.0800	0.0800	10:47	43:30	92:00
3.94	0.0700	0.0694	12:57	51:00	106:45

* International Standards Organization ISO 2631:

Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)

RUN-13 Driver

8-OCT-93 16:14:23

1: **HET Ride Quality**
2: **Oct 4, 1993**
3: **Cross Country #2**
4: **Driver**
5: **10 mph**
6: **No Load**

Third-octave bands with greatest weighted RMS accelerations (m/s^2)

Durations of WBV exposure before reaching ISO limits* (given in hours:minutes)

X: Longitudinal

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
2.02	**0.1100**	**0.1087**	**4:26**	**20:30**	**45:56**
1.61	0.1000	0.1000	5:00	22:40	50:21
2.53	0.1200	0.0950	5:22	24:07	53:21
5.05	0.2300	0.0910	5:43	25:22	55:51
6.37	0.2500	0.0785	7:01	30:15	65:45

Y: Transverse

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
1.20	**0.2600**	**0.2600**	**1:05**	**6:35**	**16:22**
1.61	0.1600	0.1600	2:27	12:37	29:30
2.02	0.1200	0.1185	3:54	18:25	41:36
2.53	0.1300	0.1029	4:48	21:53	48:45
3.14	0.1200	0.0764	7:18	31:10	67:37

Z: Vertical

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
2.53	**0.4000**	**0.3179**	**1:22**	**7:56**	**19:22**
1.61	0.5000	0.3174	1:22	7:58	19:25
2.02	0.4100	0.2917	1:36	8:56	21:30
3.14	0.2500	0.2215	2:30	12:48	29:52
1.20	0.3600	0.1975	3:00	14:49	34:06

* International Standards Organization ISO 2631:
Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)

RUN-13 Front

8-OCT-93 16:14:23

1: **HET Ride Quality**
2: **Oct 4, 1993**
3: **Cross Country #2**
4: **Front**
5: **10 mph**
6: **No Load**

Third-octave bands with greatest weighted RMS accelerations (m/s^2)

Durations of WBV exposure before reaching ISO limits* (given in hours:minutes)

X: Longitudinal

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
2.02	**0.1000**	**0.0988**	**5:05**	**23:00**	**51:06**
2.53	0.1200	0.0950	5:22	24:07	53:21
1.61	0.0900	0.0900	5:48	25:45	56:36
1.20	0.0900	0.0900	5:48	25:45	56:36
5.05	0.1800	0.0712	8:02	33:51	72:52

Y: Transverse

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
1.20	**0.2600**	**0.2600**	**1:05**	**6:35**	**16:22**
1.61	0.1600	0.1600	2:27	12:37	29:30
2.02	0.1000	0.0988	5:05	23:00	51:06
2.53	0.1100	0.0871	6:05	26:45	58:36
6.37	0.2600	0.0816	6:39	28:52	63:00

Z: Vertical

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
2.02	**0.4500**	**0.3202**	**1:21**	**7:52**	**19:10**
2.53	0.4000	0.3179	1:22	7:56	19:22
1.61	0.5000	0.3174	1:22	7:58	19:25
3.14	0.3000	0.2658	1:52	10:07	24:02
3.94	0.2500	0.2480	2:04	11:03	26:07

* International Standards Organization ISO 2631:

Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)

RUN-13 Roadside

8-OCT-93 16:14:23

1: **HET Ride Quality**
2: **Oct 4, 1993**
3: **Cross Country #2**
4: **Roadside**
5: **10 mph**
6: **No Load**

Third-octave bands with greatest weighted RMS accelerations (m/s^2)

Durations of WBV exposure before reaching ISO limits* (given in hours:minutes)

X: Longitudinal

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
5.05	**0.3400**	**0.1346**	**3:13**	**15:45**	**36:00**
6.37	0.3500	0.1099	4:22	20:13	45:21
2.02	0.1000	0.0988	5:05	23:00	51:06
2.53	0.1200	0.0950	5:22	24:07	53:21
1.61	0.0900	0.0900	5:48	25:45	56:36

Y: Transverse

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
1.20	**0.2000**	**0.2000**	**1:42**	**9:26**	**22:37**
1.61	0.1100	0.1100	4:20	20:10	45:15
6.37	0.2800	0.0879	6:01	26:25	58:06
2.02	0.0800	0.0790	6:58	30:00	65:15
2.53	0.0900	0.0712	8:02	33:51	72:52

Z: Vertical

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
1.61	**0.4300**	**0.2730**	**1:46**	**9:45**	**23:17**
5.05	0.2400	0.2400	2:12	11:33	27:10
2.53	0.3000	0.2384	2:13	11:38	27:22
2.02	0.3300	0.2348	2:16	11:53	27:52
3.94	0.2300	0.2282	2:23	12:19	28:52

* International Standards Organization ISO 2631:

Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)

RUN-13 Curbside

8-OCT-93 16:14:23

1: **HET Ride Quality**
2: **Oct 4, 1993**
3: **Cross Country #2**
4: **Curbside**
5: **10 mph**
6: **No Load**

Third-octave bands with greatest weighted RMS accelerations (m/s^2)

Durations of WBV exposure before reaching ISO limits* (given in hours:minutes)

X: Longitudinal

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
2.53	**0.1600**	**0.1266**	**3:31**	**16:58**	**38:36**
5.05	0.3000	0.1187	3:53	18:23	41:32
2.02	0.1100	0.1087	4:26	20:30	45:56
1.61	0.1000	0.1000	5:00	22:40	50:21
1.20	0.0900	0.0900	5:48	25:45	56:36

Y: Transverse

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
1.20	**0.1800**	**0.1800**	**2:01**	**10:49**	**25:38**
1.61	0.1000	0.1000	5:00	22:40	50:21
6.37	0.2800	0.0879	6:01	26:25	58:06
5.05	0.1900	0.0752	7:28	31:45	68:45
7.98	0.2800	0.0702	8:12	34:26	74:07

Z: Vertical

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
5.05	**0.2900**	**0.2900**	**1:37**	**9:00**	**21:40**
1.61	0.4300	0.2730	1:46	9:45	23:17
2.02	0.3600	0.2561	1:59	10:37	25:10
2.53	0.3200	0.2543	2:00	10:42	25:22
3.94	0.2300	0.2282	2:23	12:19	28:52

* International Standards Organization ISO 2631:

Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)

RUN-14 Driver

8-OCT-93 16:14:24

1: **HET Ride Quality**
2: **Oct 4, 1993**
3: **Cross Country #2**
4: **Driver**
5: **15 mph**
6: **No Load**

Third-octave bands with greatest weighted RMS accelerations (m/s^2)

Durations of WBV exposure before reaching ISO limits* (given in hours:minutes)

X: Longitudinal

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
1.61	**0.1900**	**0.1900**	**1:52**	**10:04**	**24:02**
2.02	0.1800	0.1778	2:03	11:00	26:00
1.20	0.1200	0.1200	3:49	18:08	41:02
3.94	0.2300	0.1168	3:59	18:45	42:21
2.53	0.1400	0.1108	4:18	20:00	44:56

Y: Transverse

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
1.61	**0.2700**	**0.2700**	**0:57**	**6:16**	**15:37**
1.20	0.2600	0.2600	1:05	6:35	16:22
2.02	0.2500	0.2470	1:10	7:05	17:28
3.14	0.2000	0.1274	3:30	16:52	38:21
3.94	0.2500	0.1270	3:30	16:55	38:30

Z: Vertical

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
1.61	**0.8200**	**0.5206**	**0:30**	**3:57**	**10:22**
2.02	0.7000	0.4980	0:33	4:13	10:57
2.53	0.4300	0.3418	1:13	7:11	17:43
1.20	0.5500	0.3017	1:30	8:32	20:38
3.94	0.2600	0.2579	1:57	10:30	24:55

* International Standards Organization ISO 2631:
Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)

RUN-14 Front

8-OCT-93 16:14:24

1: **HET Ride Quality**
2: **Oct 4, 1993**
3: **Cross Country #2**
4: **Front**
5: **15 mph**
6: **No Load**

Third-octave bands with greatest weighted RMS accelerations (m/s^2)

Durations of WBV exposure before reaching ISO limits* (given in hours:minutes)

X: Longitudinal

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
1.61	**0.1900**	**0.1900**	**1:52**	**10:04**	**24:02**
2.02	0.1700	0.1679	2:15	11:52	27:52
1.20	0.1200	0.1200	3:49	18:08	41:02
6.37	0.3300	0.1036	4:45	21:45	48:26
2.53	0.1300	0.1029	4:48	21:53	48:45

Y: Transverse

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
1.20	**0.2700**	**0.2700**	**0:57**	**6:16**	**15:37**
1.61	0.2200	0.2200	1:27	8:18	20:07
2.02	0.1900	0.1877	1:53	10:15	24:23
3.14	0.2100	0.1337	3:15	15:52	36:15
3.94	0.2400	0.1219	3:44	17:47	40:21

Z: Vertical

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
2.02	**0.8800**	**0.6261**	**0:18**	**2:59**	**8:04**
1.61	0.9200	0.5840	0:22	3:18	8:53
2.53	0.4900	0.3894	0:55	6:00	15:03
1.20	0.5800	0.3181	1:22	7:56	19:22
3.94	0.3100	0.3076	1:27	8:18	20:10

* International Standards Organization ISO 2631:

Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)

RUN-14 Roadside

8-OCT-93 16:14:24

1: **HET Ride Quality**
2: **Oct 4, 1993**
3: **Cross Country #2**
4: **Roadside**
5: **15 mph**
6: **No Load**

Third-octave bands with greatest weighted RMS accelerations (m/s^2)

Durations of WBV exposure before reaching ISO limits* (given in hours:minutes)

X: Longitudinal

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
3.94	**0.3000**	**0.1524**	**2:39**	**13:26**	**31:10**
1.61	0.1400	0.1400	3:01	14:57	34:26
5.05	0.3500	0.1385	3:04	15:11	34:51
2.02	0.1400	0.1383	3:04	15:12	34:56
6.37	0.4300	0.1350	3:12	15:41	35:51

Y: Transverse

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
1.20	**0.2200**	**0.2200**	**1:27**	**8:18**	**20:07**
1.61	0.1900	0.1900	1:52	10:04	24:02
5.05	0.4100	0.1623	2:24	12:23	29:00
2.02	0.1600	0.1581	2:30	12:49	29:55
3.94	0.2200	0.1118	4:15	19:47	44:30

Z: Vertical

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
1.61	**0.7100**	**0.4507**	**0:40**	**4:52**	**12:30**
2.02	0.5900	0.4198	0:47	5:24	13:41
3.94	0.4200	0.4167	0:47	5:26	13:48
5.05	0.3200	0.3200	1:22	7:52	19:13
2.53	0.3800	0.3020	1:30	8:30	20:37

* International Standards Organization ISO 2631:
Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)

RUN-14 Curbside

8-OCT-93 16:14:24

1: **HET Ride Quality**
2: **Oct 4, 1993**
3: **Cross Country #2**
4: **Curbside**
5: **15 mph**
6: **No Load**

Third-octave bands with greatest weighted RMS accelerations (m/s^2)

Durations of WBV exposure before reaching ISO limits* (given in hours:minutes)

X: Longitudinal

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
3.94	**0.3100**	**0.1575**	**2:30**	**12:53**	**30:00**
1.61	0.1300	0.1300	3:24	16:25	37:30
1.20	0.1200	0.1200	3:49	18:08	41:02
6.37	0.3800	0.1193	3:51	18:17	41:21
2.02	0.1200	0.1185	3:54	18:25	41:36

Y: Transverse

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
1.20	**0.1700**	**0.1700**	**2:14**	**11:41**	**27:25**
5.05	0.4200	0.1662	2:18	12:00	28:10
1.61	0.1400	0.1400	3:01	14:57	34:26
2.02	0.1200	0.1185	3:54	18:25	41:36
6.37	0.3700	0.1162	4:01	18:53	42:36

Z: Vertical

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
2.02	**0.7400**	**0.5265**	**0:30**	**3:53**	**10:12**
1.61	0.7900	0.5015	0:32	4:09	10:52
3.94	0.3700	0.3671	1:04	6:31	16:13
2.53	0.4100	0.3259	1:19	7:41	18:47
5.05	0.3100	0.3100	1:25	8:12	20:00

* International Standards Organization ISO 2631:

Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)

RUN-15 Driver

8-OCT-93 16:14:25

1: **HET Ride Quality**
2: **Oct 4, 1993**
3: **Secondary A**
4: **Driver**
5: **15 mph**
6: **No Load**

Third-octave bands with greatest weighted RMS accelerations (m/s^2)

Durations of WBV exposure before reaching ISO limits* (given in hours:minutes)

X: Longitudinal

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
2.02	**0.0800**	**0.0790**	**6:58**	**30:00**	**65:15**
6.37	0.2400	0.0753	7:26	31:40	68:37
7.98	0.2800	0.0702	8:12	34:26	74:07
2.53	0.0700	0.0554	11:12	45:00	95:00
1.61	0.0500	0.0500	12:49	50:30	105:45

Y: Transverse

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
1.61	**0.1100**	**0.1100**	**4:20**	**20:10**	**45:15**
2.02	0.1100	0.1087	4:26	20:30	45:56
7.98	0.3200	0.0802	6:50	29:30	64:15
1.20	0.0700	0.0700	8:14	34:30	74:15
3.14	0.0800	0.0510	12:30	49:30	103:45

Z: Vertical

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
2.02	**0.3700**	**0.2632**	**1:52**	**10:14**	**24:22**
2.53	0.2700	0.2146	2:38	13:19	31:00
1.61	0.3000	0.1904	3:10	15:30	35:36
7.98	0.1700	0.1700	3:45	17:52	40:30
3.94	0.1700	0.1687	3:47	18:02	40:51

* International Standards Organization ISO 2631:

Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)

RUN-15 Front

8-OCT-93 16:14:25

1: **HET Ride Quality**
2: **Oct 4, 1993**
3: **Secondary A**
4: **Front**
5: **15 mph**
6: **No Load**

Third-octave bands with greatest weighted RMS accelerations (m/s^2)

Durations of WBV exposure before reaching ISO limits* (given in hours:minutes)

X: Longitudinal

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
7.98	**0.2400**	**0.0601**	**10:04**	**41:06**	**87:15**
1.61	0.0600	0.0600	10:07	41:11	87:30
6.37	0.1900	0.0596	10:11	41:26	88:00
2.02	0.0600	0.0593	10:15	41:45	88:37
10.10	0.2200	0.0436	15:15	58:45	121:45

Y: Transverse

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
1.61	**0.1000**	**0.1000**	**5:00**	**22:40**	**50:21**
2.02	0.0900	0.0889	5:54	26:07	57:21
1.20	0.0800	0.0800	6:50	29:32	64:22
7.98	0.3100	0.0777	7:09	30:37	66:30
3.94	0.1000	0.0508	12:33	49:36	104:00

Z: Vertical

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
2.02	**0.4000**	**0.2846**	**1:39**	**9:14**	**22:10**
3.94	0.2400	0.2381	2:14	11:41	27:25
2.53	0.2900	0.2305	2:20	12:11	28:30
1.61	0.3100	0.1968	3:00	14:53	34:15
3.14	0.2100	0.1861	3:16	16:00	36:32

* International Standards Organization ISO 2631:

Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)

RUN-15 Roadside

8-OCT-93 16:14:25

1: **HET Ride Quality**
2: **Oct 4, 1993**
3: **Secondary A**
4: **Roadside**
5: **15 mph**
6: **No Load**

Third-octave bands with greatest weighted RMS accelerations (m/s^2)

Durations of WBV exposure before reaching ISO limits* (given in hours:minutes)

X: Longitudinal

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
6.37	**0.3600**	**0.1130**	**4:11**	**19:32**	**43:56**
7.98	0.3500	0.0877	6:01	26:30	58:15
5.05	0.1600	0.0633	9:25	38:45	82:37
2.02	0.0600	0.0593	10:15	41:45	88:37
3.94	0.1000	0.0508	12:33	49:36	104:00

Y: Transverse

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
7.98	**0.4300**	**0.1077**	**4:28**	**20:43**	**46:21**
1.61	0.0700	0.0700	8:14	34:30	74:15
2.02	0.0700	0.0691	8:22	35:00	75:15
5.05	0.1700	0.0673	8:41	36:06	77:30
1.20	0.0600	0.0600	10:07	41:11	87:30

Z: Vertical

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
2.02	**0.3200**	**0.2277**	**2:24**	**12:22**	**28:55**
5.05	0.2100	0.2100	2:43	13:42	31:45
6.37	0.2000	0.2000	2:56	14:34	33:36
3.94	0.2000	0.1984	2:58	14:45	33:56
7.98	0.1800	0.1800	3:27	16:38	38:00

* International Standards Organization ISO 2631:
Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)

RUN-15 Curbside

8-OCT-93 16:14:25

1: **HET Ride Quality**
2: **Oct 4, 1993**
3: **Secondary A**
4: **Curbside**
5: **15 mph**
6: **No Load**

Third-octave bands with greatest weighted RMS accelerations (m/s^2)

Durations of WBV exposure before reaching ISO limits* (given in hours:minutes)

X: Longitudinal

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
6.37	**0.3300**	**0.1036**	**4:45**	**21:45**	**48:26**
7.98	0.3000	0.0752	7:28	31:47	68:52
2.02	0.0700	0.0691	8:22	35:00	75:15
5.05	0.1700	0.0673	8:41	36:06	77:30
3.94	0.1200	0.0610	9:53	40:26	86:00

Y: Transverse

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
7.98	**0.4300**	**0.1077**	**4:28**	**20:43**	**46:21**
5.05	0.1800	0.0712	8:02	33:51	72:52
1.61	0.0600	0.0600	10:07	41:11	87:30
2.02	0.0600	0.0593	10:15	41:45	88:37
6.37	0.1800	0.0565	10:56	44:02	93:15

Z: Vertical

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
2.02	**0.3500**	**0.2490**	**2:03**	**11:00**	**26:00**
3.94	0.2000	0.1984	2:58	14:45	33:56
1.61	0.2800	0.1778	3:30	16:55	38:30
2.53	0.2200	0.1749	3:35	17:15	39:15
6.37	0.1500	0.1500	4:31	20:52	46:36

* International Standards Organization ISO 2631:

Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)

RUN-16 Driver

8-OCT-93 16:14:26

1: **HET Ride Quality**
2: **Oct 4, 1993**
3: **Secondary A**
4: **Driver**
5: **20 mph**
6: **No Load**

Third-octave bands with greatest weighted RMS accelerations (m/s^2)

Durations of WBV exposure before reaching ISO limits* (given in hours:minutes)

X: Longitudinal

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
2.02	**0.1200**	**0.1185**	**3:54**	**18:25**	**41:36**
5.05	0.2900	0.1148	4:05	19:10	43:11
2.53	0.1200	0.0950	5:22	24:07	53:21
6.37	0.3000	0.0942	5:26	24:22	53:51
1.61	0.0900	0.0900	5:48	25:45	56:36

Y: Transverse

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
1.20	**0.1600**	**0.1600**	**2:27**	**12:37**	**29:30**
1.61	0.1400	0.1400	3:01	14:57	34:26
2.53	0.1600	0.1266	3:31	16:58	38:36
2.02	0.1200	0.1185	3:54	18:25	41:36
7.98	0.4000	0.1002	4:58	22:37	50:15

Z: Vertical

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
2.53	**0.5400**	**0.4292**	**0:45**	**5:13**	**13:18**
2.02	0.4300	0.3059	1:28	8:22	20:17
1.61	0.4000	0.2539	2:00	10:44	25:25
3.14	0.2500	0.2215	2:30	12:48	29:52
3.94	0.1900	0.1885	3:13	15:42	36:00

* International Standards Organization ISO 2631:

Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)

RUN-16 Front

8-OCT-93 16:14:26

1: **HET Ride Quality**
2: **Oct 4, 1993**
3: **Secondary A**
4: **Front**
5: **20 mph**
6: **No Load**

Third-octave bands with greatest weighted RMS accelerations (m/s^2)

Durations of WBV exposure before reaching ISO limits* (given in hours:minutes)

X: Longitudinal

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
5.05	**0.2500**	**0.0989**	**5:05**	**22:58**	**51:00**
2.02	0.0900	0.0889	5:54	26:07	57:21
7.98	0.3500	0.0877	6:01	26:30	58:15
6.37	0.2600	0.0816	6:39	28:52	63:00
1.20	0.0800	0.0800	6:50	29:32	64:22

Y: Transverse

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
1.20	**0.1500**	**0.1500**	**2:43**	**13:42**	**31:45**
1.61	0.1400	0.1400	3:01	14:57	34:26
2.53	0.1400	0.1108	4:18	20:00	44:56
2.02	0.1100	0.1087	4:26	20:30	45:56
7.98	0.3600	0.0902	5:48	25:40	56:30

Z: Vertical

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
2.53	**0.5900**	**0.4689**	**0:37**	**4:35**	**11:52**
2.02	0.4900	0.3486	1:09	7:00	17:17
1.61	0.4200	0.2666	1:51	10:03	24:00
3.14	0.2900	0.2569	1:58	10:33	25:02
3.94	0.2300	0.2282	2:23	12:19	28:52

* International Standards Organization ISO 2631:
Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)

RUN-16 Roadside

8-OCT-93 16:14:26

1: **HET Ride Quality**
2: **Oct 4, 1993**
3: **Secondary A**
4: **Roadside**
5: **20 mph**
6: **No Load**

Third-octave bands with greatest weighted RMS accelerations (m/s^2)

Durations of WBV exposure before reaching ISO limits* (given in hours:minutes)

X: Longitudinal

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
5.05	**0.4600**	**0.1821**	**2:00**	**10:41**	**25:17**
6.37	0.4300	0.1350	3:12	15:41	35:51
7.98	0.4200	0.1052	4:39	21:17	47:36
2.02	0.1000	0.0988	5:05	23:00	51:06
2.53	0.1200	0.0950	5:22	24:07	53:21

Y: Transverse

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
1.20	**0.1300**	**0.1300**	**3:24**	**16:25**	**37:30**
1.61	0.1200	0.1200	3:49	18:08	41:02
7.98	0.4700	0.1178	3:56	18:35	41:56
6.37	0.3100	0.0973	5:11	23:25	51:51
2.02	0.0900	0.0889	5:54	26:07	57:21

Z: Vertical

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
5.05	**0.3600**	**0.3600**	**1:06**	**6:41**	**16:37**
2.53	0.4100	0.3259	1:19	7:41	18:47
6.37	0.2800	0.2800	1:42	9:26	22:37
2.02	0.3600	0.2561	1:59	10:37	25:10
3.94	0.2500	0.2480	2:04	11:03	26:07

* International Standards Organization ISO 2631:
Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)

RUN-16 Curbside

8-OCT-93 16:14:26

1: **HET Ride Quality**
2: **Oct 4, 1993**
3: **Secondary A**
4: **Curbside**
5: **20 mph**
6: **No Load**

Third-octave bands with greatest weighted RMS accelerations (m/s^2)

Durations of WBV exposure before reaching ISO limits* (given in hours:minutes)

X: Longitudinal

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
5.05	**0.4300**	**0.1702**	**2:14**	**11:38**	**27:25**
6.37	0.3700	0.1162	4:01	18:53	42:36
2.02	0.1100	0.1087	4:26	20:30	45:56
2.53	0.1300	0.1029	4:48	21:53	48:45
7.98	0.3900	0.0977	5:09	23:17	51:41

Y: Transverse

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
7.98	**0.4800**	**0.1203**	**3:48**	**18:07**	**41:00**
6.37	0.3300	0.1036	4:45	21:45	48:26
5.05	0.2600	0.1029	4:48	21:53	48:45
1.61	0.1000	0.1000	5:00	22:40	50:21
1.20	0.1000	0.1000	5:00	22:40	50:21

Z: Vertical

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
2.53	**0.4500**	**0.3576**	**1:07**	**6:46**	**16:45**
5.05	0.3200	0.3200	1:22	7:52	19:13
2.02	0.3800	0.2704	1:49	9:52	23:35
1.61	0.3700	0.2349	2:16	11:52	27:52
6.37	0.2300	0.2300	2:20	12:12	28:32

* International Standards Organization ISO 2631:

Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)

RUN-17 Driver

8-OCT-93 16:14:27

1: **HET Ride Quality**
2: **Oct 4, 1993**
3: **Secondary A**
4: **Driver**
5: **25 mph**
6: **No Load**

Third-octave bands with greatest weighted RMS accelerations (m/s^2)

Durations of WBV exposure before reaching ISO limits* (given in hours:minutes)

X: Longitudinal

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
6.37	**0.3200**	**0.1005**	**4:58**	**22:32**	**50:06**
2.02	0.0900	0.0889	5:54	26:07	57:21
2.53	0.1100	0.0871	6:05	26:45	58:36
5.05	0.2100	0.0831	6:30	28:15	61:45
7.98	0.2800	0.0702	8:12	34:26	74:07

Y: Transverse

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
1.61	**0.1400**	**0.1400**	**3:01**	**14:57**	**34:26**
1.20	0.1400	0.1400	3:01	14:57	34:26
3.14	0.1500	0.0955	5:20	23:55	53:00
2.53	0.1200	0.0950	5:22	24:07	53:21
2.02	0.0800	0.0790	6:58	30:00	65:15

Z: Vertical

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
2.53	**0.4100**	**0.3259**	**1:19**	**7:41**	**18:47**
3.14	0.3600	0.3190	1:22	7:54	19:17
2.02	0.3700	0.2632	1:52	10:14	24:22
1.61	0.3700	0.2349	2:16	11:52	27:52
7.98	0.1700	0.1700	3:45	17:52	40:30

* International Standards Organization ISO 2631:

Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)

RUN-17 . Front

8-OCT-93 16:14:27

1: **HET Ride Quality**
2: **Oct 4, 1993**
3: **Secondary A**
4: **Front**
5: **25 mph**
6: **No Load**

Third-octave bands with greatest weighted RMS accelerations (m/s^2)

Durations of WBV exposure before reaching ISO limits* (given in hours:minutes)

X: Longitudinal

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
2.53	**0.1200**	**0.0950**	**5:22**	**24:07**	**53:21**
6.37	0.3000	0.0942	5:26	24:22	53:51
7.98	0.3400	0.0852	6:16	27:25	60:06
10.10	0.3900	0.0773	7:11	30:47	66:45
5.05	0.1900	0.0752	7:28	31:45	68:45

Y: Transverse

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
1.20	**0.1400**	**0.1400**	**3:01**	**14:57**	**34:26**
1.61	0.1300	0.1300	3:24	16:25	37:30
2.53	0.1000	0.0792	6:58	29:55	65:07
2.02	0.0800	0.0790	6:58	30:00	65:15
3.14	0.1200	0.0764	7:18	31:10	67:37

Z: Vertical

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
2.53	**0.4200**	**0.3338**	**1:15**	**7:26**	**18:15**
3.14	0.3600	0.3190	1:22	7:54	19:17
2.02	0.4400	0.3130	1:24	8:07	19:45
1.61	0.4100	0.2603	1:55	10:23	24:40
3.94	0.1900	0.1885	3:13	15:42	36:00

* International Standards Organization ISO 2631:

Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)

RUN-17 Roadside

8-OCT-93 16:14:27

1: **HET Ride Quality**
2: **Oct 4, 1993**
3: **Secondary A**
4: **Roadside**
5: **25 mph**
6: **No Load**

Third-octave bands with greatest weighted RMS accelerations (m/s^2)

Durations of WBV exposure before reaching ISO limits* (given in hours:minutes)

X: Longitudinal

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
6.37	**0.4700**	**0.1476**	**2:47**	**14:00**	**32:21**
5.05	0.3400	0.1346	3:13	15:45	36:00
7.98	0.3600	0.0902	5:48	25:40	56:30
10.10	0.3900	0.0773	7:11	30:47	66:45
12.74	0.4800	0.0754	7:26	31:40	68:37

Y: Transverse

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
1.20	**0.1200**	**0.1200**	**3:49**	**18:08**	**41:02**
1.61	0.1100	0.1100	4:20	20:10	45:15
6.37	0.2900	0.0910	5:43	25:22	55:51
7.98	0.2900	0.0727	7:50	33:02	71:22
2.02	0.0700	0.0691	8:22	35:00	75:15

Z: Vertical

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
6.37	**0.3000**	**0.3000**	**1:30**	**8:36**	**20:47**
3.14	0.3000	0.2658	1:52	10:07	24:02
2.53	0.3100	0.2464	2:06	11:08	26:22
2.02	0.3300	0.2348	2:16	11:53	27:52
5.05	0.2300	0.2300	2:20	12:12	28:32

* International Standards Organization ISO 2631:

Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)

RUN-17 Curbside

8-OCT-93 16:14:27

1: **HET Ride Quality**
2: **Oct 4, 1993**
3: **Secondary A**
4: **Curbside**
5: **25 mph**
6: **No Load**

Third-octave bands with greatest weighted RMS accelerations (m/s^2)

Durations of WBV exposure before reaching ISO limits* (given in hours:minutes)

X: Longitudinal

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
6.37	**0.4300**	**0.1350**	**3:12**	**15:41**	**35:51**
5.05	0.3100	0.1227	3:42	17:38	40:00
2.53	0.1200	0.0950	5:22	24:07	53:21
7.98	0.3600	0.0902	5:48	25:40	56:30
10.10	0.3700	0.0733	7:43	32:45	70:45

Y: Transverse

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
1.20	**0.1000**	**0.1000**	**5:00**	**22:40**	**50:21**
6.37	0.2900	0.0910	5:43	25:22	55:51
1.61	0.0900	0.0900	5:48	25:45	56:36
7.98	0.3000	0.0752	7:28	31:47	68:52
5.05	0.1800	0.0712	8:02	33:51	72:52

Z: Vertical

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
6.37	**0.2700**	**0.2700**	**1:49**	**9:53**	**23:37**
3.14	0.3000	0.2658	1:52	10:07	24:02
2.02	0.3700	0.2632	1:52	10:14	24:22
2.53	0.3200	0.2543	2:00	10:42	25:22
1.61	0.3600	0.2285	2:23	12:18	28:47

* International Standards Organization ISO 2631:

Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)

RUN-18 Driver

8-OCT-93 16:14:27

1: **HET Ride Quality**
2: **Oct 4, 1993**
3: **Secondary A**
4: **Driver**
5: **30 mph**
6: **No Load**

Third-octave bands with greatest weighted RMS accelerations (m/s^2)

Durations of WBV exposure before reaching ISO limits* (given in hours:minutes)

X: Longitudinal

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
6.37	**0.3300**	**0.1036**	**4:45**	**21:45**	**48:26**
2.02	0.0800	0.0790	6:58	30:00	65:15
7.98	0.3100	0.0777	7:09	30:37	66:30
10.10	0.3700	0.0733	7:43	32:45	70:45
1.61	0.0700	0.0700	8:14	34:30	74:15

Y: Transverse

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
1.61	**0.1700**	**0.1700**	**2:14**	**11:41**	**27:25**
1.20	0.1500	0.1500	2:43	13:42	31:45
7.98	0.5000	0.1253	3:34	17:13	39:06
2.02	0.1200	0.1185	3:54	18:25	41:36
3.14	0.1600	0.1019	4:52	22:10	49:21

Z: Vertical

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
2.02	**0.4500**	**0.3202**	**1:21**	**7:52**	**19:10**
2.53	0.3600	0.2861	1:38	9:10	22:00
3.14	0.3200	0.2835	1:39	9:15	22:15
3.94	0.2700	0.2679	1:50	10:00	23:52
1.61	0.3900	0.2476	2:05	11:04	26:10

* International Standards Organization ISO 2631:
Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)

RUN-18 Front

8-OCT-93 16:14:27

1: **HET Ride Quality**
2: **Oct 4, 1993**
3: **Secondary A**
4: **Front**
5: **30 mph**
6: **No Load**

Third-octave bands with greatest weighted RMS accelerations (m/s^2)

Durations of WBV exposure before reaching ISO limits* (given in hours:minutes)

X: Longitudinal

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
6.37	**0.3200**	**0.1005**	**4:58**	**22:32**	**50:06**
7.98	0.3900	0.0977	5:09	23:17	51:41
10.10	0.4700	0.0931	5:33	24:40	54:30
1.61	0.0800	0.0800	6:50	29:32	64:22
1.20	0.0800	0.0800	6:50	29:32	64:22

Y: Transverse

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
1.61	**0.1500**	**0.1500**	**2:43**	**13:42**	**31:45**
1.20	0.1500	0.1500	2:43	13:42	31:45
7.98	0.4600	0.1152	4:03	19:05	43:00
3.94	0.2100	0.1067	4:33	20:58	46:51
3.14	0.1600	0.1019	4:52	22:10	49:21

Z: Vertical

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
3.94	**0.5000**	**0.4961**	**0:33**	**4:13**	**11:02**
2.02	0.5300	0.3771	0:57	6:16	15:41
3.14	0.3500	0.3101	1:25	8:12	19:58
2.53	0.3900	0.3100	1:25	8:14	20:00
1.61	0.4400	0.2793	1:43	9:27	22:40

* International Standards Organization ISO 2631:

Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)

RUN-18 Roadside

8-OCT-93 16:14:27

1: **HET Ride Quality**
2: **Oct 4, 1993**
3: **Secondary A**
4: **Roadside**
5: **30 mph**
6: **No Load**

Third-octave bands with greatest weighted RMS accelerations (m/s^2)

Durations of WBV exposure before reaching ISO limits* (given in hours:minutes)

X: Longitudinal

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
6.37	**0.4700**	**0.1476**	**2:47**	**14:00**	**32:21**
7.98	0.4100	0.1027	4:48	21:55	48:51
5.05	0.2400	0.0950	5:22	24:07	53:21
10.10	0.4500	0.0891	5:54	26:00	57:11
1.61	0.0800	0.0800	6:50	29:32	64:22

Y: Transverse

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
7.98	**0.5600**	**0.1403**	**3:00**	**14:56**	**34:21**
1.20	0.1300	0.1300	3:24	16:25	37:30
1.61	0.1100	0.1100	4:20	20:10	45:15
6.37	0.3100	0.0973	5:11	23:25	51:51
5.05	0.2000	0.0792	6:58	29:55	65:07

Z: Vertical

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
3.94	**0.3100**	**0.3076**	**1:27**	**8:18**	**20:10**
6.37	0.2800	0.2800	1:42	9:26	22:37
2.02	0.3700	0.2632	1:52	10:14	24:22
7.98	0.2500	0.2500	2:03	10:57	25:52
3.14	0.2800	0.2481	2:04	11:03	26:07

* International Standards Organization ISO 2631:

Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)

RUN-18 Curbside

8-OCT-93 16:14:27

1: **HET Ride Quality**
2: **Oct 4, 1993**
3: **Secondary A**
4: **Curbside**
5: **30 mph**
6: **No Load**

Third-octave bands with greatest weighted RMS accelerations (m/s^2)

Durations of WBV exposure before reaching ISO limits* (given in hours:minutes)

X: Longitudinal

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
6.37	**0.4300**	**0.1350**	**3:12**	**15:41**	**35:51**
7.98	0.4300	0.1077	4:28	20:43	46:21
5.05	0.2200	0.0871	6:05	26:45	58:36
10.10	0.4100	0.0812	6:43	29:02	63:15
1.61	0.0800	0.0800	6:50	29:32	64:22

Y: Transverse

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
7.98	**0.5600**	**0.1403**	**3:00**	**14:56**	**34:21**
6.37	0.3400	0.1067	4:33	20:55	46:51
1.20	0.1000	0.1000	5:00	22:40	50:21
5.05	0.2100	0.0831	6:30	28:15	61:45
1.61	0.0800	0.0800	6:50	29:32	64:22

Z: Vertical

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
3.94	**0.4300**	**0.4266**	**0:45**	**5:16**	**13:23**
2.02	0.4200	0.2988	1:31	8:38	20:53
3.14	0.2800	0.2481	2:04	11:03	26:07
2.53	0.3100	0.2464	2:06	11:08	26:22
1.61	0.3500	0.2222	2:29	12:45	29:45

* International Standards Organization ISO 2631:

Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)

RUN-19 Driver

8-OCT-93 16:14:28

1: **HET Ride Quality**
2: **Oct 4, 1993**
3: **Paved**
4: **Driver**
5: **25 mph**
6: **No Load**

Third-octave bands with greatest weighted RMS accelerations (m/s^2)

Durations of WBV exposure before reaching ISO limits* (given in hours:minutes)

X: Longitudinal

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
3.14	**0.1200**	**0.0764**	**7:18**	**31:10**	**67:37**
2.53	0.0800	0.0633	9:25	38:45	82:37
6.37	0.1800	0.0565	10:56	44:02	93:15
5.05	0.1300	0.0515	12:22	48:56	102:45
2.02	0.0400	0.0395	17:15	65:22	134:30

Y: Transverse

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
3.14	**0.1000**	**0.0637**	**9:19**	**38:30**	**82:07**
2.53	0.0600	0.0475	13:41	53:30	111:30
6.37	0.1000	0.0314	22:52	83:37	169:30
1.61	0.0300	0.0300	24:08	87:45	177:15
2.02	0.0300	0.0296	24:30	88:45	179:30

Z: Vertical

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
3.14	**0.4400**	**0.3899**	**0:53**	**6:00**	**15:03**
2.53	0.3000	0.2384	2:13	11:38	27:22
2.02	0.2100	0.1494	4:33	20:55	46:51
1.61	0.1300	0.0825	10:21	42:00	89:07
7.98	0.0800	0.0800	10:47	43:30	92:00

* International Standards Organization ISO 2631:
Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)

RUN-19 Front

8-OCT-93 16:14:28

1: **HET Ride Quality**
2: **Oct 4, 1993**
3: **Paved**
4: **Front**
5: **25 mph**
6: **No Load**

Third-octave bands with greatest weighted RMS accelerations (m/s^2)

Durations of WBV exposure before reaching ISO limits* (given in hours:minutes)

X: Longitudinal

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
6.37	**0.1500**	**0.0471**	**13:49**	**54:00**	**112:30**
5.05	0.1000	0.0396	17:15	65:15	134:15
2.53	0.0500	0.0396	17:15	65:15	134:15
3.14	0.0600	0.0382	18:00	67:45	139:15
7.98	0.1100	0.0276	26:45	95:45	192:30

Y: Transverse

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
3.14	**0.1300**	**0.0828**	**6:31**	**28:22**	**62:00**
2.53	0.0700	0.0554	11:12	45:00	95:00
6.37	0.1100	0.0345	20:22	75:30	154:00
7.98	0.1200	0.0301	24:07	87:30	177:00
1.61	0.0300	0.0300	24:08	87:45	177:15

Z: Vertical

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
3.14	**0.4300**	**0.3810**	**0:56**	**6:11**	**15:27**
2.53	0.2800	0.2225	2:29	12:45	29:40
2.02	0.2200	0.1565	4:15	19:47	44:30
6.37	0.1300	0.1300	5:33	24:47	54:36
3.94	0.0900	0.0893	9:19	38:26	82:00

* International Standards Organization ISO 2631:

Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)

RUN-19 Roadside

8-OCT-93 16:14:28

1: **HET Ride Quality**
2: **Oct 4, 1993**
3: **Paved**
4: **Roadside**
5: **25 mph**
6: **No Load**

Third-octave bands with greatest weighted RMS accelerations (m/s^2)

Durations of WBV exposure before reaching ISO limits* (given in hours:minutes)

X: Longitudinal

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
6.37	**0.2800**	**0.0879**	**6:01**	**26:25**	**58:06**
5.05	0.1900	0.0752	7:28	31:45	68:45
3.14	0.0900	0.0573	10:45	43:21	91:45
2.53	0.0700	0.0554	11:12	45:00	95:00
7.98	0.1500	0.0376	18:22	69:00	141:30

Y: Transverse

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
2.02	**0.0800**	**0.0790**	**6:58**	**30:00**	**65:15**
6.37	0.1500	0.0471	13:49	54:00	112:30
3.14	0.0500	0.0318	22:30	82:22	167:00
7.98	0.1200	0.0301	24:07	87:30	177:00
5.05	0.0600	0.0237	31:47	111:45	222:30

Z: Vertical

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
3.14	**0.3100**	**0.2747**	**1:45**	**9:41**	**23:07**
6.37	0.2000	0.2000	2:56	14:34	33:36
5.05	0.1700	0.1700	3:45	17:52	40:30
2.53	0.2100	0.1669	3:51	18:17	41:21
2.02	0.1900	0.1352	5:16	23:38	52:21

* International Standards Organization ISO 2631:
Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)

RUN-19 Curbside

8-OCT-93 16:14:28

1: **HET Ride Quality**
2: **Oct 4, 1993**
3: **Paved**
4: **Curbside**
5: **25 mph**
6: **No Load**

Third-octave bands with greatest weighted RMS accelerations (m/s^2)

Durations of WBV exposure before reaching ISO limits* (given in hours:minutes)

X: Longitudinal

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
6.37	**0.3000**	**0.0942**	**5:26**	**24:22**	**53:51**
5.05	0.2100	0.0831	6:30	28:15	61:45
2.53	0.0800	0.0633	9:25	38:45	82:37
3.14	0.0900	0.0573	10:45	43:21	91:45
7.98	0.1500	0.0376	18:22	69:00	141:30

Y: Transverse

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
6.37	**0.1600**	**0.0502**	**12:45**	**50:15**	**105:15**
5.05	0.0900	0.0356	19:37	73:07	149:30
7.98	0.1100	0.0276	26:45	95:45	192:30
3.14	0.0400	0.0255	29:17	104:00	208:00
2.53	0.0300	0.0237	31:47	111:45	222:30

Z: Vertical

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
3.14	**0.3000**	**0.2658**	**1:52**	**10:07**	**24:02**
6.37	0.1700	0.1700	3:45	17:52	40:30
2.53	0.2100	0.1669	3:51	18:17	41:21
2.02	0.2000	0.1423	4:52	22:15	49:30
5.05	0.1200	0.1200	6:13	27:15	59:45

* International Standards Organization ISO 2631:

Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)

RUN-20 Driver

8-OCT-93 16:14:29

1: **HET Ride Quality**
2: **Oct 4, 1993**
3: **Paved**
4: **Driver**
5: **30 mph**
6: **No Load**

Third-octave bands with greatest weighted RMS accelerations (m/s^2)

Durations of WBV exposure before reaching ISO limits* (given in hours:minutes)

X: Longitudinal

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
6.37	**0.2000**	**0.0628**	**9:30**	**39:06**	**83:22**
3.94	0.0900	0.0457	14:22	55:45	116:00
3.14	0.0600	0.0382	18:00	67:45	139:15
7.98	0.1500	0.0376	18:22	69:00	141:30
2.02	0.0300	0.0296	24:30	88:45	179:30

Y: Transverse

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
3.94	**0.1900**	**0.0965**	**5:16**	**23:40**	**52:21**
7.98	0.2300	0.0576	10:40	43:06	91:15
3.14	0.0900	0.0573	10:45	43:21	91:45
6.37	0.1100	0.0345	20:22	75:30	154:00
1.61	0.0300	0.0300	24:08	87:45	177:15

Z: Vertical

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
3.94	**0.2900**	**0.2877**	**1:37**	**9:06**	**21:52**
3.14	0.2000	0.1772	3:31	17:00	38:36
7.98	0.1400	0.1400	5:00	22:40	50:21
2.02	0.1800	0.1281	5:41	25:15	55:36
2.53	0.1500	0.1192	6:16	27:25	60:06

* International Standards Organization ISO 2631:

Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)

RUN-20 Front

8-OCT-93 16:14:29

1: **HET Ride Quality**
2: **Oct 4, 1993**
3: **Paved**
4: **Front**
5: **30 mph**
6: **No Load**

Third-octave bands with greatest weighted RMS accelerations (m/s^2)

Durations of WBV exposure before reaching ISO limits* (given in hours:minutes)

X: Longitudinal

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
6.37	**0.1800**	**0.0565**	**10:56**	**44:02**	**93:15**
3.94	0.0800	0.0406	16:40	63:21	130:45
7.98	0.1500	0.0376	18:22	69:00	141:30
3.14	0.0500	0.0318	22:30	82:22	167:00
10.10	0.1600	0.0317	22:37	82:45	167:45

Y: Transverse

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
3.94	**0.1900**	**0.0965**	**5:16**	**23:40**	**52:21**
7.98	0.2700	0.0676	8:37	35:56	77:00
3.14	0.0800	0.0510	12:30	49:30	103:45
6.37	0.1100	0.0345	20:22	75:30	154:00
1.61	0.0300	0.0300	24:08	87:45	177:15

Z: Vertical

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
3.94	**0.5900**	**0.5853**	**0:22**	**3:17**	**8:52**
3.14	0.2800	0.2481	2:04	11:03	26:07
7.98	0.1300	0.1300	5:33	24:47	54:36
2.02	0.1800	0.1281	5:41	25:15	55:36
2.53	0.1600	0.1272	5:43	25:25	56:00

* International Standards Organization ISO 2631:

Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)

RUN-20 Roadside

8-OCT-93 16:14:29

1: **HET Ride Quality**
2: **Oct 4, 1993**
3: **Paved**
4: **Roadside**
5: **30 mph**
6: **No Load**

Third-octave bands with greatest weighted RMS accelerations (m/s^2)

Durations of WBV exposure before reaching ISO limits* (given in hours:minutes)

X: Longitudinal

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
6.37	**0.3200**	**0.1005**	**4:58**	**22:32**	**50:06**
3.94	0.1200	0.0610	9:53	40:26	86:00
3.14	0.0700	0.0446	14:49	57:21	119:00
7.98	0.1700	0.0426	15:42	60:15	124:45
10.10	0.1400	0.0277	26:30	95:15	191:30

Y: Transverse

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
7.98	**0.3600**	**0.0902**	**5:48**	**25:40**	**56:30**
3.94	0.1200	0.0610	9:53	40:26	86:00
6.37	0.1600	0.0502	12:45	50:15	105:15
3.14	0.0500	0.0318	22:30	82:22	167:00
1.61	0.0200	0.0200	38:45	133:15	262:30

Z: Vertical

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
3.94	**0.2500**	**0.2480**	**2:04**	**11:03**	**26:07**
6.37	0.1800	0.1800	3:27	16:38	38:00
7.98	0.1500	0.1500	4:31	20:52	46:36
3.14	0.1300	0.1152	6:35	28:37	62:21
2.02	0.1500	0.1067	7:20	31:15	67:45

* International Standards Organization ISO 2631:

Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)

RUN-20 Curbside

8-OCT-93 16:14:29

1: **HET Ride Quality**
2: **Oct 4, 1993**
3: **Paved**
4: **Curbside**
5: **30 mph**
6: **No Load**

Third-octave bands with greatest weighted RMS accelerations (m/s^2)

Durations of WBV exposure before reaching ISO limits* (given in hours:minutes)

X: Longitudinal

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
6.37	**0.3200**	**0.1005**	**4:58**	**22:32**	**50:06**
7.98	0.1600	0.0401	16:58	64:22	132:45
3.14	0.0600	0.0382	18:00	67:45	139:15
3.94	0.0700	0.0356	19:40	73:15	149:45
10.10	0.1400	0.0277	26:30	95:15	191:30

Y: Transverse

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
7.98	**0.3500**	**0.0877**	**6:01**	**26:30**	**58:15**
6.37	0.1800	0.0565	10:56	44:02	93:15
3.94	0.0800	0.0406	16:40	63:21	130:45
3.14	0.0400	0.0255	29:17	104:00	208:00
1.61	0.0200	0.0200	38:45	133:15	262:30

Z: Vertical

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
3.94	**0.3800**	**0.3770**	**0:57**	**6:16**	**15:41**
3.14	0.1800	0.1595	4:07	19:22	43:30
6.37	0.1500	0.1500	4:31	20:52	46:36
2.02	0.1600	0.1138	6:41	29:00	63:15
7.98	0.1100	0.1100	7:01	30:10	65:37

* International Standards Organization ISO 2631:

Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)

RUN-21 Driver

8-OCT-93 16:14:30

1: **HET Ride Quality**
2: **Oct 4, 1993**
3: **Paved**
4: **Driver**
5: **35 mph**
6: **No Load**

Third-octave bands with greatest weighted RMS accelerations (m/s^2)

Durations of WBV exposure before reaching ISO limits* (given in hours:minutes)

X: Longitudinal

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
7.98	**0.2100**	**0.0526**	**12:00**	**47:45**	**100:22**
3.94	0.0800	0.0406	16:40	63:21	130:45
2.53	0.0400	0.0317	22:37	82:52	168:00
1.61	0.0300	0.0300	24:08	87:45	177:15
2.02	0.0300	0.0296	24:30	88:45	179:30

Y: Transverse

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
7.98	**0.3000**	**0.0752**	**7:28**	**31:47**	**68:52**
3.94	0.1400	0.0711	8:03	33:51	73:00
2.02	0.0500	0.0494	13:00	51:15	107:15
1.61	0.0400	0.0400	17:00	64:30	133:00
5.05	0.0800	0.0317	22:37	82:52	168:00

Z: Vertical

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
3.94	**0.3100**	**0.3076**	**1:27**	**8:18**	**20:10**
2.53	0.2900	0.2305	2:20	12:11	28:30
5.05	0.1700	0.1700	3:45	17:52	40:30
2.02	0.2300	0.1636	3:59	18:45	42:17
3.14	0.1500	0.1329	5:22	24:07	53:21

* International Standards Organization ISO 2631:
Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)

RUN-21 Front

8-OCT-93 16:14:30

1: **HET Ride Quality**
2: **Oct 4, 1993**
3: **Paved**
4: **Front**
5: **35 mph**
6: **No Load**

Third-octave bands with greatest weighted RMS accelerations (m/s^2)

Durations of WBV exposure before reaching ISO limits* (given in hours:minutes)

X: Longitudinal

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
3.94	**0.1200**	**0.0610**	**9:53**	**40:26**	**86:00**
7.98	0.1900	0.0476	13:38	53:21	111:15
12.74	0.2400	0.0377	18:17	68:45	141:15
1.61	0.0300	0.0300	24:08	87:45	177:15
1.20	0.0300	0.0300	24:08	87:45	177:15

Y: Transverse

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
3.94	**0.1300**	**0.0660**	**8:53**	**36:56**	**79:00**
7.98	0.2500	0.0626	9:33	39:15	83:37
2.02	0.0400	0.0395	17:15	65:22	134:30
5.05	0.0800	0.0317	22:37	82:52	168:00
1.61	0.0300	0.0300	24:08	87:45	177:15

Z: Vertical

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
3.94	**0.4700**	**0.4663**	**0:37**	**4:37**	**11:57**
2.53	0.3200	0.2543	2:00	10:42	25:22
5.05	0.2500	0.2500	2:03	10:57	25:52
2.02	0.2500	0.1779	3:30	16:53	38:30
3.14	0.1700	0.1506	4:30	20:45	46:26

* International Standards Organization ISO 2631:

Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)

RUN-21 Roadside

8-OCT-93 16:14:30

1: **HET Ride Quality**
2: **Oct 4, 1993**
3: **Paved**
4: **Roadside**
5: **35 mph**
6: **No Load**

Third-octave bands with greatest weighted RMS accelerations (m/s^2)

Durations of WBV exposure before reaching ISO limits* (given in hours:minutes)

X: Longitudinal

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
7.98	**0.2800**	**0.0702**	**8:12**	**34:26**	**74:07**
3.94	0.0900	0.0457	14:22	55:45	116:00
6.37	0.1300	0.0408	16:35	63:06	130:15
2.02	0.0400	0.0395	17:15	65:22	134:30
12.74	0.2100	0.0330	21:32	79:22	161:15

Y: Transverse

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
7.98	**0.3100**	**0.0777**	**7:09**	**30:37**	**66:30**
3.94	0.1000	0.0508	12:33	49:36	104:00
1.20	0.0300	0.0300	24:08	87:45	177:15
2.02	0.0300	0.0296	24:30	88:45	179:30
5.05	0.0700	0.0277	26:32	95:15	191:30

Z: Vertical

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
3.94	**0.3000**	**0.2976**	**1:31**	**8:41**	**21:00**
5.05	0.1900	0.1900	3:11	15:34	35:41
2.53	0.2100	0.1669	3:51	18:17	41:21
7.98	0.1500	0.1500	4:31	20:52	46:36
2.02	0.1700	0.1209	6:09	27:00	59:06

* International Standards Organization ISO 2631:

Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)

RUN-21 Curbside

8-OCT-93 16:14:30

1: **HET Ride Quality**
2: **Oct 4, 1993**
3: **Paved**
4: **Curbside**
5: **35 mph**
6: **No Load**

Third-octave bands with greatest weighted RMS accelerations (m/s^2)

Durations of WBV exposure before reaching ISO limits* (given in hours:minutes)

X: Longitudinal

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
7.98	**0.2600**	**0.0651**	**9:03**	**37:30**	**80:15**
3.94	0.1100	0.0559	11:07	44:36	94:15
6.37	0.1500	0.0471	13:49	54:00	112:30
5.05	0.0800	0.0317	22:37	82:52	168:00
2.53	0.0400	0.0317	22:37	82:52	168:00

Y: Transverse

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
7.98	**0.2900**	**0.0727**	**7:50**	**33:02**	**71:22**
3.94	0.0700	0.0356	19:40	73:15	149:45
6.37	0.0900	0.0283	25:55	93:22	188:00
10.10	0.1200	0.0238	31:47	111:45	222:30
5.05	0.0600	0.0237	31:47	111:45	222:30

Z: Vertical

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
3.94	**0.3800**	**0.3770**	**0:57**	**6:16**	**15:41**
5.05	0.2200	0.2200	2:31	12:56	30:07
2.53	0.2300	0.1828	3:21	16:20	37:17
2.02	0.1900	0.1352	5:16	23:38	52:21
3.14	0.1200	0.1063	7:22	31:25	68:00

* International Standards Organization ISO 2631:

Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)

RUN-22 Driver

8-OCT-93 16:14:30

1: **HET Ride Quality**
2: **Oct 4, 1993**
3: **Paved**
4: **Driver**
5: **40 mph**
6: **No Load**

Third-octave bands with greatest weighted RMS accelerations (m/s^2)

Durations of WBV exposure before reaching ISO limits* (given in hours:minutes)

X: Longitudinal

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
2.02	**0.0500**	**0.0494**	**13:00**	**51:15**	**107:15**
5.05	0.1000	0.0396	17:15	65:15	134:15
7.98	0.1300	0.0326	21:52	80:22	163:30
2.53	0.0400	0.0317	22:37	82:52	168:00
1.61	0.0300	0.0300	24:08	87:45	177:15

Y: Transverse

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
5.05	**0.2300**	**0.0910**	**5:43**	**25:22**	**55:51**
2.02	0.0400	0.0395	17:15	65:22	134:30
2.53	0.0400	0.0317	22:37	82:52	168:00
1.61	0.0300	0.0300	24:08	87:45	177:15
1.20	0.0300	0.0300	24:08	87:45	177:15

Z: Vertical

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
5.05	**0.2500**	**0.2500**	**2:03**	**10:57**	**25:52**
2.53	0.2100	0.1669	3:51	18:17	41:21
2.02	0.1700	0.1209	6:09	27:00	59:06
3.94	0.1000	0.0992	8:06	34:00	73:15
3.14	0.1100	0.0975	8:18	34:45	74:45

* International Standards Organization ISO 2631:
Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)

RUN-22 Front

8-OCT-93 16:14:30

1: **HET Ride Quality**
2: **Oct 4, 1993**
3: **Paved**
4: **Front**
5: **40 mph**
6: **No Load**

Third-octave bands with greatest weighted RMS accelerations (m/s^2)

Durations of WBV exposure before reaching ISO limits* (given in hours:minutes)

X: Longitudinal

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
5.05	**0.1000**	**0.0396**	**17:15**	**65:15**	**134:15**
10.10	0.1800	0.0357	19:37	73:00	149:15
7.98	0.1300	0.0326	21:52	80:22	163:30
2.02	0.0300	0.0296	24:30	88:45	179:30
12.74	0.1700	0.0267	27:45	99:00	198:45

Y: Transverse

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
5.05	**0.2100**	**0.0831**	**6:30**	**28:15**	**61:45**
1.20	0.0300	0.0300	24:08	87:45	177:15
2.02	0.0300	0.0296	24:30	88:45	179:30
7.98	0.1000	0.0251	29:52	105:45	211:30
10.10	0.1200	0.0238	31:47	111:45	222:30

Z: Vertical

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
5.05	**0.4000**	**0.4000**	**0:52**	**5:46**	**14:33**
2.53	0.2200	0.1749	3:35	17:15	39:15
3.94	0.1400	0.1389	5:03	22:52	50:51
2.02	0.1800	0.1281	5:41	25:15	55:36
10.10	0.1400	0.1109	6:56	29:52	65:00

* International Standards Organization ISO 2631:

Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)

RUN-22 Roadside

8-OCT-93 16:14:30

1: **HET Ride Quality**
2: **Oct 4, 1993**
3: **Paved**
4: **Roadside**
5: **40 mph**
6: **No Load**

Third-octave bands with greatest weighted RMS accelerations (m/s^2)

Durations of WBV exposure before reaching ISO limits* (given in hours:minutes)

X: Longitudinal

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
7.98	**0.1900**	**0.0476**	**13:38**	**53:21**	**111:15**
5.05	0.1100	0.0435	15:18	58:51	122:00
2.53	0.0500	0.0396	17:15	65:15	134:15
2.02	0.0400	0.0395	17:15	65:22	134:30
6.37	0.1100	0.0345	20:22	75:30	154:00

Y: Transverse

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
5.05	**0.1900**	**0.0752**	**7:28**	**31:45**	**68:45**
10.10	0.2100	0.0416	16:10	61:51	127:45
7.98	0.1300	0.0326	21:52	80:22	163:30
1.20	0.0300	0.0300	24:08	87:45	177:15
6.37	0.0700	0.0220	34:47	121:00	240:00

Z: Vertical

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
5.05	**0.3400**	**0.3400**	**1:13**	**7:15**	**17:50**
7.98	0.1500	0.1500	4:31	20:52	46:36
2.53	0.1300	0.1033	7:39	32:30	70:15
2.02	0.1400	0.0996	8:03	33:51	73:00
3.94	0.0900	0.0893	9:19	38:26	82:00

* International Standards Organization ISO 2631:
Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)

RUN-22 Curbside

8-OCT-93 16:14:30

1: **HET Ride Quality**
2: **Oct 4, 1993**
3: **Paved**
4: **Curbside**
5: **40 mph**
6: **No Load**

Third-octave bands with greatest weighted RMS accelerations (m/s^2)

Durations of WBV exposure before reaching ISO limits* (given in hours:minutes)

X: Longitudinal

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
5.05	**0.1800**	**0.0712**	**8:02**	**33:51**	**72:52**
7.98	0.1600	0.0401	16:58	64:22	132:45
2.53	0.0500	0.0396	17:15	65:15	134:15
2.02	0.0400	0.0395	17:15	65:22	134:30
6.37	0.1100	0.0345	20:22	75:30	154:00

Y: Transverse

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
5.05	**0.1500**	**0.0594**	**10:15**	**41:41**	**88:30**
10.10	0.2100	0.0416	16:10	61:51	127:45
7.98	0.1400	0.0351	20:00	74:15	151:45
1.20	0.0300	0.0300	24:08	87:45	177:15
2.02	0.0300	0.0296	24:30	88:45	179:30

Z: Vertical

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
5.05	**0.4100**	**0.4100**	**0:48**	**5:35**	**14:07**
2.53	0.1500	0.1192	6:16	27:25	60:06
10.10	0.1500	0.1189	6:18	27:32	60:21
2.02	0.1400	0.0996	8:03	33:51	73:00
3.94	0.0900	0.0893	9:19	38:26	82:00

* International Standards Organization ISO 2631:

Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)

RUN-23 Driver

8-OCT-93 16:37:52

1: **HET Ride Quality**
2: **Oct 4, 1993**
3: **Paved**
4: **Driver**
5: **99 mph**
6: **No Load**

Third-octave bands with greatest weighted RMS accelerations (m/s^2)

Durations of WBV exposure before reaching ISO limits* (given in hours:minutes)

X: Longitudinal

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
2.02	**0.0700**	**0.0691**	**8:22**	**35:00**	**75:15**
5.05	0.1600	0.0633	9:25	38:45	82:37
2.53	0.0800	0.0633	9:25	38:45	82:37
1.61	0.0400	0.0400	17:00	64:30	133:00
10.10	0.2000	0.0396	17:13	65:15	134:15

Y: Transverse

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
5.05	**0.1800**	**0.0712**	**8:02**	**33:51**	**72:52**
2.02	0.0700	0.0691	8:22	35:00	75:15
2.53	0.0600	0.0475	13:41	53:30	111:30
1.61	0.0400	0.0400	17:00	64:30	133:00
3.94	0.0600	0.0305	23:40	86:15	174:30

Z: Vertical

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
2.53	**0.3700**	**0.2941**	**1:34**	**8:49**	**21:17**
2.02	0.2700	0.1921	3:06	15:22	35:15
5.05	0.1900	0.1900	3:11	15:34	35:41
3.14	0.2000	0.1772	3:31	17:00	38:36
1.61	0.2100	0.1333	5:22	24:02	53:11

* International Standards Organization ISO 2631:
Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)

RUN-23 Front

8-OCT-93 16:37:52

1: **HET Ride Quality**
2: **Oct 4, 1993**
3: **Paved**
4: **Front**
5: **99 mph**
6: **No Load**

Third-octave bands with greatest weighted RMS accelerations (m/s^2)

Durations of WBV exposure before reaching ISO limits* (given in hours:minutes)

X: Longitudinal

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
5.05	**0.1600**	**0.0633**	**9:25**	**38:45**	**82:37**
10.10	0.2100	0.0416	16:10	61:51	127:45
2.53	0.0500	0.0396	17:15	65:15	134:15
2.02	0.0400	0.0395	17:15	65:22	134:30
7.98	0.1300	0.0326	21:52	80:22	163:30

Y: Transverse

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
5.05	**0.2200**	**0.0871**	**6:05**	**26:45**	**58:36**
1.20	0.0400	0.0400	17:00	64:30	133:00
7.98	0.1300	0.0326	21:52	80:22	163:30
2.53	0.0400	0.0317	22:37	82:52	168:00
3.94	0.0600	0.0305	23:40	86:15	174:30

Z: Vertical

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
5.05	**0.3700**	**0.3700**	**1:02**	**6:26**	**16:02**
2.53	0.3800	0.3020	1:30	8:30	20:37
2.02	0.3000	0.2134	2:39	13:26	31:10
3.14	0.1900	0.1683	3:48	18:07	41:00
3.94	0.1500	0.1488	4:35	21:02	47:02

* International Standards Organization ISO 2631:

Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)

RUN-23 Roadside

8-OCT-93 16:37:52

1: **HET Ride Quality**
2: **Oct 4, 1993**
3: **Paved**
4: **Roadside**
5: **99 mph**
6: **No Load**

Third-octave bands with greatest weighted RMS accelerations (m/s^2)

Durations of WBV exposure before reaching ISO limits* (given in hours:minutes)

X: Longitudinal

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
5.05	**0.2000**	**0.0792**	**6:58**	**29:55**	**65:07**
2.53	0.0900	0.0712	8:02	33:51	72:52
2.02	0.0700	0.0691	8:22	35:00	75:15
6.37	0.1700	0.0534	11:48	47:00	98:52
7.98	0.2000	0.0501	12:48	50:21	105:30

Y: Transverse

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
5.05	**0.2400**	**0.0950**	**5:22**	**24:07**	**53:21**
7.98	0.1700	0.0426	15:42	60:15	124:45
1.20	0.0400	0.0400	17:00	64:30	133:00
10.10	0.1900	0.0376	18:20	68:52	141:15
2.02	0.0300	0.0296	24:30	88:45	179:30

Z: Vertical

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
5.05	**0.3300**	**0.3300**	**1:16**	**7:33**	**18:30**
2.53	0.2200	0.1749	3:35	17:15	39:15
3.94	0.1600	0.1587	4:09	19:28	43:45
2.02	0.2100	0.1494	4:33	20:55	46:51
7.98	0.1400	0.1400	5:00	22:40	50:21

* International Standards Organization ISO 2631:

Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

USAARL summary of analysis
per ISO-2631* guideline on
whole-body vibration (WBV)

RUN-23 Curbside

8-OCT-93 16:37:52

1: **HET Ride Quality**
2: **Oct 4, 1993**
3: **Paved**
4: **Curbside**
5: **99 mph**
6: **No Load**

Third-octave bands with greatest weighted RMS accelerations (m/s^2)

Durations of WBV exposure before reaching ISO limits* (given in hours:minutes)

X: Longitudinal

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
5.05	**0.2500**	**0.0989**	**5:05**	**22:58**	**51:00**
2.53	0.0900	0.0712	8:02	33:51	72:52
2.02	0.0600	0.0593	10:15	41:45	88:37
6.37	0.1500	0.0471	13:49	54:00	112:30
10.10	0.2200	0.0436	15:15	58:45	121:45

Y: Transverse

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
5.05	**0.2200**	**0.0871**	**6:05**	**26:45**	**58:36**
7.98	0.1700	0.0426	15:42	60:15	124:45
10.10	0.2000	0.0396	17:13	65:15	134:15
2.02	0.0400	0.0395	17:15	65:22	134:30
1.61	0.0300	0.0300	24:08	87:45	177:15

Z: Vertical

(Hz)	actual	weighted	COMFORT	FATIGUE	HEALTH
5.05	**0.3400**	**0.3400**	**1:13**	**7:15**	**17:50**
2.53	0.2600	0.2066	2:46	14:00	32:21
2.02	0.2300	0.1636	3:59	18:45	42:17
10.10	0.1700	0.1347	5:16	23:45	52:36
3.14	0.1400	0.1240	5:56	26:10	57:36

* International Standards Organization ISO 2631:

Comfort ... Reduced comfort boundary
Fatigue ... Fatigue-decreased proficiency boundary
Health ... Health and safety exposure limit

HSEL: Health and safety exposure limit
FDPB: Fatigue-decreased proficiency boundary
RCB: Reduced comfort boundary
RMS: Vibration R.M.S. acceleration (m/s2)

X: Longitudinal
Y: Transverse
Z: Vertical

RUN-01

Oct 4, 1993

Driver Seat

HET Ride Quality

Exposure: 10h 0m



8-OCT-93 16:14:14

Course: Paved
Speed: 25 mph
Note: Loaded

HSEL: Health and safety exposure limit
FDPB: Fatigue-decreased proficiency boundary
RCB: Reduced comfort boundary
RMS: Vibration R.M.S. acceleration (m/s2)

X: Longitudinal
Y: Transverse
Z: Vertical

RUN-01

Oct 4, 1993

Front Seat

HET Ride Quality

Exposure: 10h 0m



(Hz)		RMS / FDPB
1.20	X	0.02 / 0.191
	Y	0.02 / 0.191
	Z	0.04 / 0.488
1.61	X	0.02 / 0.191
	Y	0.02 / 0.191
	Z	0.08 / 0.422
2.02	X	0.02 / 0.194
	Y	0.02 / 0.194
	Z	0.17 / 0.377
2.53	X	0.09 / 0.242
	Y	0.07 / 0.242
	Z	0.58 / 0.337
3.14	X	0.08 / 0.300
	Y	0.06 / 0.300
	Z	0.47 / 0.302
3.94	X	0.03 / 0.377
	Y	0.02 / 0.377
	Z	0.07 / 0.270
5.05	X	0.09 / 0.484
	Y	0.05 / 0.484
	Z	0.07 / 0.268
6.37	X	0.18 / 0.610
	Y	0.07 / 0.610
	Z	0.06 / 0.268
7.98	X	0.12 / 0.764
	Y	0.16 / 0.764
	Z	0.09 / 0.268
10.10	X	0.09 / 0.966
	Y	0.06 / 0.966
	Z	0.05 / 0.338
12.74	X	0.15 / 1.219
	Y	0.04 / 1.219
	Z	0.05 / 0.427
15.97	X	0.08 / 1.528
	Y	0.09 / 1.528
	Z	0.05 / 0.535
20.10	X	0.06 / 1.924
	Y	0.13 / 1.924
	Z	0.05 / 0.673
25.36	X	0.08 / 2.427
	Y	0.03 / 2.427
	Z	0.03 / 0.849
32.02	X	0.03 / 3.064
	Y	0.01 / 3.064
	Z	0.02 / 1.073
40.33	X	0.09 / 3.859
	Y	0.02 / 3.859
	Z	0.03 / 1.351
50.73	X	0.11 / 4.854
	Y	0.02 / 4.854
	Z	0.03 / 1.699
63.97	X	0.03 / 6.121
	Y	0.02 / 6.121
	Z	0.00 / 2.142
80.64	X	0.03 / 7.716
	Y	0.03 / 7.716
	Z	0.00 / 2.701



8-OCT-93 16:14:14

Course: Paved
Speed: 25 mph
Note: Loaded

HSEL: Health and safety exposure limit
FDPB: Fatigue-decreased proficiency boundary
RCB: Reduced comfort boundary
RMS: Vibration R.M.S. acceleration (m/s2)

X: Longitudinal
Y: Transverse
Z: Vertical

RUN-01

Oct 4, 1993

Roadside Seat

HET Ride Quality

Exposure: 10h 0m



8-OCT-93 16:14:14

Course: Paved
Speed: 25 mph
Note: Loaded

HSEL: Health and safety exposure limit
FDPB: Fatigue-decreased proficiency boundary
RCB: Reduced comfort boundary
RMS: Vibration R.M.S. acceleration (m/s2)

X: Longitudinal
Y: Transverse
Z: Vertical

RUN-01

Oct 4, 1993

Curbside Seat

HET Ride Quality

Exposure: 10h 0m

RCB FDPB HSEL

(Hz)		RMS / FDPB
1.20	X	0.02 / 0.191
	Y	0.02 / 0.191
	Z	0.03 / 0.488
1.61	X	0.02 / 0.191
	Y	0.02 / 0.191
	Z	0.07 / 0.422
2.02	X	0.03 / 0.194
	Y	0.02 / 0.194
	Z	0.14 / 0.377
2.53	X	0.05 / 0.242
	Y	0.07 / 0.242
	Z	0.47 / 0.337
3.14	X	0.03 / 0.300
	Y	0.06 / 0.300
	Z	0.38 / 0.302
3.94	X	0.05 / 0.377
	Y	0.02 / 0.377
	Z	0.08 / 0.270
5.05	X	0.14 / 0.484
	Y	0.07 / 0.484
	Z	0.13 / 0.268
6.37	X	0.26 / 0.610
	Y	0.10 / 0.610
	Z	0.21 / 0.268
7.98	X	0.15 / 0.764
	Y	0.15 / 0.764
	Z	0.08 / 0.268
10.10	X	0.11 / 0.966
	Y	0.09 / 0.966
	Z	0.06 / 0.338
12.74	X	0.14 / 1.219
	Y	0.09 / 1.219
	Z	0.07 / 0.427
15.97	X	0.07 / 1.528
	Y	0.06 / 1.528
	Z	0.05 / 0.535
20.10	X	0.04 / 1.924
	Y	0.09 / 1.924
	Z	0.07 / 0.673
25.36	X	0.05 / 2.427
	Y	0.05 / 2.427
	Z	0.05 / 0.849
32.02	X	0.03 / 3.064
	Y	0.02 / 3.064
	Z	0.04 / 1.073
40.33	X	0.05 / 3.859
	Y	0.09 / 3.859
	Z	0.01 / 1.351
50.73	X	0.05 / 4.854
	Y	0.02 / 4.854
	Z	0.01 / 1.699
63.97	X	0.03 / 6.121
	Y	0.03 / 6.121
	Z	0.01 / 2.142
80.64	X	0.04 / 7.716
	Y	0.09 / 7.716
	Z	0.01 / 2.701

8-OCT-93 16:14:14

0.1 1.0 RMS/FDPB ratio 10.

-20 -10 0 (deciBels) 10 20

Course: Paved
Speed: 25 mph
Note: Loaded

HSEL: Health and safety exposure limit
FDPB: Fatigue-decreased proficiency boundary
RCB: Reduced comfort boundary
RMS: Vibration R.M.S. acceleration (m/s2)

X: Longitudinal
Y: Transverse
Z: Vertical

RUN-02

Oct 4, 1993

Driver Seat

HET Ride Quality

Exposure: 10h 0m



8-OCT-93 16:14:15

Course: Paved
Speed: 30 mph
Note: Loaded

HSEL: Health and safety exposure limit
FDPB: Fatigue-decreased proficiency boundary
RCB: Reduced comfort boundary
RMS: Vibration R.M.S. acceleration (m/s2)

X: Longitudinal
Y: Transverse
Z: Vertical

RUN-02

Oct 4, 1993

Front Seat

HET Ride Quality

Exposure: 10h 0m



(Hz)		RMS / FDPB
1.20	X	0.03 / 0.191
	Y	0.02 / 0.191
	Z	0.06 / 0.488
1.61	X	0.05 / 0.191
	Y	0.04 / 0.191
	Z	0.10 / 0.422
2.02	X	0.03 / 0.194
	Y	0.03 / 0.194
	Z	0.16 / 0.377
2.53	X	0.03 / 0.242
	Y	0.03 / 0.242
	Z	0.25 / 0.337
3.14	X	0.06 / 0.300
	Y	0.08 / 0.300
	Z	0.48 / 0.302
3.94	X	0.07 / 0.377
	Y	0.07 / 0.377
	Z	0.40 / 0.270
5.05	X	0.08 / 0.484
	Y	0.03 / 0.484
	Z	0.06 / 0.268
6.37	X	0.19 / 0.610
	Y	0.13 / 0.610
	Z	0.10 / 0.268
7.98	X	0.14 / 0.764
	Y	0.15 / 0.764
	Z	0.07 / 0.268
10.10	X	0.15 / 0.966
	Y	0.07 / 0.966
	Z	0.07 / 0.338
12.74	X	0.19 / 1.219
	Y	0.04 / 1.219
	Z	0.07 / 0.427
15.97	X	0.07 / 1.528
	Y	0.11 / 1.528
	Z	0.05 / 0.535
20.10	X	0.04 / 1.924
	Y	0.10 / 1.924
	Z	0.04 / 0.673
25.36	X	0.11 / 2.427
	Y	0.08 / 2.427
	Z	0.05 / 0.849
32.02	X	0.04 / 3.064
	Y	0.01 / 3.064
	Z	0.02 / 1.073
40.33	X	0.04 / 3.859
	Y	0.01 / 3.859
	Z	0.00 / 1.351
50.73	X	0.24 / 4.854
	Y	0.04 / 4.854
	Z	0.06 / 1.699
63.97	X	0.06 / 6.121
	Y	0.04 / 6.121
	Z	0.01 / 2.142
80.64	X	0.03 / 7.716
	Y	0.03 / 7.716
	Z	0.00 / 2.701



8-OCT-93 16:14:15

Course: Paved
Speed: 30 mph
Note: Loaded

HSEL: Health and safety exposure limit
FDPB: Fatigue-decreased proficiency boundary
RCB: Reduced comfort boundary
RMS: Vibration R.M.S. acceleration (m/s2)

X: Longitudinal
Y: Transverse
Z: Vertical

RUN-02

Oct 4, 1993

Roadside Seat

HET Ride Quality

Exposure: 10h 0m



Course: Paved
Speed: 30 mph
Note: Loaded

HSEL: Health and safety exposure limit
FDPB: Fatigue-decreased proficiency boundary
RCB: Reduced comfort boundary
RMS: Vibration R.M.S. acceleration (m/s2)

X: Longitudinal
Y: Transverse
Z: Vertical

RUN-02

Oct 4, 1993

Curbside Seat

HET Ride Quality

Exposure: 10h 0m



(Hz)		RMS / FDPB
1.20	X	0.03 / 0.191
	Y	0.02 / 0.191
	Z	0.06 / 0.488
1.61	X	0.04 / 0.191
	Y	0.03 / 0.191
	Z	0.10 / 0.422
2.02	X	0.03 / 0.194
	Y	0.03 / 0.194
	Z	0.14 / 0.377
2.53	X	0.03 / 0.242
	Y	0.02 / 0.242
	Z	0.20 / 0.337
3.14	X	0.06 / 0.300
	Y	0.07 / 0.300
	Z	0.41 / 0.302
3.94	X	0.08 / 0.377
	Y	0.07 / 0.377
	Z	0.35 / 0.270
5.05	X	0.13 / 0.484
	Y	0.05 / 0.484
	Z	0.10 / 0.268
6.37	X	0.26 / 0.610
	Y	0.19 / 0.610
	Z	0.17 / 0.268
7.98	X	0.18 / 0.764
	Y	0.18 / 0.764
	Z	0.08 / 0.268
10.10	X	0.15 / 0.966
	Y	0.13 / 0.966
	Z	0.06 / 0.338
12.74	X	0.17 / 1.219
	Y	0.09 / 1.219
	Z	0.07 / 0.427
15.97	X	0.06 / 1.528
	Y	0.06 / 1.528
	Z	0.05 / 0.535
20.10	X	0.03 / 1.924
	Y	0.05 / 1.924
	Z	0.05 / 0.673
25.36	X	0.08 / 2.427
	Y	0.10 / 2.427
	Z	0.07 / 0.849
32.02	X	0.03 / 3.064
	Y	0.02 / 3.064
	Z	0.04 / 1.073
40.33	X	0.02 / 3.859
	Y	0.02 / 3.859
	Z	0.01 / 1.351
50.73	X	0.09 / 4.854
	Y	0.10 / 4.854
	Z	0.02 / 1.699
63.97	X	0.03 / 6.121
	Y	0.03 / 6.121
	Z	0.01 / 2.142
80.64	X	0.04 / 7.716
	Y	0.04 / 7.716
	Z	0.01 / 2.701

8-OCT-93 16:14:15



Course: Paved
Speed: 30 mph
Note: Loaded

HSEL: Health and safety exposure limit
FDPB: Fatigue-decreased proficiency boundary
RCB: Reduced comfort boundary
RMS: Vibration R.M.S. acceleration (m/s2)

X: Longitudinal
Y: Transverse
Z: Vertical

RUN-03

Oct 4, 1993

Driver Seat

HET Ride Quality

Exposure: 10h 0m

RCB | FDPB | HSEL

(Hz)		RMS / FDPB
1.20	X	0.03 / 0.191
	Y	0.03 / 0.191
	Z	0.07 / 0.488
1.61	X	0.05 / 0.191
	Y	0.04 / 0.191
	Z	0.12 / 0.422
2.02	X	0.04 / 0.194
	Y	0.04 / 0.194
	Z	0.19 / 0.377
2.53	X	0.04 / 0.242
	Y	0.03 / 0.242
	Z	0.19 / 0.337
3.14	X	0.05 / 0.300
	Y	0.02 / 0.300
	Z	0.13 / 0.302
3.94	X	0.11 / 0.377
	Y	0.14 / 0.377
	Z	0.27 / 0.270
5.05	X	0.05 / 0.484
	Y	0.03 / 0.484
	Z	0.05 / 0.268
6.37	X	0.15 / 0.610
	Y	0.07 / 0.610
	Z	0.06 / 0.268
7.98	X	0.14 / 0.764
	Y	0.21 / 0.764
	Z	0.13 / 0.268
10.10	X	0.12 / 0.966
	Y	0.09 / 0.966
	Z	0.06 / 0.338
12.74	X	0.12 / 1.219
	Y	0.06 / 1.219
	Z	0.06 / 0.427
15.97	X	0.08 / 1.528
	Y	0.05 / 1.528
	Z	0.04 / 0.536
20.10	X	0.07 / 1.924
	Y	0.07 / 1.924
	Z	0.03 / 0.673
25.36	X	0.08 / 2.427
	Y	0.08 / 2.427
	Z	0.04 / 0.849
32.02	X	0.07 / 3.064
	Y	0.06 / 3.064
	Z	0.03 / 1.073
40.33	X	0.03 / 3.859
	Y	0.02 / 3.859
	Z	0.02 / 1.351
50.73	X	0.21 / 4.854
	Y	0.04 / 4.854
	Z	0.07 / 1.699
63.97	X	0.11 / 6.121
	Y	0.04 / 6.121
	Z	0.03 / 2.142
80.64	X	0.02 / 7.716
	Y	0.04 / 7.716
	Z	0.01 / 2.701

0.1 1.0 RMS/FDPB ratio 10.

8-OCT-93 16:14:15

-20 -10 0 (deciBels) 10 20

Course: Paved
Speed: 35 mph
Note: Loaded

HSEL: Health and safety exposure limit
FDPB: Fatigue-decreased proficiency boundary
RCB: Reduced comfort boundary
RMS: Vibration R.M.S. acceleration (m/s2)

X: Longitudinal
Y: Transverse
Z: Vertical

RUN-03

Oct 4, 1993

Front Seat

HET Ride Quality

Exposure: 10h 0m



(Hz)		RMS / FDPB
1.20	X	0.03 / 0.191
	Y	0.03 / 0.191
	Z	0.06 / 0.488
1.61	X	0.05 / 0.191
	Y	0.03 / 0.191
	Z	0.10 / 0.422
2.02	X	0.04 / 0.194
	Y	0.03 / 0.194
	Z	0.18 / 0.377
2.53	X	0.03 / 0.242
	Y	0.02 / 0.242
	Z	0.19 / 0.337
3.14	X	0.03 / 0.300
	Y	0.03 / 0.300
	Z	0.14 / 0.302
3.94	X	0.11 / 0.377
	Y	0.17 / 0.377
	Z	0.45 / 0.270
5.05	X	0.05 / 0.484
	Y	0.03 / 0.484
	Z	0.07 / 0.268
6.37	X	0.15 / 0.610
	Y	0.08 / 0.610
	Z	0.05 / 0.268
7.98	X	0.16 / 0.764
	Y	0.26 / 0.764
	Z	0.14 / 0.268
10.10	X	0.15 / 0.966
	Y	0.12 / 0.966
	Z	0.07 / 0.338
12.74	X	0.19 / 1.219
	Y	0.05 / 1.219
	Z	0.08 / 0.427
15.97	X	0.08 / 1.528
	Y	0.11 / 1.528
	Z	0.06 / 0.535
20.10	X	0.05 / 1.924
	Y	0.11 / 1.924
	Z	0.05 / 0.673
25.36	X	0.08 / 2.427
	Y	0.03 / 2.427
	Z	0.03 / 0.849
32.02	X	0.09 / 3.064
	Y	0.03 / 3.064
	Z	0.03 / 1.073
40.33	X	0.05 / 3.859
	Y	0.01 / 3.859
	Z	0.01 / 1.351
50.73	X	0.27 / 4.854
	Y	0.09 / 4.854
	Z	0.07 / 1.699
63.97	X	0.10 / 6.121
	Y	0.06 / 6.121
	Z	0.02 / 2.142
80.64	X	0.03 / 7.716
	Y	0.03 / 7.716
	Z	0.01 / 2.701



8-OCT-93 16:14:15

Course: Paved
Speed: 35 mph
Note: Loaded

HSEL: Health and safety exposure limit
FDPB: Fatigue-decreased proficiency boundary
RCB: Reduced comfort boundary
RMS: Vibration R.M.S. acceleration (m/s2)

X: Longitudinal
Y: Transverse
Z: Vertical

RUN-03

Oct 4, 1993

Roadside Seat

HET Ride Quality

Exposure: 10h 0m



8-OCT-93 16:14:15

Course: Paved
Speed: 35 mph
Note: Loaded

HSEL: Health and safety exposure limit
FDPB: Fatigue-decreased proficiency boundary
RCB: Reduced comfort boundary
RMS: Vibration R.M.S. acceleration (m/s2)

X: Longitudinal
Y: Transverse
Z: Vertical

RUN-03

Oct 4, 1993

Curbside Seat

HET Ride Quality

Exposure: 10h 0m



8-OCT-93 16:14:16

Course: Paved
Speed: 35 mph
Note: Loaded

HSEL: Health and safety exposure limit
FDPB: Fatigue-decreased proficiency boundary
RCB: Reduced comfort boundary
RMS: Vibration R.M.S. acceleration (m/s2)

X: Longitudinal
Y: Transverse
Z: Vertical

RUN-04

Oct 4, 1993

Driver Seat

HET Ride Quality

Exposure: 10h 0m



8-OCT-93 16:14:16

Course: Paved
Speed: 40 mph
Note: Loaded

HSEL: Health and safety exposure limit
FDPB: Fatigue-decreased proficiency boundary
RCB: Reduced comfort boundary
RMS: Vibration R.M.S. acceleration (m/s2)

X: Longitudinal
Y: Transverse
Z: Vertical

RUN-04

Oct 4, 1993

Front Seat

HET Ride Quality

Exposure: 10h 0m



(Hz)		RMS / FDPB
1.20	X	0.04 / 0.191
	Y	0.03 / 0.191
	Z	0.08 / 0.488
1.61	X	0.09 / 0.191
	Y	0.04 / 0.191
	Z	0.12 / 0.422
2.02	X	0.07 / 0.194
	Y	0.03 / 0.194
	Z	0.23 / 0.377
2.53	X	0.04 / 0.242
	Y	0.02 / 0.242
	Z	0.28 / 0.337
3.14	X	0.02 / 0.300
	Y	0.02 / 0.300
	Z	0.12 / 0.302
3.94	X	0.11 / 0.377
	Y	0.18 / 0.377
	Z	0.36 / 0.270
5.05	X	0.13 / 0.484
	Y	0.20 / 0.484
	Z	0.37 / 0.268
6.37	X	0.09 / 0.610
	Y	0.06 / 0.610
	Z	0.06 / 0.268
7.98	X	0.21 / 0.764
	Y	0.16 / 0.764
	Z	0.12 / 0.268
10.10	X	0.25 / 0.966
	Y	0.21 / 0.966
	Z	0.14 / 0.338
12.74	X	0.25 / 1.219
	Y	0.04 / 1.219
	Z	0.08 / 0.427
15.97	X	0.06 / 1.528
	Y	0.10 / 1.528
	Z	0.06 / 0.536
20.10	X	0.04 / 1.924
	Y	0.09 / 1.924
	Z	0.05 / 0.673
25.36	X	0.04 / 2.427
	Y	0.03 / 2.427
	Z	0.02 / 0.849
32.02	X	0.07 / 3.064
	Y	0.03 / 3.064
	Z	0.03 / 1.073
40.33	X	0.06 / 3.859
	Y	0.02 / 3.859
	Z	0.01 / 1.351
50.73	X	0.07 / 4.854
	Y	0.02 / 4.854
	Z	0.02 / 1.699
63.97	X	0.13 / 6.121
	Y	0.08 / 6.121
	Z	0.02 / 2.142
80.64	X	0.02 / 7.716
	Y	0.02 / 7.716
	Z	0.00 / 2.701



8-OCT-93 16:14:16

Course: Paved
Speed: 40 mph
Note: Loaded

HSEL: Health and safety exposure limit
FDPB: Fatigue-decreased proficiency boundary
RCB: Reduced comfort boundary
RMS: Vibration R.M.S. acceleration (m/s2)

X: Longitudinal
Y: Transverse
Z: Vertical

RUN-04
Oct 4, 1993

Roadside Seat
HET Ride Quality

Exposure: 10h 0m



(Hz)		RMS / FDPB
1.20	X	0.03 / 0.191
	Y	0.03 / 0.191
	Z	0.08 / 0.488
1.61	X	0.06 / 0.191
	Y	0.03 / 0.191
	Z	0.12 / 0.422
2.02	X	0.05 / 0.194
	Y	0.03 / 0.194
	Z	0.19 / 0.377
2.53	X	0.02 / 0.242
	Y	0.03 / 0.242
	Z	0.21 / 0.337
3.14	X	0.02 / 0.300
	Y	0.02 / 0.300
	Z	0.10 / 0.302
3.94	X	0.21 / 0.377
	Y	0.13 / 0.377
	Z	0.33 / 0.270
5.05	X	0.24 / 0.484
	Y	0.15 / 0.484
	Z	0.36 / 0.268
6.37	X	0.15 / 0.610
	Y	0.08 / 0.610
	Z	0.12 / 0.268
7.98	X	0.20 / 0.764
	Y	0.21 / 0.764
	Z	0.14 / 0.268
10.10	X	0.20 / 0.966
	Y	0.29 / 0.966
	Z	0.12 / 0.338
12.74	X	0.20 / 1.219
	Y	0.10 / 1.219
	Z	0.08 / 0.427
15.97	X	0.06 / 1.528
	Y	0.05 / 1.528
	Z	0.06 / 0.535
20.10	X	0.05 / 1.924
	Y	0.06 / 1.924
	Z	0.06 / 0.673
25.36	X	0.04 / 2.427
	Y	0.05 / 2.427
	Z	0.04 / 0.849
32.02	X	0.06 / 3.064
	Y	0.08 / 3.064
	Z	0.05 / 1.073
40.33	X	0.03 / 3.859
	Y	0.02 / 3.859
	Z	0.01 / 1.351
50.73	X	0.03 / 4.854
	Y	0.02 / 4.854
	Z	0.01 / 1.699
63.97	X	0.05 / 6.121
	Y	0.04 / 6.121
	Z	0.04 / 2.142
80.64	X	0.02 / 7.716
	Y	0.02 / 7.716
	Z	0.01 / 2.701



8-OCT-93 16:14:16

Course: Paved
Speed: 40 mph
Note: Loaded

HSEL: Health and safety exposure limit
FDPB: Fatigue-decreased proficiency boundary
RCB: Reduced comfort boundary
RMS: Vibration R.M.S. acceleration (m/s2)

X: Longitudinal
Y: Transverse
Z: Vertical

RUN-04

Oct 4, 1993

Curbside Seat

HET Ride Quality

Exposure: 10h 0m



(Hz)		RMS / FDPB
1.20	X	0.04 / 0.191
	Y	0.03 / 0.191
	Z	0.08 / 0.488
1.61	X	0.07 / 0.191
	Y	0.04 / 0.191
	Z	0.11 / 0.422
2.02	X	0.06 / 0.194
	Y	0.03 / 0.194
	Z	0.19 / 0.377
2.53	X	0.02 / 0.242
	Y	0.02 / 0.242
	Z	0.23 / 0.337
3.14	X	0.02 / 0.300
	Y	0.02 / 0.300
	Z	0.10 / 0.302
3.94	X	0.19 / 0.377
	Y	0.12 / 0.377
	Z	0.33 / 0.270
5.05	X	0.23 / 0.484
	Y	0.14 / 0.484
	Z	0.35 / 0.268
6.37	X	0.15 / 0.610
	Y	0.08 / 0.610
	Z	0.11 / 0.268
7.98	X	0.21 / 0.764
	Y	0.22 / 0.764
	Z	0.11 / 0.268
10.10	X	0.21 / 0.966
	Y	0.29 / 0.966
	Z	0.10 / 0.338
12.74	X	0.20 / 1.219
	Y	0.12 / 1.219
	Z	0.08 / 0.427
15.97	X	0.05 / 1.528
	Y	0.06 / 1.528
	Z	0.05 / 0.535
20.10	X	0.05 / 1.924
	Y	0.06 / 1.924
	Z	0.05 / 0.673
25.36	X	0.05 / 2.427
	Y	0.04 / 2.427
	Z	0.03 / 0.849
32.02	X	0.09 / 3.064
	Y	0.09 / 3.064
	Z	0.03 / 1.073
40.33	X	0.03 / 3.859
	Y	0.02 / 3.859
	Z	0.01 / 1.351
50.73	X	0.03 / 4.854
	Y	0.02 / 4.854
	Z	0.00 / 1.699
63.97	X	0.07 / 6.121
	Y	0.05 / 6.121
	Z	0.02 / 2.142
80.64	X	0.03 / 7.716
	Y	0.03 / 7.716
	Z	0.00 / 2.701

8-OCT-93 16:14:16



Course: Paved
Speed: 40 mph
Note: Loaded

HSEL: Health and safety exposure limit
FDPB: Fatigue-decreased proficiency boundary
RCB: Reduced comfort boundary
RMS: Vibration R.M.S. acceleration (m/s2)

X: Longitudinal
Y: Transverse
Z: Vertical

RUN-05

Oct 4, 1993

Driver Seat

HET Ride Quality

Exposure: 10h 0m



Course: Cross Country #2
Speed: 5 mph
Note: Loaded

HSEL: Health and safety exposure limit
FDPB: Fatigue-decreased proficiency boundary
RCB: Reduced comfort boundary
RMS: Vibration R.M.S. acceleration (m/s2)

X: Longitudinal
Y: Transverse
Z: Vertical

RUN-05

Oct 4, 1993

Front Seat

HET Ride Quality

Exposure: 10h 0m



Course: Cross Country #2
Speed: 5 mph
Note: Loaded

HSEL: Health and safety exposure limit
FDPB: Fatigue-decreased proficiency boundary
RCB: Reduced comfort boundary
RMS: Vibration R.M.S. acceleration (m/s2)

X: Longitudinal
Y: Transverse
Z: Vertical

RUN-05

Oct 4, 1993

Roadside Seat

HET Ride Quality

Exposure: 10h 0m



Course: Cross Country #2
Speed: 5 mph
Note: Loaded

HSEL: Health and safety exposure limit
FDPB: Fatigue-decreased proficiency boundary
RCB: Reduced comfort boundary
RMS: Vibration R.M.S. acceleration (m/s2)

X: Longitudinal
Y: Transverse
Z: Vertical

RUN-05

Oct 4, 1993

Curbside Seat

HET Ride Quality

Exposure: 10h 0m



(Hz)		RMS / FDPB
1.20	X	0.09 / 0.191
	Y	0.13 / 0.191
	Z	0.14 / 0.488
1.61	X	0.08 / 0.191
	Y	0.10 / 0.191
	Z	0.16 / 0.422
2.02	X	0.05 / 0.194
	Y	0.05 / 0.194
	Z	0.20 / 0.377
2.53	X	0.05 / 0.242
	Y	0.04 / 0.242
	Z	0.16 / 0.337
3.14	X	0.05 / 0.300
	Y	0.03 / 0.300
	Z	0.08 / 0.302
3.94	X	0.09 / 0.377
	Y	0.05 / 0.377
	Z	0.08 / 0.270
5.05	X	0.09 / 0.484
	Y	0.06 / 0.484
	Z	0.05 / 0.268
6.37	X	0.12 / 0.610
	Y	0.12 / 0.610
	Z	0.08 / 0.268
7.98	X	0.09 / 0.764
	Y	0.14 / 0.764
	Z	0.05 / 0.268
10.10	X	0.07 / 0.966
	Y	0.11 / 0.966
	Z	0.06 / 0.338
12.74	X	0.17 / 1.219
	Y	0.15 / 1.219
	Z	0.14 / 0.427
15.97	X	0.08 / 1.528
	Y	0.09 / 1.528
	Z	0.05 / 0.535
20.10	X	0.11 / 1.924
	Y	0.14 / 1.924
	Z	0.18 / 0.673
25.36	X	0.06 / 2.427
	Y	0.04 / 2.427
	Z	0.08 / 0.849
32.02	X	0.02 / 3.064
	Y	0.03 / 3.064
	Z	0.02 / 1.073
40.33	X	0.02 / 3.859
	Y	0.03 / 3.859
	Z	0.01 / 1.351
50.73	X	0.02 / 4.854
	Y	0.01 / 4.854
	Z	0.01 / 1.699
63.97	X	0.03 / 6.121
	Y	0.13 / 6.121
	Z	0.02 / 2.142
80.64	X	0.03 / 7.716
	Y	0.06 / 7.716
	Z	0.01 / 2.701



8-OCT-93 16:14:17

Course: Cross Country #2
Speed: 5 mph
Note: Loaded

HSEL: Health and safety exposure limit
FDPB: Fatigue-decreased proficiency boundary
RCB: Reduced comfort boundary
RMS: Vibration R.M.S. acceleration (m/s2)

X: Longitudinal
Y: Transverse
Z: Vertical

RUN-06

Oct 4, 1993

Driver Seat

HET Ride Quality

Exposure: 10h 0m



8-OCT-93 16:14:18

Course: Cross Country #2
Speed: 10 mph
Note: Loaded

HSEL: Health and safety exposure limit
FDPB: Fatigue-decreased proficiency boundary
RCB: Reduced comfort boundary
RMS: Vibration R.M.S. acceleration (m/s2)

X: Longitudinal
Y: Transverse
Z: Vertical

RUN-06

Oct 4, 1993

Front Seat

HET Ride Quality

Exposure: 10h 0m



8-OCT-93 16:14:18

Course: Cross Country #2
Speed: 10 mph
Note: Loaded

HSEL: Health and safety exposure limit
FDPB: Fatigue-decreased proficiency boundary
RCB: Reduced comfort boundary
RMS: Vibration R.M.S. acceleration (m/s2)

X: Longitudinal
Y: Transverse
Z: Vertical

RUN-06

Oct 4, 1993

Roadside Seat

HET Ride Quality

Exposure: 10h 0m



Course: Cross Country #2
Speed: 10 mph
Note: Loaded

HSEL: Health and safety exposure limit
FDPB: Fatigue-decreased proficiency boundary
RCB: Reduced comfort boundary
RMS: Vibration R.M.S. acceleration (m/s2)

X: Longitudinal
Y: Transverse
Z: Vertical

RUN-06

Oct 4, 1993

Curbside Seat

HET Ride Quality

Exposure: 10h 0m



8-OCT-93 16:14:18

Course: Cross Country #2
Speed: 10 mph
Note: Loaded

HSEL: Health and safety exposure limit
FDPB: Fatigue-decreased proficiency boundary
RCB: Reduced comfort boundary
RMS: Vibration R.M.S. acceleration (m/s2)

X: Longitudinal
Y: Transverse
Z: Vertical

RUN-07 **Driver Seat**

Oct 4, 1993 **HET Ride Quality**

Exposure: 10h 0m



8-OCT-93 16:14:19

Course: Cross Country #2
Speed: 15 mph
Note: Loaded

HSEL: Health and safety exposure limit
FDPB: Fatigue-decreased proficiency boundary
RCB: Reduced comfort boundary
RMS: Vibration R.M.S. acceleration (m/s2)

X: Longitudinal
Y: Transverse
Z: Vertical

RUN-07

Oct 4, 1993

Front Seat

HET Ride Quality

Exposure: 10h 0m



8-OCT-93 16:14:19

Course: Cross Country #2
Speed: 15 mph
Note: Loaded

HSEL: Health and safety exposure limit
FDPB: Fatigue-decreased proficiency boundary
RCB: Reduced comfort boundary
RMS: Vibration R.M.S. acceleration (m/s2)

X: Longitudinal
Y: Transverse
Z: Vertical

RUN-07
Oct 4, 1993

Roadside Seat
HET Ride Quality

Exposure: 10h 0m



Course: Cross Country #2
Speed: 15 mph
Note: Loaded

HSEL: Health and safety exposure limit
FDPB: Fatigue-decreased proficiency boundary
RCB: Reduced comfort boundary
RMS: Vibration R.M.S. acceleration (m/s2)

X: Longitudinal
Y: Transverse
Z: Vertical

RUN-07
Oct 4, 1993

Curbside Seat
HET Ride Quality

Exposure: 10h 0m



Course: Cross Country #2
Speed: 15 mph
Note: Loaded

HSEL: Health and safety exposure limit
FDPB: Fatigue-decreased proficiency boundary
RCB: Reduced comfort boundary
RMS: Vibration R.M.S. acceleration (m/s2)

X: Longitudinal
Y: Transverse
Z: Vertical

RUN-08

Oct 4, 1993

Driver Seat

HET Ride Quality

Exposure: 10h 0m



(Hz)		RMS / FDPB
1.20	X	0.05 / 0.191
	Y	0.16 / 0.191
	Z	0.18 / 0.488
1.61	X	0.05 / 0.191
	Y	0.13 / 0.191
	Z	0.24 / 0.422
2.02	X	0.06 / 0.194
	Y	0.12 / 0.194
	Z	0.36 / 0.377
2.53	X	0.08 / 0.242
	Y	0.13 / 0.242
	Z	0.38 / 0.337
3.14	X	0.12 / 0.300
	Y	0.11 / 0.300
	Z	0.20 / 0.302
3.94	X	0.14 / 0.377
	Y	0.10 / 0.377
	Z	0.18 / 0.270
5.05	X	0.16 / 0.484
	Y	0.10 / 0.484
	Z	0.11 / 0.268
6.37	X	0.19 / 0.610
	Y	0.18 / 0.610
	Z	0.12 / 0.268
7.98	X	0.15 / 0.764
	Y	0.16 / 0.764
	Z	0.08 / 0.268
10.10	X	0.16 / 0.966
	Y	0.10 / 0.966
	Z	0.08 / 0.338
12.74	X	0.17 / 1.219
	Y	0.07 / 1.219
	Z	0.08 / 0.427
15.97	X	0.23 / 1.528
	Y	0.21 / 1.528
	Z	0.12 / 0.535
20.10	X	0.12 / 1.924
	Y	0.08 / 1.924
	Z	0.07 / 0.673
25.36	X	0.12 / 2.427
	Y	0.11 / 2.427
	Z	0.05 / 0.849
32.02	X	0.05 / 3.064
	Y	0.04 / 3.064
	Z	0.03 / 1.073
40.33	X	0.05 / 3.859
	Y	0.04 / 3.859
	Z	0.02 / 1.351
50.73	X	0.08 / 4.854
	Y	0.02 / 4.854
	Z	0.02 / 1.699
63.97	X	0.05 / 6.121
	Y	0.02 / 6.121
	Z	0.01 / 2.142
80.64	X	0.03 / 7.716
	Y	0.03 / 7.716
	Z	0.00 / 2.701



8-OCT-93 16:14:19

Course: Secondary A
Speed: 10 mph
Note: Loaded

HSEL: Health and safety exposure limit
FDPB: Fatigue-decreased proficiency boundary
RCB: Reduced comfort boundary
RMS: Vibration R.M.S. acceleration (m/s2)

X: Longitudinal
Y: Transverse
Z: Vertical

RUN-08

Oct 4, 1993

Front Seat

HET Ride Quality

Exposure: 10h 0m



Course: Secondary A
Speed: 10 mph
Note: Loaded

HSEL: Health and safety exposure limit
FDPB: Fatigue-decreased proficiency boundary
RCB: Reduced comfort boundary
RMS: Vibration R.M.S. acceleration (m/s2)

X: Longitudinal
Y: Transverse
Z: Vertical

RUN-08

Oct 4, 1993

Roadside Seat

HET Ride Quality

Exposure: 10h 0m



(Hz)		RMS / FDPB
1.20	X	0.04 / 0.191
	Y	0.12 / 0.191
	Z	0.15 / 0.488
1.61	X	0.05 / 0.191
	Y	0.09 / 0.191
	Z	0.19 / 0.422
2.02	X	0.06 / 0.194
	Y	0.08 / 0.194
	Z	0.28 / 0.377
2.53	X	0.07 / 0.242
	Y	0.09 / 0.242
	Z	0.31 / 0.337
3.14	X	0.14 / 0.300
	Y	0.08 / 0.300
	Z	0.21 / 0.302
3.94	X	0.18 / 0.377
	Y	0.09 / 0.377
	Z	0.20 / 0.270
5.05	X	0.25 / 0.484
	Y	0.12 / 0.484
	Z	0.16 / 0.268
6.37	X	0.27 / 0.610
	Y	0.21 / 0.610
	Z	0.18 / 0.268
7.98	X	0.20 / 0.764
	Y	0.21 / 0.764
	Z	0.13 / 0.268
10.10	X	0.20 / 0.966
	Y	0.15 / 0.966
	Z	0.16 / 0.338
12.74	X	0.19 / 1.219
	Y	0.15 / 1.219
	Z	0.14 / 0.427
15.97	X	0.18 / 1.528
	Y	0.25 / 1.528
	Z	0.29 / 0.535
20.10	X	0.10 / 1.924
	Y	0.09 / 1.924
	Z	0.12 / 0.673
25.36	X	0.08 / 2.427
	Y	0.07 / 2.427
	Z	0.09 / 0.849
32.02	X	0.04 / 3.064
	Y	0.04 / 3.064
	Z	0.03 / 1.073
40.33	X	0.05 / 3.859
	Y	0.03 / 3.859
	Z	0.02 / 1.351
50.73	X	0.03 / 4.854
	Y	0.02 / 4.854
	Z	0.01 / 1.699
63.97	X	0.02 / 6.121
	Y	0.03 / 6.121
	Z	0.01 / 2.142
80.64	X	0.04 / 7.716
	Y	0.05 / 7.716
	Z	0.01 / 2.701



8-OCT-93 16:14:19

Course: Secondary A
Speed: 10 mph
Note: Loaded

HSEL: Health and safety exposure limit
FDPB: Fatigue-decreased proficiency boundary
RCB: Reduced comfort boundary
RMS: Vibration R.M.S. acceleration (m/s2)

X: Longitudinal
Y: Transverse
Z: Vertical

RUN-08

Oct 4, 1993

Curbside Seat

HET Ride Quality

Exposure: 10h 0m



Course: Secondary A
Speed: 10 mph
Note: Loaded

HSEL: Health and safety exposure limit
FDPB: Fatigue-decreased proficiency boundary
RCB: Reduced comfort boundary
RMS: Vibration R.M.S. acceleration (m/s2)

X: Longitudinal
Y: Transverse
Z: Vertical

RUN-09
Oct 4, 1993

Driver Seat
HET Ride Quality

Exposure: 10h 0m



8-OCT-93 16:14:20

Course: Secondary A
Speed: 15 mph
Note: Loaded

HSEL: Health and safety exposure limit
FDPB: Fatigue-decreased proficiency boundary
RCB: Reduced comfort boundary
RMS: Vibration R.M.S. acceleration (m/s2)

X: Longitudinal
Y: Transverse
Z: Vertical

RUN-09

Oct 4, 1993

Front Seat

HET Ride Quality

Exposure: 10h 0m



(Hz)		RMS / FDPB
1.20	X	0.05 / 0.191
	Y	0.10 / 0.191
	Z	0.12 / 0.488
1.61	X	0.08 / 0.191
	Y	0.12 / 0.191
	Z	0.30 / 0.422
2.02	X	0.06 / 0.194
	Y	0.09 / 0.194
	Z	0.35 / 0.377
2.53	X	0.04 / 0.242
	Y	0.06 / 0.242
	Z	0.31 / 0.337
3.14	X	0.06 / 0.300
	Y	0.07 / 0.300
	Z	0.23 / 0.302
3.94	X	0.13 / 0.377
	Y	0.07 / 0.377
	Z	0.24 / 0.270
5.05	X	0.11 / 0.484
	Y	0.07 / 0.484
	Z	0.13 / 0.268
6.37	X	0.15 / 0.610
	Y	0.10 / 0.610
	Z	0.12 / 0.268
7.98	X	0.20 / 0.764
	Y	0.21 / 0.764
	Z	0.12 / 0.268
10.10	X	0.17 / 0.966
	Y	0.07 / 0.966
	Z	0.08 / 0.338
12.74	X	0.21 / 1.219
	Y	0.07 / 1.219
	Z	0.10 / 0.427
15.97	X	0.10 / 1.528
	Y	0.12 / 1.528
	Z	0.08 / 0.535
20.10	X	0.06 / 1.924
	Y	0.10 / 1.924
	Z	0.06 / 0.673
25.36	X	0.14 / 2.427
	Y	0.12 / 2.427
	Z	0.08 / 0.849
32.02	X	0.05 / 3.064
	Y	0.02 / 3.064
	Z	0.02 / 1.073
40.33	X	0.05 / 3.859
	Y	0.02 / 3.859
	Z	0.02 / 1.351
50.73	X	0.07 / 4.854
	Y	0.03 / 4.854
	Z	0.02 / 1.699
63.97	X	0.03 / 6.121
	Y	0.03 / 6.121
	Z	0.01 / 2.142
80.64	X	0.02 / 7.716
	Y	0.03 / 7.716
	Z	0.01 / 2.701



8-OCT-93 16:14:20

Course: Secondary A
Speed: 15 mph
Note: Loaded

HSEL: Health and safety exposure limit
FDPB: Fatigue-decreased proficiency boundary
RCB: Reduced comfort boundary
RMS: Vibration R.M.S. acceleration (m/s2)

X: Longitudinal
Y: Transverse
Z: Vertical

RUN-09
Oct 4, 1993

Roadside Seat
HET Ride Quality

Exposure: 10h 0m



8-OCT-93 16:14:20

Course: Secondary A
Speed: 15 mph
Note: Loaded

HSEL: Health and safety exposure limit
FDPB: Fatigue-decreased proficiency boundary
RCB: Reduced comfort boundary
RMS: Vibration R.M.S. acceleration (m/s2)

X: Longitudinal
Y: Transverse
Z: Vertical

RUN-09

Oct 4, 1993

Curbside Seat

HET Ride Quality

Exposure: 10h 0m



8-OCT-93 16:14:20

Course: Secondary A
Speed: 15 mph
Note: Loaded

HSEL: Health and safety exposure limit
FDPB: Fatigue-decreased proficiency boundary
RCB: Reduced comfort boundary
RMS: Vibration R.M.S. acceleration (m/s2)

X: Longitudinal
Y: Transverse
Z: Vertical

RUN-10
Oct 4, 1993

Driver Seat
HET Ride Quality

Exposure: 10h 0m



Course: Secondary A
Speed: 20 mph
Note: Loaded

HSEL: Health and safety exposure limit
FDPB: Fatigue-decreased proficiency boundary
RCB: Reduced comfort boundary
RMS: Vibration R.M.S. acceleration (m/s2)

X: Longitudinal
Y: Transverse
Z: Vertical

RUN-10

Oct 4, 1993

Front Seat

HET Ride Quality

Exposure: 10h 0m



Course: Secondary A
Speed: 20 mph
Note: Loaded

HSEL: Health and safety exposure limit
FDPB: Fatigue-decreased proficiency boundary
RCB: Reduced comfort boundary
RMS: Vibration R.M.S. acceleration (m/s2)

X: Longitudinal
Y: Transverse
Z: Vertical

RUN-10
Oct 4, 1993

Roadside Seat
HET Ride Quality

Exposure: 10h 0m



8-OCT-93 16:14:21

Course: Secondary A
Speed: 20 mph
Note: Loaded

HSEL: Health and safety exposure limit
FDPB: Fatigue-decreased proficiency boundary
RCB: Reduced comfort boundary
RMS: Vibration R.M.S. acceleration (m/s2)

X: Longitudinal
Y: Transverse
Z: Vertical

RUN-10

Oct 4, 1993

Curbside Seat

HET Ride Quality

Exposure: 10h 0m



Course: Secondary A
Speed: 20 mph
Note: Loaded

HSEL: Health and safety exposure limit
FDPB: Fatigue-decreased proficiency boundary
RCB: Reduced comfort boundary
RMS: Vibration R.M.S. acceleration (m/s2)

X: Longitudinal
Y: Transverse
Z: Vertical

RUN-11

Oct 4, 1993

Driver Seat

HET Ride Quality

Exposure: 10h 0m



(Hz)		RMS / FDPB
1.20	X	0.08 / 0.191
	Y	0.11 / 0.191
	Z	0.15 / 0.488
1.61	X	0.08 / 0.191
	Y	0.10 / 0.191
	Z	0.23 / 0.422
2.02	X	0.06 / 0.194
	Y	0.10 / 0.194
	Z	0.37 / 0.377
2.53	X	0.08 / 0.242
	Y	0.12 / 0.242
	Z	0.40 / 0.337
3.14	X	0.07 / 0.300
	Y	0.09 / 0.300
	Z	0.24 / 0.302
3.94	X	0.13 / 0.377
	Y	0.10 / 0.377
	Z	0.17 / 0.270
5.05	X	0.23 / 0.484
	Y	0.13 / 0.484
	Z	0.17 / 0.268
6.37	X	0.39 / 0.610
	Y	0.24 / 0.610
	Z	0.18 / 0.268
7.98	X	0.34 / 0.764
	Y	0.35 / 0.764
	Z	0.18 / 0.268
10.10	X	0.39 / 0.966
	Y	0.25 / 0.966
	Z	0.16 / 0.338
12.74	X	0.40 / 1.219
	Y	0.17 / 1.219
	Z	0.13 / 0.427
15.97	X	0.18 / 1.528
	Y	0.10 / 1.528
	Z	0.10 / 0.535
20.10	X	0.14 / 1.924
	Y	0.12 / 1.924
	Z	0.09 / 0.673
25.36	X	0.10 / 2.427
	Y	0.12 / 2.427
	Z	0.05 / 0.849
32.02	X	0.06 / 3.064
	Y	0.05 / 3.064
	Z	0.04 / 1.073
40.33	X	0.04 / 3.859
	Y	0.05 / 3.859
	Z	0.02 / 1.351
50.73	X	0.07 / 4.854
	Y	0.02 / 4.854
	Z	0.02 / 1.699
63.97	X	0.07 / 6.121
	Y	0.03 / 6.121
	Z	0.02 / 2.142
80.64	X	0.03 / 7.716
	Y	0.03 / 7.716
	Z	0.00 / 2.701



8-OCT-93 16:14:22

Course: Secondary A
Speed: 25 mph
Note: Loaded

HSEL: Health and safety exposure limit
FDPB: Fatigue-decreased proficiency boundary
RCB: Reduced comfort boundary
RMS: Vibration R.M.S. acceleration (m/s2)

X: Longitudinal
Y: Transverse
Z: Vertical

RUN-11

Oct 4, 1993

Front Seat

HET Ride Quality

Exposure: 10h 0m



(Hz)		RMS / FDPB
1.20	X	0.09 / 0.191
	Y	0.10 / 0.191
	Z	0.14 / 0.488
1.61	X	0.09 / 0.191
	Y	0.08 / 0.191
	Z	0.26 / 0.422
2.02	X	0.05 / 0.194
	Y	0.06 / 0.194
	Z	0.38 / 0.377
2.53	X	0.05 / 0.242
	Y	0.07 / 0.242
	Z	0.46 / 0.337
3.14	X	0.04 / 0.300
	Y	0.06 / 0.300
	Z	0.28 / 0.302
3.94	X	0.10 / 0.377
	Y	0.08 / 0.377
	Z	0.19 / 0.270
5.05	X	0.19 / 0.484
	Y	0.11 / 0.484
	Z	0.15 / 0.268
6.37	X	0.28 / 0.610
	Y	0.23 / 0.610
	Z	0.20 / 0.268
7.98	X	0.30 / 0.764
	Y	0.29 / 0.764
	Z	0.18 / 0.268
10.10	X	0.33 / 0.966
	Y	0.16 / 0.966
	Z	0.17 / 0.338
12.74	X	0.40 / 1.219
	Y	0.12 / 1.219
	Z	0.18 / 0.427
15.97	X	0.14 / 1.528
	Y	0.23 / 1.528
	Z	0.10 / 0.535
20.10	X	0.09 / 1.924
	Y	0.16 / 1.924
	Z	0.08 / 0.673
25.36	X	0.08 / 2.427
	Y	0.04 / 2.427
	Z	0.05 / 0.849
32.02	X	0.06 / 3.064
	Y	0.02 / 3.064
	Z	0.03 / 1.073
40.33	X	0.11 / 3.859
	Y	0.02 / 3.859
	Z	0.03 / 1.351
50.73	X	0.06 / 4.854
	Y	0.03 / 4.854
	Z	0.02 / 1.699
63.97	X	0.04 / 6.121
	Y	0.05 / 6.121
	Z	0.01 / 2.142
80.64	X	0.03 / 7.716
	Y	0.04 / 7.716
	Z	0.01 / 2.701



8-OCT-93 16:14:22

Course: Secondary A
Speed: 25 mph
Note: Loaded

HSEL: Health and safety exposure limit
FDPB: Fatigue-decreased proficiency boundary
RCB: Reduced comfort boundary
RMS: Vibration R.M.S. acceleration (m/s2)

X: Longitudinal
Y: Transverse
Z: Vertical

RUN-11
Oct 4, 1993

Roadside Seat
HET Ride Quality

Exposure: 10h 0m



8-OCT-93 16:14:22

Course: Secondary A
Speed: 25 mph
Note: Loaded

HSEL: Health and safety exposure limit
FDPB: Fatigue-decreased proficiency boundary
RCB: Reduced comfort boundary
RMS: Vibration R.M.S. acceleration (m/s2)

X: Longitudinal
Y: Transverse
Z: Vertical

RUN-11

Oct 4, 1993

Curbside Seat

HET Ride Quality

Exposure: 10h 0m



(Hz)		RMS / FDPB
1.20	X	0.08 / 0.191
	Y	0.08 / 0.191
	Z	0.13 / 0.488
1.61	X	0.07 / 0.191
	Y	0.06 / 0.191
	Z	0.22 / 0.422
2.02	X	0.05 / 0.194
	Y	0.05 / 0.194
	Z	0.33 / 0.377
2.53	X	0.05 / 0.242
	Y	0.06 / 0.242
	Z	0.40 / 0.337
3.14	X	0.06 / 0.300
	Y	0.06 / 0.300
	Z	0.26 / 0.302
3.94	X	0.19 / 0.377
	Y	0.10 / 0.377
	Z	0.21 / 0.270
5.05	X	0.35 / 0.484
	Y	0.19 / 0.484
	Z	0.20 / 0.268
6.37	X	0.50 / 0.610
	Y	0.32 / 0.610
	Z	0.34 / 0.268
7.98	X	0.46 / 0.764
	Y	0.38 / 0.764
	Z	0.19 / 0.268
10.10	X	0.42 / 0.966
	Y	0.39 / 0.966
	Z	0.19 / 0.338
12.74	X	0.43 / 1.219
	Y	0.37 / 1.219
	Z	0.21 / 0.427
15.97	X	0.13 / 1.528
	Y	0.16 / 1.528
	Z	0.14 / 0.535
20.10	X	0.09 / 1.924
	Y	0.13 / 1.924
	Z	0.12 / 0.673
25.36	X	0.08 / 2.427
	Y	0.07 / 2.427
	Z	0.07 / 0.849
32.02	X	0.05 / 3.064
	Y	0.06 / 3.064
	Z	0.05 / 1.073
40.33	X	0.06 / 3.859
	Y	0.11 / 3.859
	Z	0.03 / 1.351
50.73	X	0.04 / 4.854
	Y	0.02 / 4.854
	Z	0.02 / 1.699
63.97	X	0.05 / 6.121
	Y	0.06 / 6.121
	Z	0.02 / 2.142
80.64	X	0.03 / 7.716
	Y	0.07 / 7.716
	Z	0.02 / 2.701

8-OCT-93 16:14:22



Course: Secondary A
Speed: 25 mph
Note: Loaded

HSEL: Health and safety exposure limit
FDPB: Fatigue-decreased proficiency boundary
RCB: Reduced comfort boundary
RMS: Vibration R.M.S. acceleration (m/s2)

X: Longitudinal
Y: Transverse
Z: Vertical

RUN-12 — Oct 4, 1993

Driver Seat — HET Ride Quality

Exposure: 10h 0m



8-OCT-93 16:14:23

Course: Cross Country #2
Speed: 5 mph
Note: No Load

HSEL: Health and safety exposure limit
FDPB: Fatigue-decreased proficiency boundary
RCB: Reduced comfort boundary
RMS: Vibration R.M.S. acceleration (m/s2)

X: Longitudinal
Y: Transverse
Z: Vertical

RUN-12

Oct 4, 1993

Front Seat

HET Ride Quality

Exposure: 10h 0m



(Hz)		RMS / FDPB
1.20	X	0.04 / 0.191
	Y	0.10 / 0.191
	Z	0.08 / 0.488
1.61	X	0.06 / 0.191
	Y	0.10 / 0.191
	Z	0.16 / 0.422
2.02	X	0.04 / 0.194
	Y	0.05 / 0.194
	Z	0.22 / 0.377
2.53	X	0.03 / 0.242
	Y	0.02 / 0.242
	Z	0.16 / 0.337
3.14	X	0.02 / 0.300
	Y	0.03 / 0.300
	Z	0.09 / 0.302
3.94	X	0.03 / 0.377
	Y	0.04 / 0.377
	Z	0.09 / 0.270
5.05	X	0.04 / 0.484
	Y	0.04 / 0.484
	Z	0.05 / 0.268
6.37	X	0.07 / 0.610
	Y	0.06 / 0.610
	Z	0.06 / 0.268
7.98	X	0.08 / 0.764
	Y	0.12 / 0.764
	Z	0.06 / 0.268
10.10	X	0.08 / 0.966
	Y	0.05 / 0.966
	Z	0.04 / 0.338
12.74	X	0.23 / 1.219
	Y	0.09 / 1.219
	Z	0.09 / 0.427
15.97	X	0.22 / 1.528
	Y	0.13 / 1.528
	Z	0.08 / 0.535
20.10	X	0.08 / 1.924
	Y	0.20 / 1.924
	Z	0.09 / 0.673
25.36	X	0.06 / 2.427
	Y	0.04 / 2.427
	Z	0.03 / 0.849
32.02	X	0.03 / 3.064
	Y	0.01 / 3.064
	Z	0.01 / 1.073
40.33	X	0.04 / 3.859
	Y	0.01 / 3.859
	Z	0.01 / 1.351
50.73	X	0.04 / 4.854
	Y	0.02 / 4.854
	Z	0.01 / 1.699
63.97	X	0.05 / 6.121
	Y	0.07 / 6.121
	Z	0.01 / 2.142
80.64	X	0.05 / 7.716
	Y	0.08 / 7.716
	Z	0.01 / 2.701



8-OCT-93 16:14:23

Course: Cross Country #2
Speed: 5 mph
Note: No Load

HSEL: Health and safety exposure limit
FDPB: Fatigue-decreased proficiency boundary
RCB: Reduced comfort boundary
RMS: Vibration R.M.S. acceleration (m/s2)

X: Longitudinal
Y: Transverse
Z: Vertical

RUN-12
Oct 4, 1993

Roadside Seat
HET Ride Quality

Exposure: 10h 0m



Course: Cross Country #2
Speed: 5 mph
Note: No Load

HSEL: Health and safety exposure limit
FDPB: Fatigue-decreased proficiency boundary
RCB: Reduced comfort boundary
RMS: Vibration R.M.S. acceleration (m/s2)

X: Longitudinal
Y: Transverse
Z: Vertical

RUN-12

Oct 4, 1993

Curbside Seat

HET Ride Quality

Exposure: 10h 0m



(Hz)		RMS / FDPB
1.20	X	0.04 / 0.191
	Y	0.06 / 0.191
	Z	0.07 / 0.488
1.61	X	0.05 / 0.191
	Y	0.05 / 0.191
	Z	0.14 / 0.422
2.02	X	0.04 / 0.194
	Y	0.03 / 0.194
	Z	0.19 / 0.377
2.53	X	0.04 / 0.242
	Y	0.03 / 0.242
	Z	0.13 / 0.337
3.14	X	0.03 / 0.300
	Y	0.02 / 0.300
	Z	0.06 / 0.302
3.94	X	0.05 / 0.377
	Y	0.03 / 0.377
	Z	0.07 / 0.270
5.05	X	0.07 / 0.484
	Y	0.06 / 0.484
	Z	0.06 / 0.268
6.37	X	0.12 / 0.610
	Y	0.07 / 0.610
	Z	0.08 / 0.268
7.98	X	0.11 / 0.764
	Y	0.11 / 0.764
	Z	0.05 / 0.268
10.10	X	0.08 / 0.966
	Y	0.12 / 0.966
	Z	0.05 / 0.338
12.74	X	0.19 / 1.219
	Y	0.16 / 1.219
	Z	0.08 / 0.427
15.97	X	0.16 / 1.528
	Y	0.14 / 1.528
	Z	0.07 / 0.535
20.10	X	0.08 / 1.924
	Y	0.09 / 1.924
	Z	0.08 / 0.673
25.36	X	0.05 / 2.427
	Y	0.03 / 2.427
	Z	0.04 / 0.849
32.02	X	0.03 / 3.064
	Y	0.01 / 3.064
	Z	0.02 / 1.073
40.33	X	0.02 / 3.859
	Y	0.02 / 3.859
	Z	0.01 / 1.351
50.73	X	0.02 / 4.854
	Y	0.01 / 4.854
	Z	0.01 / 1.699
63.97	X	0.09 / 6.121
	Y	0.24 / 6.121
	Z	0.05 / 2.142
80.64	X	0.10 / 7.716
	Y	0.29 / 7.716
	Z	0.04 / 2.701



8-OCT-93 16:14:23

Course: Cross Country #2
Speed: 5 mph
Note: No Load

HSEL: Health and safety exposure limit
FDPB: Fatigue-decreased proficiency boundary
RCB: Reduced comfort boundary
RMS: Vibration R.M.S. acceleration (m/s2)

X: Longitudinal
Y: Transverse
Z: Vertical

RUN-13

Oct 4, 1993

Driver Seat

HET Ride Quality

Exposure: 10h 0m



8-OCT-93 16:14:23

Course: Cross Country #2
Speed: 10 mph
Note: No Load

HSEL: Health and safety exposure limit
FDPB: Fatigue-decreased proficiency boundary
RCB: Reduced comfort boundary
RMS: Vibration R.M.S. acceleration (m/s2)

X: Longitudinal
Y: Transverse
Z: Vertical

RUN-13

Oct 4, 1993

Front Seat

HET Ride Quality

Exposure: 10h 0m



8-OCT-93 16:14:23

Course: Cross Country #2
Speed: 10 mph
Note: No Load

HSEL: Health and safety exposure limit
FDPB: Fatigue-decreased proficiency boundary
RCB: Reduced comfort boundary
RMS: Vibration R.M.S. acceleration (m/s2)

X: Longitudinal
Y: Transverse
Z: Vertical

RUN-13

Oct 4, 1993

Roadside Seat

HET Ride Quality

Exposure: 10h 0m



8-OCT-93 16:14:23

Course: Cross Country #2
Speed: 10 mph
Note: No Load

HSEL: Health and safety exposure limit
FDPB: Fatigue-decreased proficiency boundary
RCB: Reduced comfort boundary
RMS: Vibration R.M.S. acceleration (m/s2)

X: Longitudinal
Y: Transverse
Z: Vertical

RUN-13

Oct 4, 1993

Curbside Seat

HET Ride Quality

Exposure: 10h 0m



(Hz)		RMS / FDPB
1.20	X	0.09 / 0.191
	Y	0.18 / 0.191
	Z	0.33 / 0.488
1.61	X	0.10 / 0.191
	Y	0.10 / 0.191
	Z	0.43 / 0.422
2.02	X	0.11 / 0.194
	Y	0.06 / 0.194
	Z	0.36 / 0.377
2.53	X	0.16 / 0.242
	Y	0.07 / 0.242
	Z	0.32 / 0.337
3.14	X	0.14 / 0.300
	Y	0.07 / 0.300
	Z	0.23 / 0.302
3.94	X	0.12 / 0.377
	Y	0.10 / 0.377
	Z	0.23 / 0.270
5.05	X	0.30 / 0.484
	Y	0.19 / 0.484
	Z	0.29 / 0.268
6.37	X	0.27 / 0.610
	Y	0.28 / 0.610
	Z	0.22 / 0.268
7.98	X	0.22 / 0.764
	Y	0.28 / 0.764
	Z	0.10 / 0.268
10.10	X	0.15 / 0.966
	Y	0.17 / 0.966
	Z	0.10 / 0.338
12.74	X	0.21 / 1.219
	Y	0.15 / 1.219
	Z	0.10 / 0.427
15.97	X	0.13 / 1.528
	Y	0.14 / 1.528
	Z	0.10 / 0.535
20.10	X	0.08 / 1.924
	Y	0.08 / 1.924
	Z	0.09 / 0.673
25.36	X	0.07 / 2.427
	Y	0.05 / 2.427
	Z	0.06 / 0.849
32.02	X	0.04 / 3.064
	Y	0.03 / 3.064
	Z	0.05 / 1.073
40.33	X	0.08 / 3.859
	Y	0.05 / 3.859
	Z	0.03 / 1.361
50.73	X	0.04 / 4.854
	Y	0.02 / 4.854
	Z	0.02 / 1.699
63.97	X	0.03 / 6.121
	Y	0.03 / 6.121
	Z	0.02 / 2.142
80.64	X	0.04 / 7.716
	Y	0.10 / 7.716
	Z	0.01 / 2.701



8-OCT-93 16:14:23

Course: Cross Country #2
Speed: 10 mph
Note: No Load

HSEL: Health and safety exposure limit
FDPB: Fatigue-decreased proficiency boundary
RCB: Reduced comfort boundary
RMS: Vibration R.M.S. acceleration (m/s2)

X: Longitudinal
Y: Transverse
Z: Vertical

RUN-14

Oct 4, 1993

Driver Seat

HET Ride Quality

Exposure: 10h 0m



Course: Cross Country #2
Speed: 15 mph
Note: No Load

HSEL: Health and safety exposure limit
FDPB: Fatigue-decreased proficiency boundary
RCB: Reduced comfort boundary
RMS: Vibration R.M.S. acceleration (m/s2)

X: Longitudinal
Y: Transverse
Z: Vertical

RUN-14 **Front Seat**

Oct 4, 1993 **HET Ride Quality**

Exposure: 10h 0m



8-OCT-93 16:14:24

Course: Cross Country #2
Speed: 15 mph
Note: No Load

HSEL: Health and safety exposure limit
FDPB: Fatigue-decreased proficiency boundary
RCB: Reduced comfort boundary
RMS: Vibration R.M.S. acceleration (m/s2)

X: Longitudinal
Y: Transverse
Z: Vertical

RUN-14
Oct 4, 1993

Roadside Seat
HET Ride Quality

Exposure: 10h 0m



8-OCT-93 16:14:24

Course: Cross Country #2
Speed: 15 mph
Note: No Load

HSEL: Health and safety exposure limit
FDPB: Fatigue-decreased proficiency boundary
RCB: Reduced comfort boundary
RMS: Vibration R.M.S. acceleration (m/s2)

X: Longitudinal
Y: Transverse
Z: Vertical

RUN-14

Oct 4, 1993

Curbside Seat

HET Ride Quality

Exposure: 10h 0m



8-OCT-93 16:14:24

Course: Cross Country #2
Speed: 15 mph
Note: No Load

HSEL: Health and safety exposure limit
FDPB: Fatigue-decreased proficiency boundary
RCB: Reduced comfort boundary
RMS: Vibration R.M.S. acceleration (m/s2)

X: Longitudinal
Y: Transverse
Z: Vertical

RUN-15
Oct 4, 1993

Driver Seat
HET Ride Quality

Exposure: 10h 0m



Course: Secondary A
Speed: 15 mph
Note: No Load

HSEL: Health and safety exposure limit
FDPB: Fatigue-decreased proficiency boundary
RCB: Reduced comfort boundary
RMS: Vibration R.M.S. acceleration (m/s2)

X: Longitudinal
Y: Transverse
Z: Vertical

RUN-15

Oct 4, 1993

Front Seat

HET Ride Quality

Exposure: 10h 0m



8-OCT-93 16:14:25

Course: Secondary A
Speed: 15 mph
Note: No Load

HSEL: Health and safety exposure limit
FDPB: Fatigue-decreased proficiency boundary
RCB: Reduced comfort boundary
RMS: Vibration R.M.S. acceleration (m/s2)

X: Longitudinal
Y: Transverse
Z: Vertical

RUN-15
Oct 4, 1993

Roadside Seat
HET Ride Quality

Exposure: 10h 0m



(Hz)		RMS / FDPB
1.20	X	0.02 / 0.191
	Y	0.06 / 0.191
	Z	0.08 / 0.488
1.61	X	0.04 / 0.191
	Y	0.07 / 0.191
	Z	0.26 / 0.422
2.02	X	0.06 / 0.194
	Y	0.07 / 0.194
	Z	0.32 / 0.377
2.53	X	0.06 / 0.242
	Y	0.04 / 0.242
	Z	0.20 / 0.337
3.14	X	0.06 / 0.300
	Y	0.05 / 0.300
	Z	0.14 / 0.302
3.94	X	0.10 / 0.377
	Y	0.08 / 0.377
	Z	0.20 / 0.270
5.05	X	0.16 / 0.484
	Y	0.17 / 0.484
	Z	0.21 / 0.268
6.37	X	0.36 / 0.610
	Y	0.16 / 0.610
	Z	0.20 / 0.268
7.98	X	0.35 / 0.764
	Y	0.43 / 0.764
	Z	0.18 / 0.268
10.10	X	0.24 / 0.966
	Y	0.24 / 0.966
	Z	0.12 / 0.338
12.74	X	0.24 / 1.219
	Y	0.16 / 1.219
	Z	0.12 / 0.427
15.97	X	0.12 / 1.528
	Y	0.11 / 1.528
	Z	0.09 / 0.536
20.10	X	0.06 / 1.924
	Y	0.07 / 1.924
	Z	0.07 / 0.673
25.36	X	0.10 / 2.427
	Y	0.13 / 2.427
	Z	0.10 / 0.849
32.02	X	0.04 / 3.064
	Y	0.04 / 3.064
	Z	0.03 / 1.073
40.33	X	0.03 / 3.859
	Y	0.02 / 3.859
	Z	0.01 / 1.351
50.73	X	0.03 / 4.854
	Y	0.02 / 4.854
	Z	0.01 / 1.699
63.97	X	0.02 / 6.121
	Y	0.03 / 6.121
	Z	0.00 / 2.142
80.64	X	0.02 / 7.716
	Y	0.05 / 7.716
	Z	0.00 / 2.701



8-OCT-93 16:14:25

Course: Secondary A
Speed: 15 mph
Note: No Load

HSEL: Health and safety exposure limit
FDPB: Fatigue-decreased proficiency boundary
RCB: Reduced comfort boundary
RMS: Vibration R.M.S. acceleration (m/s2)

X: Longitudinal
Y: Transverse
Z: Vertical

RUN-15
Oct 4, 1993

Curbside Seat
HET Ride Quality

Exposure: 10h 0m



8-OCT-93 16:14:25

Course: Secondary A
Speed: 15 mph
Note: No Load

HSEL: Health and safety exposure limit
FDPB: Fatigue-decreased proficiency boundary
RCB: Reduced comfort boundary
RMS: Vibration R.M.S. acceleration (m/s2)

X: Longitudinal
Y: Transverse
Z: Vertical

RUN-16

Oct 4, 1993

Driver Seat

HET Ride Quality

Exposure: 10h 0m



Course: Secondary A
Speed: 20 mph
Note: No Load

HSEL: Health and safety exposure limit
FDPB: Fatigue-decreased proficiency boundary
RCB: Reduced comfort boundary
RMS: Vibration R.M.S. acceleration (m/s2)

X: Longitudinal
Y: Transverse
Z: Vertical

RUN-16 **Front Seat**

Oct 4, 1993 **HET Ride Quality**

Exposure: 10h 0m



(Hz)		RMS / FDPB
1.20	X	0.08 / 0.191
	Y	0.15 / 0.191
	Z	0.25 / 0.488
1.61	X	0.06 / 0.191
	Y	0.14 / 0.191
	Z	0.42 / 0.422
2.02	X	0.09 / 0.194
	Y	0.11 / 0.194
	Z	0.49 / 0.377
2.53	X	0.09 / 0.242
	Y	0.14 / 0.242
	Z	0.59 / 0.337
3.14	X	0.05 / 0.300
	Y	0.10 / 0.300
	Z	0.29 / 0.302
3.94	X	0.09 / 0.377
	Y	0.14 / 0.377
	Z	0.23 / 0.270
5.05	X	0.25 / 0.484
	Y	0.15 / 0.484
	Z	0.17 / 0.268
6.37	X	0.26 / 0.610
	Y	0.25 / 0.610
	Z	0.17 / 0.268
7.98	X	0.35 / 0.764
	Y	0.36 / 0.764
	Z	0.17 / 0.268
10.10	X	0.36 / 0.966
	Y	0.13 / 0.966
	Z	0.16 / 0.338
12.74	X	0.34 / 1.219
	Y	0.12 / 1.219
	Z	0.13 / 0.427
15.97	X	0.14 / 1.528
	Y	0.22 / 1.528
	Z	0.10 / 0.535
20.10	X	0.10 / 1.924
	Y	0.17 / 1.924
	Z	0.06 / 0.673
25.36	X	0.09 / 2.427
	Y	0.04 / 2.427
	Z	0.04 / 0.849
32.02	X	0.14 / 3.064
	Y	0.05 / 3.064
	Z	0.04 / 1.073
40.33	X	0.08 / 3.859
	Y	0.03 / 3.859
	Z	0.02 / 1.351
50.73	X	0.07 / 4.854
	Y	0.04 / 4.854
	Z	0.01 / 1.699
63.97	X	0.06 / 6.121
	Y	0.07 / 6.121
	Z	0.00 / 2.142
80.64	X	0.04 / 7.716
	Y	0.04 / 7.716
	Z	0.00 / 2.701



8-OCT-93 16:14:26

Course: Secondary A
Speed: 20 mph
Note: No Load

HSEL: Health and safety exposure limit
FDPB: Fatigue-decreased proficiency boundary
RCB: Reduced comfort boundary
RMS: Vibration R.M.S. acceleration (m/s2)

X: Longitudinal
Y: Transverse
Z: Vertical

RUN-16

Oct 4, 1993

Roadside Seat

HET Ride Quality

Exposure: 10h 0m



(Hz)		RMS / FDPB
1.20	X	0.08 / 0.191
	Y	0.13 / 0.191
	Z	0.23 / 0.488
1.61	X	0.05 / 0.191
	Y	0.12 / 0.191
	Z	0.36 / 0.422
2.02	X	0.10 / 0.194
	Y	0.09 / 0.194
	Z	0.36 / 0.377
2.53	X	0.12 / 0.242
	Y	0.10 / 0.242
	Z	0.41 / 0.337
3.14	X	0.06 / 0.300
	Y	0.07 / 0.300
	Z	0.23 / 0.302
3.94	X	0.14 / 0.377
	Y	0.13 / 0.377
	Z	0.25 / 0.270
5.05	X	0.46 / 0.484
	Y	0.21 / 0.484
	Z	0.36 / 0.268
6.37	X	0.43 / 0.610
	Y	0.31 / 0.610
	Z	0.28 / 0.268
7.98	X	0.42 / 0.764
	Y	0.47 / 0.764
	Z	0.21 / 0.268
10.10	X	0.43 / 0.966
	Y	0.36 / 0.966
	Z	0.15 / 0.338
12.74	X	0.35 / 1.219
	Y	0.23 / 1.219
	Z	0.17 / 0.427
15.97	X	0.16 / 1.528
	Y	0.16 / 1.528
	Z	0.14 / 0.535
20.10	X	0.08 / 1.924
	Y	0.11 / 1.924
	Z	0.10 / 0.673
25.36	X	0.06 / 2.427
	Y	0.06 / 2.427
	Z	0.07 / 0.849
32.02	X	0.10 / 3.064
	Y	0.14 / 3.064
	Z	0.08 / 1.073
40.33	X	0.04 / 3.859
	Y	0.04 / 3.859
	Z	0.02 / 1.351
50.73	X	0.03 / 4.854
	Y	0.02 / 4.854
	Z	0.01 / 1.699
63.97	X	0.07 / 6.121
	Y	0.13 / 6.121
	Z	0.02 / 2.142
80.64	X	0.03 / 7.716
	Y	0.03 / 7.716
	Z	0.01 / 2.701



8-OCT-93 16:14:26

Course: Secondary A
Speed: 20 mph
Note: No Load

HSEL: Health and safety exposure limit
FDPB: Fatigue-decreased proficiency boundary
RCB: Reduced comfort boundary
RMS: Vibration R.M.S. acceleration (m/s2)

X: Longitudinal
Y: Transverse
Z: Vertical

RUN-16

Oct 4, 1993

Curbside Seat

HET Ride Quality

Exposure: 10h 0m



Course: Secondary A
Speed: 20 mph
Note: No Load

HSEL: Health and safety exposure limit
FDPB: Fatigue-decreased proficiency boundary
RCB: Reduced comfort boundary
RMS: Vibration R.M.S. acceleration (m/s2)

X: Longitudinal
Y: Transverse
Z: Vertical

RUN-17

Oct 4, 1993

Driver Seat

HET Ride Quality

Exposure: 10h 0m



Course: Secondary A
Speed: 25 mph
Note: No Load

HSEL: Health and safety exposure limit
FDPB: Fatigue-decreased proficiency boundary
RCB: Reduced comfort boundary
RMS: Vibration R.M.S. acceleration (m/s2)

X: Longitudinal
Y: Transverse
Z: Vertical

RUN-17

Oct 4, 1993

Front Seat

HET Ride Quality

Exposure: 10h 0m



Course: Secondary A
Speed: 25 mph
Note: No Load

HSEL: Health and safety exposure limit
FDPB: Fatigue-decreased proficiency boundary
RCB: Reduced comfort boundary
RMS: Vibration R.M.S. acceleration (m/s2)

X: Longitudinal
Y: Transverse
Z: Vertical

RUN-17
Oct 4, 1993

Roadside Seat
HET Ride Quality

Exposure: 10h 0m



Course: Secondary A
Speed: 25 mph
Note: No Load

HSEL: Health and safety exposure limit
FDPB: Fatigue-decreased proficiency boundary
RCB: Reduced comfort boundary
RMS: Vibration R.M.S. acceleration (m/s2)

X: Longitudinal
Y: Transverse
Z: Vertical

RUN-17
Oct 4, 1993

Curbside Seat
HET Ride Quality

Exposure: 10h 0m



(Hz)		RMS / FDPB
1.20	X	0.07 / 0.191
	Y	0.10 / 0.191
	Z	0.19 / 0.488
1.61	X	0.05 / 0.191
	Y	0.09 / 0.191
	Z	0.36 / 0.422
2.02	X	0.06 / 0.194
	Y	0.06 / 0.194
	Z	0.37 / 0.377
2.53	X	0.12 / 0.242
	Y	0.06 / 0.242
	Z	0.32 / 0.337
3.14	X	0.08 / 0.300
	Y	0.07 / 0.300
	Z	0.30 / 0.302
3.94	X	0.08 / 0.377
	Y	0.07 / 0.377
	Z	0.17 / 0.270
5.05	X	0.31 / 0.484
	Y	0.18 / 0.484
	Z	0.21 / 0.268
6.37	X	0.43 / 0.610
	Y	0.29 / 0.610
	Z	0.27 / 0.268
7.98	X	0.36 / 0.764
	Y	0.30 / 0.764
	Z	0.15 / 0.268
10.10	X	0.37 / 0.966
	Y	0.30 / 0.966
	Z	0.15 / 0.338
12.74	X	0.38 / 1.219
	Y	0.32 / 1.219
	Z	0.19 / 0.427
15.97	X	0.15 / 1.528
	Y	0.21 / 1.528
	Z	0.16 / 0.535
20.10	X	0.08 / 1.924
	Y	0.12 / 1.924
	Z	0.11 / 0.673
25.36	X	0.07 / 2.427
	Y	0.07 / 2.427
	Z	0.08 / 0.849
32.02	X	0.05 / 3.064
	Y	0.04 / 3.064
	Z	0.07 / 1.073
40.33	X	0.06 / 3.859
	Y	0.12 / 3.859
	Z	0.04 / 1.351
50.73	X	0.03 / 4.854
	Y	0.03 / 4.854
	Z	0.02 / 1.699
63.97	X	0.04 / 6.121
	Y	0.06 / 6.121
	Z	0.02 / 2.142
80.64	X	0.03 / 7.716
	Y	0.10 / 7.716
	Z	0.03 / 2.701



8-OCT-93 16:14:27

Course: Secondary A
Speed: 25 mph
Note: No Load

HSEL: Health and safety exposure limit
FDPB: Fatigue-decreased proficiency boundary
RCB: Reduced comfort boundary
RMS: Vibration R.M.S. acceleration (m/s2)

X: Longitudinal
Y: Transverse
Z: Vertical

RUN-18

Oct 4, 1993

Driver Seat

HET Ride Quality

Exposure: 10h 0m



8-OCT-93 16:14:27

Course: Secondary A
Speed: 30 mph
Note: No Load

HSEL: Health and safety exposure limit
FDPB: Fatigue-decreased proficiency boundary
RCB: Reduced comfort boundary
RMS: Vibration R.M.S. acceleration (m/s2)

X: Longitudinal
Y: Transverse
Z: Vertical

RUN-18

Oct 4, 1993

Front Seat

HET Ride Quality

Exposure: 10h 0m



8-OCT-93 16:14:27

Course: Secondary A
Speed: 30 mph
Note: No Load

HSEL: Health and safety exposure limit
FDPB: Fatigue-decreased proficiency boundary
RCB: Reduced comfort boundary
RMS: Vibration R.M.S. acceleration (m/s2)

X: Longitudinal
Y: Transverse
Z: Vertical

RUN-18 — **Roadside Seat**

Oct 4, 1993 — **HET Ride Quality**

Exposure: 10h 0m



(Hz)		RMS / FDPB
1.20	X	0.07 / 0.191
	Y	0.13 / 0.191
	Z	0.21 / 0.488
1.61	X	0.08 / 0.191
	Y	0.11 / 0.191
	Z	0.32 / 0.422
2.02	X	0.06 / 0.194
	Y	0.08 / 0.194
	Z	0.37 / 0.377
2.53	X	0.06 / 0.242
	Y	0.06 / 0.242
	Z	0.29 / 0.337
3.14	X	0.08 / 0.300
	Y	0.11 / 0.300
	Z	0.28 / 0.302
3.94	X	0.11 / 0.377
	Y	0.15 / 0.377
	Z	0.31 / 0.270
5.05	X	0.24 / 0.484
	Y	0.20 / 0.484
	Z	0.22 / 0.268
6.37	X	0.47 / 0.610
	Y	0.31 / 0.610
	Z	0.28 / 0.268
7.98	X	0.41 / 0.764
	Y	0.56 / 0.764
	Z	0.25 / 0.268
10.10	X	0.45 / 0.966
	Y	0.31 / 0.966
	Z	0.14 / 0.338
12.74	X	0.38 / 1.219
	Y	0.20 / 1.219
	Z	0.17 / 0.427
15.97	X	0.20 / 1.528
	Y	0.22 / 1.528
	Z	0.19 / 0.535
20.10	X	0.10 / 1.924
	Y	0.13 / 1.924
	Z	0.12 / 0.673
25.36	X	0.09 / 2.427
	Y	0.11 / 2.427
	Z	0.09 / 0.849
32.02	X	0.05 / 3.064
	Y	0.06 / 3.064
	Z	0.05 / 1.073
40.33	X	0.04 / 3.859
	Y	0.07 / 3.859
	Z	0.02 / 1.351
50.73	X	0.04 / 4.854
	Y	0.05 / 4.854
	Z	0.02 / 1.699
63.97	X	0.05 / 6.121
	Y	0.11 / 6.121
	Z	0.02 / 2.142
80.64	X	0.04 / 7.716
	Y	0.06 / 7.716
	Z	0.01 / 2.701



8-OCT-93 16:14:27

Course: Secondary A
Speed: 30 mph
Note: No Load

HSEL: Health and safety exposure limit
FDPB: Fatigue-decreased proficiency boundary
RCB: Reduced comfort boundary
RMS: Vibration R.M.S. acceleration (m/s2)

X: Longitudinal
Y: Transverse
Z: Vertical

RUN-18

Oct 4, 1993

Curbside Seat

HET Ride Quality

Exposure: 10h 0m



8-OCT-93 16:14:27

Course: Secondary A
Speed: 30 mph
Note: No Load

HSEL: Health and safety exposure limit
FDPB: Fatigue-decreased proficiency boundary
RCB: Reduced comfort boundary
RMS: Vibration R.M.S. acceleration (m/s2)

X: Longitudinal
Y: Transverse
Z: Vertical

RUN-19

Oct 4, 1993

Driver Seat

HET Ride Quality

Exposure: 10h 0m



Course: Paved
Speed: 25 mph
Note: No Load

HSEL: Health and safety exposure limit
FDPB: Fatigue-decreased proficiency boundary
RCB: Reduced comfort boundary
RMS: Vibration R.M.S. acceleration (m/s2)

X: Longitudinal
Y: Transverse
Z: Vertical

RUN-19

Oct 4, 1993

Front Seat

HET Ride Quality

Exposure: 10h 0m



(Hz)		RMS / FDPB
1.20	X	0.02 / 0.191
	Y	0.03 / 0.191
	Z	0.05 / 0.488
1.61	X	0.02 / 0.191
	Y	0.03 / 0.191
	Z	0.13 / 0.422
2.02	X	0.02 / 0.194
	Y	0.03 / 0.194
	Z	0.22 / 0.377
2.53	X	0.05 / 0.242
	Y	0.07 / 0.242
	Z	0.28 / 0.337
3.14	X	0.06 / 0.300
	Y	0.13 / 0.300
	Z	0.43 / 0.302
3.94	X	0.02 / 0.377
	Y	0.04 / 0.377
	Z	0.09 / 0.270
5.05	X	0.10 / 0.484
	Y	0.05 / 0.484
	Z	0.07 / 0.268
6.37	X	0.15 / 0.610
	Y	0.11 / 0.610
	Z	0.13 / 0.268
7.98	X	0.11 / 0.764
	Y	0.12 / 0.764
	Z	0.08 / 0.268
10.10	X	0.12 / 0.966
	Y	0.08 / 0.966
	Z	0.08 / 0.338
12.74	X	0.17 / 1.219
	Y	0.05 / 1.219
	Z	0.07 / 0.427
15.97	X	0.06 / 1.528
	Y	0.10 / 1.528
	Z	0.04 / 0.535
20.10	X	0.06 / 1.924
	Y	0.13 / 1.924
	Z	0.05 / 0.673
25.36	X	0.04 / 2.427
	Y	0.04 / 2.427
	Z	0.03 / 0.849
32.02	X	0.03 / 3.064
	Y	0.02 / 3.064
	Z	0.02 / 1.073
40.33	X	0.11 / 3.859
	Y	0.02 / 3.859
	Z	0.01 / 1.351
50.73	X	0.05 / 4.854
	Y	0.01 / 4.854
	Z	0.00 / 1.699
63.97	X	0.07 / 6.121
	Y	0.04 / 6.121
	Z	0.02 / 2.142
80.64	X	0.04 / 7.716
	Y	0.04 / 7.716
	Z	0.01 / 2.701



8-OCT-93 16:14:28

Course: Paved
Speed: 25 mph
Note: No Load

HSEL: Health and safety exposure limit
FDPB: Fatigue-decreased proficiency boundary
RCB: Reduced comfort boundary
RMS: Vibration R.M.S. acceleration (m/s2)

X: Longitudinal
Y: Transverse
Z: Vertical

RUN-19

Oct 4, 1993

Roadside Seat

HET Ride Quality

Exposure: 10h 0m



8-OCT-93 16:14:28

Course: Paved
Speed: 25 mph
Note: No Load

HSEL: Health and safety exposure limit
FDPB: Fatigue-decreased proficiency boundary
RCB: Reduced comfort boundary
RMS: Vibration R.M.S. acceleration (m/s2)

X: Longitudinal
Y: Transverse
Z: Vertical

RUN-19
Oct 4, 1993

Curbside Seat
HET Ride Quality

Exposure: 10h 0m



(Hz)		RMS / FDPB
1.20	X	0.02 / 0.191
	Y	0.02 / 0.191
	Z	0.04 / 0.488
1.61	X	0.02 / 0.191
	Y	0.02 / 0.191
	Z	0.12 / 0.422
2.02	X	0.02 / 0.194
	Y	0.02 / 0.194
	Z	0.20 / 0.377
2.53	X	0.08 / 0.242
	Y	0.03 / 0.242
	Z	0.21 / 0.337
3.14	X	0.09 / 0.300
	Y	0.04 / 0.300
	Z	0.30 / 0.302
3.94	X	0.02 / 0.377
	Y	0.02 / 0.377
	Z	0.08 / 0.270
5.05	X	0.21 / 0.484
	Y	0.09 / 0.484
	Z	0.12 / 0.268
6.37	X	0.30 / 0.610
	Y	0.16 / 0.610
	Z	0.17 / 0.268
7.98	X	0.15 / 0.764
	Y	0.11 / 0.764
	Z	0.07 / 0.268
10.10	X	0.12 / 0.966
	Y	0.10 / 0.966
	Z	0.06 / 0.338
12.74	X	0.14 / 1.219
	Y	0.14 / 1.219
	Z	0.07 / 0.427
15.97	X	0.05 / 1.528
	Y	0.06 / 1.528
	Z	0.05 / 0.535
20.10	X	0.05 / 1.924
	Y	0.11 / 1.924
	Z	0.06 / 0.673
25.36	X	0.04 / 2.427
	Y	0.06 / 2.427
	Z	0.05 / 0.849
32.02	X	0.04 / 3.064
	Y	0.03 / 3.064
	Z	0.04 / 1.073
40.33	X	0.04 / 3.859
	Y	0.10 / 3.859
	Z	0.02 / 1.351
50.73	X	0.03 / 4.854
	Y	0.03 / 4.854
	Z	0.02 / 1.699
63.97	X	0.04 / 6.121
	Y	0.04 / 6.121
	Z	0.02 / 2.142
80.64	X	0.04 / 7.716
	Y	0.10 / 7.716
	Z	0.03 / 2.701

8-OCT-93 16:14:28



Course: Paved
Speed: 25 mph
Note: No Load

HSEL: Health and safety exposure limit
FDPB: Fatigue-decreased proficiency boundary
RCB: Reduced comfort boundary
RMS: Vibration R.M.S. acceleration (m/s2)

X: Longitudinal
Y: Transverse
Z: Vertical

RUN-20

Oct 4, 1993

Driver Seat

HET Ride Quality

Exposure: 10h 0m



8-OCT-93 16:14:29

Course: Paved
Speed: 30 mph
Note: No Load

HSEL: Health and safety exposure limit
FDPB: Fatigue-decreased proficiency boundary
RCB: Reduced comfort boundary
RMS: Vibration R.M.S. acceleration (m/s2)

X: Longitudinal
Y: Transverse
Z: Vertical

RUN-20
Oct 4, 1993

Front Seat
HET Ride Quality

Exposure: 10h 0m



(Hz)		RMS / FDPB
1.20	X	0.02 / 0.191
	Y	0.02 / 0.191
	Z	0.06 / 0.488
1.61	X	0.02 / 0.191
	Y	0.03 / 0.191
	Z	0.10 / 0.422
2.02	X	0.02 / 0.194
	Y	0.03 / 0.194
	Z	0.18 / 0.377
2.53	X	0.02 / 0.242
	Y	0.02 / 0.242
	Z	0.16 / 0.337
3.14	X	0.05 / 0.300
	Y	0.08 / 0.300
	Z	0.28 / 0.302
3.94	X	0.08 / 0.377
	Y	0.19 / 0.377
	Z	0.59 / 0.270
5.05	X	0.03 / 0.484
	Y	0.03 / 0.484
	Z	0.05 / 0.268
6.37	X	0.18 / 0.610
	Y	0.11 / 0.610
	Z	0.09 / 0.268
7.98	X	0.15 / 0.764
	Y	0.27 / 0.764
	Z	0.13 / 0.268
10.10	X	0.16 / 0.966
	Y	0.07 / 0.966
	Z	0.06 / 0.338
12.74	X	0.15 / 1.219
	Y	0.04 / 1.219
	Z	0.05 / 0.427
15.97	X	0.09 / 1.528
	Y	0.09 / 1.528
	Z	0.06 / 0.535
20.10	X	0.05 / 1.924
	Y	0.09 / 1.924
	Z	0.04 / 0.673
25.36	X	0.08 / 2.427
	Y	0.05 / 2.427
	Z	0.03 / 0.849
32.02	X	0.05 / 3.064
	Y	0.02 / 3.064
	Z	0.02 / 1.073
40.33	X	0.04 / 3.859
	Y	0.01 / 3.859
	Z	0.01 / 1.351
50.73	X	0.10 / 4.854
	Y	0.02 / 4.854
	Z	0.02 / 1.699
63.97	X	0.04 / 6.121
	Y	0.05 / 6.121
	Z	0.00 / 2.142
80.64	X	0.03 / 7.716
	Y	0.04 / 7.716
	Z	0.00 / 2.701



8-OCT-93 16:14:29

Course: Paved
Speed: 30 mph
Note: No Load

HSEL: Health and safety exposure limit
FDPB: Fatigue-decreased proficiency boundary
RCB: Reduced comfort boundary
RMS: Vibration R.M.S. acceleration (m/s2)

X: Longitudinal
Y: Transverse
Z: Vertical

RUN-20

Oct 4, 1993

Roadside Seat

HET Ride Quality

Exposure: 10h 0m



8-OCT-93 16:14:29

Course: Paved
Speed: 30 mph
Note: No Load

HSEL: Health and safety exposure limit
FDPB: Fatigue-decreased proficiency boundary
RCB: Reduced comfort boundary
RMS: Vibration R.M.S. acceleration (m/s2)

X: Longitudinal
Y: Transverse
Z: Vertical

RUN-20

Oct 4, 1993

Curbside Seat

HET Ride Quality

Exposure: 10h 0m



8-OCT-93 16:14:29

Course: Paved
Speed: 30 mph
Note: No Load

HSEL: Health and safety exposure limit
FDPB: Fatigue-decreased proficiency boundary
RCB: Reduced comfort boundary
RMS: Vibration R.M.S. acceleration (m/s2)

X: Longitudinal
Y: Transverse
Z: Vertical

RUN-21

Oct 4, 1993

Driver Seat

HET Ride Quality

Exposure: 10h 0m



8-OCT-93 16:14:30

Course: Paved
Speed: 35 mph
Note: No Load

HSEL: Health and safety exposure limit
FDPB: Fatigue-decreased proficiency boundary
RCB: Reduced comfort boundary
RMS: Vibration R.M.S. acceleration (m/s2)

X: Longitudinal
Y: Transverse
Z: Vertical

RUN-21

Oct 4, 1993

Front Seat

HET Ride Quality

Exposure: 10h 0m



8-OCT-93 16:14:30

Course: Paved
Speed: 35 mph
Note: No Load

HSEL: Health and safety exposure limit
FDPB: Fatigue-decreased proficiency boundary
RCB: Reduced comfort boundary
RMS: Vibration R.M.S. acceleration (m/s2)

X: Longitudinal
Y: Transverse
Z: Vertical

RUN-21

Oct 4, 1993

Roadside Seat

HET Ride Quality

Exposure: 10h 0m



Course: Paved
Speed: 35 mph
Note: No Load

HSEL: Health and safety exposure limit
FDPB: Fatigue-decreased proficiency boundary
RCB: Reduced comfort boundary
RMS: Vibration R.M.S. acceleration (m/s2)

X: Longitudinal
Y: Transverse
Z: Vertical

RUN-21

Oct 4, 1993

Curbside Seat

HET Ride Quality

Exposure: 10h 0m



8-OCT-93 16:14:30

Course: Paved
Speed: 35 mph
Note: No Load

HSEL: Health and safety exposure limit
FDPB: Fatigue-decreased proficiency boundary
RCB: Reduced comfort boundary
RMS: Vibration R.M.S. acceleration (m/s2)

X: Longitudinal
Y: Transverse
Z: Vertical

RUN-22

Oct 4, 1993

Driver Seat

HET Ride Quality

Exposure: 10h 0m



8-OCT-93 16:14:30

Course: Paved
Speed: 40 mph
Note: No Load

HSEL: Health and safety exposure limit
FDPB: Fatigue-decreased proficiency boundary
RCB: Reduced comfort boundary
RMS: Vibration R.M.S. acceleration (m/s2)

X: Longitudinal
Y: Transverse
Z: Vertical

RUN-22

Oct 4, 1993

Front Seat

HET Ride Quality

Exposure: 10h 0m



8-OCT-93 16:14:30

Course: Paved
Speed: 40 mph
Note: No Load

HSEL: Health and safety exposure limit
FDPB: Fatigue-decreased proficiency boundary
RCB: Reduced comfort boundary
RMS: Vibration R.M.S. acceleration (m/s2)

X: Longitudinal
Y: Transverse
Z: Vertical

RUN-22

Oct 4, 1993

Roadside Seat

HET Ride Quality

Exposure: 10h 0m



8-OCT-93 16:14:30

Course: Paved
Speed: 40 mph
Note: No Load

HSEL: Health and safety exposure limit
FDPB: Fatigue-decreased proficiency boundary
RCB: Reduced comfort boundary
RMS: Vibration R.M.S. acceleration (m/s2)

X: Longitudinal
Y: Transverse
Z: Vertical

RUN-22

Oct 4, 1993

Curbside Seat

HET Ride Quality

Exposure: 10h 0m



8-OCT-93 16:14:30

Course: Paved
Speed: 40 mph
Note: No Load

HSEL: Health and safety exposure limit
FDPB: Fatigue-decreased proficiency boundary
RCB: Reduced comfort boundary
RMS: Vibration R.M.S. acceleration (m/s2)

X: Longitudinal
Y: Transverse
Z: Vertical

RUN-23

Oct 4, 1993

Driver Seat

HET Ride Quality

Exposure: 10h 0m



(Hz)		RMS / FDPB
1.20	X	0.03 / 0.191
	Y	0.03 / 0.191
	Z	0.09 / 0.488
1.61	X	0.04 / 0.191
	Y	0.04 / 0.191
	Z	0.21 / 0.422
2.02	X	0.07 / 0.194
	Y	0.07 / 0.194
	Z	0.27 / 0.377
2.53	X	0.08 / 0.242
	Y	0.06 / 0.242
	Z	0.37 / 0.337
3.14	X	0.04 / 0.300
	Y	0.03 / 0.300
	Z	0.20 / 0.302
3.94	X	0.06 / 0.377
	Y	0.06 / 0.377
	Z	0.12 / 0.270
5.05	X	0.16 / 0.484
	Y	0.18 / 0.484
	Z	0.19 / 0.268
6.37	X	0.10 / 0.610
	Y	0.05 / 0.610
	Z	0.06 / 0.268
7.98	X	0.15 / 0.764
	Y	0.12 / 0.764
	Z	0.08 / 0.268
10.10	X	0.20 / 0.966
	Y	0.12 / 0.966
	Z	0.09 / 0.338
12.74	X	0.13 / 1.219
	Y	0.04 / 1.219
	Z	0.06 / 0.427
15.97	X	0.08 / 1.528
	Y	0.05 / 1.528
	Z	0.05 / 0.535
20.10	X	0.07 / 1.924
	Y	0.10 / 1.924
	Z	0.05 / 0.673
25.36	X	0.08 / 2.427
	Y	0.07 / 2.427
	Z	0.04 / 0.849
32.02	X	0.04 / 3.064
	Y	0.03 / 3.064
	Z	0.02 / 1.073
40.33	X	0.07 / 3.859
	Y	0.06 / 3.859
	Z	0.03 / 1.351
50.73	X	0.03 / 4.854
	Y	0.02 / 4.854
	Z	0.01 / 1.699
63.97	X	0.04 / 6.121
	Y	0.02 / 6.121
	Z	0.01 / 2.142
80.64	X	0.05 / 7.716
	Y	0.03 / 7.716
	Z	0.01 / 2.701



8-OCT-93 16:37:52

Course: Paved
Speed: 99 mph
Note: No Load

HSEL: Health and safety exposure limit
FDPB: Fatigue-decreased proficiency boundary
RCB: Reduced comfort boundary
RMS: Vibration R.M.S. acceleration (m/s2)

X: Longitudinal
Y: Transverse
Z: Vertical

RUN-23

Oct 4, 1993

Front Seat

HET Ride Quality

Exposure: 10h 0m



(Hz)		RMS / FDPB
1.20	X	0.02 / 0.191
	Y	0.04 / 0.191
	Z	0.09 / 0.488
1.61	X	0.02 / 0.191
	Y	0.03 / 0.191
	Z	0.19 / 0.422
2.02	X	0.04 / 0.194
	Y	0.03 / 0.194
	Z	0.30 / 0.377
2.53	X	0.05 / 0.242
	Y	0.04 / 0.242
	Z	0.38 / 0.337
3.14	X	0.03 / 0.300
	Y	0.03 / 0.300
	Z	0.19 / 0.302
3.94	X	0.03 / 0.377
	Y	0.06 / 0.377
	Z	0.15 / 0.270
5.05	X	0.16 / 0.484
	Y	0.22 / 0.484
	Z	0.37 / 0.268
6.37	X	0.08 / 0.610
	Y	0.06 / 0.610
	Z	0.07 / 0.268
7.98	X	0.13 / 0.764
	Y	0.13 / 0.764
	Z	0.07 / 0.268
10.10	X	0.21 / 0.966
	Y	0.10 / 0.966
	Z	0.14 / 0.338
12.74	X	0.18 / 1.219
	Y	0.04 / 1.219
	Z	0.06 / 0.427
15.97	X	0.10 / 1.528
	Y	0.09 / 1.528
	Z	0.07 / 0.535
20.10	X	0.04 / 1.924
	Y	0.09 / 1.924
	Z	0.04 / 0.673
25.36	X	0.05 / 2.427
	Y	0.03 / 2.427
	Z	0.03 / 0.849
32.02	X	0.04 / 3.064
	Y	0.01 / 3.064
	Z	0.02 / 1.073
40.33	X	0.08 / 3.859
	Y	0.02 / 3.859
	Z	0.02 / 1.351
50.73	X	0.05 / 4.854
	Y	0.01 / 4.854
	Z	0.01 / 1.699
63.97	X	0.04 / 6.121
	Y	0.03 / 6.121
	Z	0.00 / 2.142
80.64	X	0.05 / 7.716
	Y	0.03 / 7.716
	Z	0.00 / 2.701

8-OCT-93 16:37:52

Course: Paved
Speed: 99 mph
Note: No Load

HSEL: Health and safety exposure limit
FDPB: Fatigue-decreased proficiency boundary
RCB: Reduced comfort boundary
RMS: Vibration R.M.S. acceleration (m/s2)

X: Longitudinal
Y: Transverse
Z: Vertical

RUN-23
Oct 4, 1993

Roadside Seat
HET Ride Quality

Exposure: 10h 0m



(Hz)		RMS / FDPB
1.20	X	0.03 / 0.191
	Y	0.04 / 0.191
	Z	0.07 / 0.488
1.61	X	0.03 / 0.191
	Y	0.02 / 0.191
	Z	0.17 / 0.422
2.02	X	0.07 / 0.194
	Y	0.03 / 0.194
	Z	0.21 / 0.377
2.53	X	0.09 / 0.242
	Y	0.03 / 0.242
	Z	0.22 / 0.337
3.14	X	0.03 / 0.300
	Y	0.02 / 0.300
	Z	0.13 / 0.302
3.94	X	0.07 / 0.377
	Y	0.04 / 0.377
	Z	0.16 / 0.270
5.05	X	0.20 / 0.484
	Y	0.24 / 0.484
	Z	0.33 / 0.268
6.37	X	0.17 / 0.610
	Y	0.07 / 0.610
	Z	0.09 / 0.268
7.98	X	0.20 / 0.764
	Y	0.17 / 0.764
	Z	0.14 / 0.268
10.10	X	0.24 / 0.966
	Y	0.19 / 0.966
	Z	0.13 / 0.338
12.74	X	0.15 / 1.219
	Y	0.06 / 1.219
	Z	0.08 / 0.427
15.97	X	0.07 / 1.528
	Y	0.07 / 1.528
	Z	0.08 / 0.536
20.10	X	0.04 / 1.924
	Y	0.06 / 1.924
	Z	0.06 / 0.673
25.36	X	0.04 / 2.427
	Y	0.05 / 2.427
	Z	0.04 / 0.849
32.02	X	0.03 / 3.064
	Y	0.03 / 3.064
	Z	0.02 / 1.073
40.33	X	0.07 / 3.859
	Y	0.09 / 3.859
	Z	0.04 / 1.351
50.73	X	0.02 / 4.864
	Y	0.02 / 4.864
	Z	0.01 / 1.699
63.97	X	0.02 / 6.121
	Y	0.03 / 6.121
	Z	0.00 / 2.142
80.64	X	0.04 / 7.716
	Y	0.07 / 7.716
	Z	0.02 / 2.701



8-OCT-93 16:37:52

Course: Paved
Speed: 99 mph
Note: No Load

HSEL: Health and safety exposure limit
FDPB: Fatigue-decreased proficiency boundary
RCB: Reduced comfort boundary
RMS: Vibration R.M.S. acceleration (m/s2)

X: Longitudinal
Y: Transverse
Z: Vertical

RUN-23

Oct 4, 1993

Curbside Seat

HET Ride Quality

Exposure: 10h 0m



8-OCT-93 16:37:52

Course: Paved
Speed: 99 mph
Note: No Load